



XYLENE V703

Features

- Xylene
- Suitable For Use In USDA Inspected Facilities

General Description

Xylene is an aromatic solvent that can be used in numerous industrial coatings systems as a general thinner and clean-up solvent. Use to modify evaporation rates and improve dry. For effective cleaning of tools and equipment.

Recommended For

Use to modify evaporation rates and modify dry. For effective cleaning of tools and equipment. May be used to reduce and thin coatings up to the legal limits allowed by local regulations.

Limitations

Product Information																																																			
<p>Colors — Standard: N/A</p> <p>— Tint Bases: N/A</p> <p>— Special Colors: N/A</p> <p>Certification & Qualifications: The product supported by this data sheet is regulated by consumer product VOC rules, in some areas, as a paint thinner, multi-purpose solvent. It also does not apply to LEED (Leadership in Energy and Environmental Design) standards. Suitable for Use in USDA Inspected Facilities</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>VOC REGION</th> <th>COMPLIANT</th> </tr> </thead> <tbody> <tr> <td>FEDERAL</td> <td>YES</td> </tr> <tr> <td>OTC</td> <td>NO</td> </tr> <tr> <td>OTCII</td> <td>NO</td> </tr> <tr> <td>CARB</td> <td>NO</td> </tr> <tr> <td>CARB07</td> <td>NO</td> </tr> <tr> <td>UTAH</td> <td>NO</td> </tr> <tr> <td>AZMC</td> <td>NO</td> </tr> <tr> <td>SCAQMD</td> <td>NO</td> </tr> </tbody> </table>	VOC REGION	COMPLIANT	FEDERAL	YES	OTC	NO	OTCII	NO	CARB	NO	CARB07	NO	UTAH	NO	AZMC	NO	SCAQMD	NO	<table border="1"> <thead> <tr> <th>Technical Data</th> <th>Xylene</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td>Xylene</td> </tr> <tr> <td>Pigment Type</td> <td>N/A</td> </tr> <tr> <td>Volume Solids</td> <td>N/A</td> </tr> <tr> <td>Coverage per Gallon at Recommended Film Thickness</td> <td>N/A</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet N/A – Dry N/A</td> </tr> <tr> <td>Dry Time @ 77 °F (25 °C) @ 50% RH</td> <td>– Tack Free N/A – To Recoat N/A</td> </tr> <tr> <td>Dries By</td> <td>N/A</td> </tr> <tr> <td>Viscosity</td> <td>N/A</td> </tr> <tr> <td>Flash Point</td> <td>80 °F (TT-P-141, Method 4293)</td> </tr> <tr> <td>Gloss / Sheen</td> <td>N/A</td> </tr> <tr> <td>Surface Temperature at Application</td> <td>– Min. N/A – Max. N/A</td> </tr> <tr> <td>Thin With</td> <td>N/A</td> </tr> <tr> <td>Clean Up Thinner</td> <td>N/A</td> </tr> <tr> <td>Weight Per Gallon</td> <td>7.25 lbs.</td> </tr> <tr> <td>Storage Temperature</td> <td>– Min. 45 °F – Max. 95 °F</td> </tr> </tbody> </table> <p style="text-align: center;">Volatile Organic Compounds (VOC)</p> <p style="text-align: center;">868 Grams/Liter 7.25 Lbs./Gallon</p>	Technical Data	Xylene	Vehicle Type	Xylene	Pigment Type	N/A	Volume Solids	N/A	Coverage per Gallon at Recommended Film Thickness	N/A	Recommended Film Thickness	– Wet N/A – Dry N/A	Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free N/A – To Recoat N/A	Dries By	N/A	Viscosity	N/A	Flash Point	80 °F (TT-P-141, Method 4293)	Gloss / Sheen	N/A	Surface Temperature at Application	– Min. N/A – Max. N/A	Thin With	N/A	Clean Up Thinner	N/A	Weight Per Gallon	7.25 lbs.	Storage Temperature	– Min. 45 °F – Max. 95 °F
VOC REGION	COMPLIANT																																																		
FEDERAL	YES																																																		
OTC	NO																																																		
OTCII	NO																																																		
CARB	NO																																																		
CARB07	NO																																																		
UTAH	NO																																																		
AZMC	NO																																																		
SCAQMD	NO																																																		
Technical Data	Xylene																																																		
Vehicle Type	Xylene																																																		
Pigment Type	N/A																																																		
Volume Solids	N/A																																																		
Coverage per Gallon at Recommended Film Thickness	N/A																																																		
Recommended Film Thickness	– Wet N/A – Dry N/A																																																		
Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free N/A – To Recoat N/A																																																		
Dries By	N/A																																																		
Viscosity	N/A																																																		
Flash Point	80 °F (TT-P-141, Method 4293)																																																		
Gloss / Sheen	N/A																																																		
Surface Temperature at Application	– Min. N/A – Max. N/A																																																		
Thin With	N/A																																																		
Clean Up Thinner	N/A																																																		
Weight Per Gallon	7.25 lbs.																																																		
Storage Temperature	– Min. 45 °F – Max. 95 °F																																																		
<p>Technical Assistance: Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-866-708-9180 or visit www.benjaminmoore.com</p>																																																			

Xylene V703

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Corotech® Xylene is for use with all 2-part solvent-based epoxy and other high-performance coatings. Use to modify evaporation rates and modify dry. For effective cleaning of tools and equipment. May be used to reduce and thin coatings up to the legal limits allowed by local regulations.

Environmental Health & Safety Information

Warning!

Harmful in contact with skin

Harmful if inhaled

Causes skin irritation

Causes serious eye irritation

Suspected of causing cancer

May cause respiratory irritation

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable liquid and vapor

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Wear eye/face protection. Do not breathe dust/fume/mist/vapors/spray. Keep away from heat/sparks/ open flames/hot surfaces, no smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep cool.

Response: If exposed or concerned get medical attention. If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical attention. Call a POISON CENTER or physician if you feel unwell. If skin irritation occurs get medical attention. If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. If inhaled remove victim to fresh air and keep at rest in a position comfortable for breathing. If swallowed immediately call a POISON CENTER or physician. Do NOT induce vomiting. In case of fire use CO₂, dry chemical, or foam for extinction.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents/container to an approved waste disposal plant.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

KEEP OUT OF REACH OF CHILDREN

**Refer to Safety Data Sheet for
additional health and safety information.**