



EPOXY THINNER V704

Features

- For use with all 2-part solvent-based epoxy coatings
- For effective cleaning of tools and equipment
- May be used to reduce and thin coatings up to the legal limits allowed by district

General Description

Epoxy Thinner is a carefully balanced combination of the proper solvents for reducing catalyzed epoxy primers and finish coats.

Recommended For

For use with all 2-part solvent-based epoxy coatings. For effective cleaning of tools and equipment. May be used to reduce and thin coatings up to the legal limits allowed by district

Limitations

- Do not use for cleaning synthetic brushes or rollers as it will dissolve them.

Product Information

<p>Colors — Standard: N/A</p>	<table border="1"> <thead> <tr> <th colspan="2">Technical Data[◇]</th> <th>Epoxy Thinner</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td></td> <td>N/A</td> </tr> <tr> <td>Pigment Type</td> <td></td> <td>N/A</td> </tr> <tr> <td>Volume Solids</td> <td></td> <td>N/A</td> </tr> <tr> <td>Coverage per Gallon at Recommended Film Thickness</td> <td></td> <td>N/A</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet</td> <td>N/A</td> </tr> <tr> <td></td> <td>– Dry</td> <td>N/A</td> </tr> <tr> <td>Dry Time @ 77 °F (25 °C) @ 50% RH</td> <td>– Tack Free</td> <td>N/A</td> </tr> <tr> <td></td> <td>– To Recoat</td> <td>N/A</td> </tr> <tr> <td>Dries By</td> <td></td> <td>N/A</td> </tr> <tr> <td>Dry Heat Resistance</td> <td></td> <td>N/A</td> </tr> <tr> <td>Viscosity</td> <td></td> <td>N/A</td> </tr> <tr> <td>Flash Point</td> <td>23 °F (TT-P-141, Method 4293)</td> <td></td> </tr> <tr> <td>Gloss / Sheen</td> <td></td> <td>N/A</td> </tr> <tr> <td>Surface Temperature at Application</td> <td>– Min.</td> <td>N/A</td> </tr> <tr> <td></td> <td>– Max</td> <td>N/A</td> </tr> <tr> <td>Thin With</td> <td></td> <td>N/A</td> </tr> <tr> <td>Clean Up Thinner</td> <td></td> <td>N/A</td> </tr> <tr> <td>Weight Per Gallon</td> <td>6.95 lbs. (3.2 kg)</td> <td></td> </tr> <tr> <td>Storage Temperature</td> <td>– Min.</td> <td>40 °F (4.4 °C)</td> </tr> <tr> <td></td> <td>– Max</td> <td>95 °F (35 °C)</td> </tr> <tr> <td colspan="3" style="text-align: center;">Volatile Organic Compounds (VOC)</td> </tr> <tr> <td colspan="3" style="text-align: center;">832 Grams/Liters 6.95 Lbs./Gallon</td> </tr> </tbody> </table>	Technical Data [◇]		Epoxy Thinner	Vehicle Type		N/A	Pigment Type		N/A	Volume Solids		N/A	Coverage per Gallon at Recommended Film Thickness		N/A	Recommended Film Thickness	– Wet	N/A		– Dry	N/A	Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free	N/A		– To Recoat	N/A	Dries By		N/A	Dry Heat Resistance		N/A	Viscosity		N/A	Flash Point	23 °F (TT-P-141, Method 4293)		Gloss / Sheen		N/A	Surface Temperature at Application	– Min.	N/A		– Max	N/A	Thin With		N/A	Clean Up Thinner		N/A	Weight Per Gallon	6.95 lbs. (3.2 kg)		Storage Temperature	– Min.	40 °F (4.4 °C)		– Max	95 °F (35 °C)	Volatile Organic Compounds (VOC)			832 Grams/Liters 6.95 Lbs./Gallon		
Technical Data [◇]		Epoxy Thinner																																																																				
Vehicle Type			N/A																																																																			
Pigment Type			N/A																																																																			
Volume Solids		N/A																																																																				
Coverage per Gallon at Recommended Film Thickness		N/A																																																																				
Recommended Film Thickness	– Wet	N/A																																																																				
	– Dry	N/A																																																																				
Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free	N/A																																																																				
	– To Recoat	N/A																																																																				
Dries By		N/A																																																																				
Dry Heat Resistance		N/A																																																																				
Viscosity		N/A																																																																				
Flash Point	23 °F (TT-P-141, Method 4293)																																																																					
Gloss / Sheen		N/A																																																																				
Surface Temperature at Application	– Min.	N/A																																																																				
	– Max	N/A																																																																				
Thin With		N/A																																																																				
Clean Up Thinner		N/A																																																																				
Weight Per Gallon	6.95 lbs. (3.2 kg)																																																																					
Storage Temperature	– Min.	40 °F (4.4 °C)																																																																				
	– Max	95 °F (35 °C)																																																																				
Volatile Organic Compounds (VOC)																																																																						
832 Grams/Liters 6.95 Lbs./Gallon																																																																						
<p>— Tint Bases: N/A</p>																																																																						
<p>— Special Colors: N/A</p>																																																																						
<p>Certification & Qualifications:</p> <p>The product supported by this data sheet is regulated by consumer product VOC rules, in some areas, as a paint thinner, multi-purpose solvent. It also does not apply to LEED (Leadership in Energy and Environmental Design) standards.</p> <table border="1" data-bbox="646 1251 938 1528"> <thead> <tr> <th>VOC REGION</th> <th>COMPLIANT</th> </tr> </thead> <tbody> <tr> <td>FEDERAL</td> <td>YES</td> </tr> <tr> <td>OTC</td> <td>NO</td> </tr> <tr> <td>OTCII</td> <td>NO</td> </tr> <tr> <td>CARB</td> <td>NO</td> </tr> <tr> <td>CARB07</td> <td>NO</td> </tr> <tr> <td>UTAH</td> <td>NO</td> </tr> <tr> <td>AZMC</td> <td>NO</td> </tr> <tr> <td>SCAQMD</td> <td>NO</td> </tr> </tbody> </table>	VOC REGION	COMPLIANT	FEDERAL	YES	OTC	NO	OTCII	NO	CARB	NO	CARB07	NO	UTAH	NO	AZMC	NO	SCAQMD	NO																																																				
VOC REGION	COMPLIANT																																																																					
FEDERAL	YES																																																																					
OTC	NO																																																																					
OTCII	NO																																																																					
CARB	NO																																																																					
CARB07	NO																																																																					
UTAH	NO																																																																					
AZMC	NO																																																																					
SCAQMD	NO																																																																					
<p>Technical Assistance:</p> <p>Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-866-708-9180 or visit www.benjaminmoore.com</p>																																																																						

Epoxy Thinner V704

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Corotech® Epoxy Thinner is for use with all 2-part solvent-based epoxy coatings and for effective cleaning of tools and equipment. It may be used to reduce and thin coatings up to the legal limits allowed by district.

Environmental Health & Safety Information

DANGER!

Causes skin irritation

Causes serious eye damage

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Highly flammable liquid and vapor

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust/fume/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces, no smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep cool.

Response: If exposed or concerned get medical attention. If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician. If skin irritation occurs get medical attention. If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. If inhaled remove victim to fresh air and keep at rest in a position comfortable for breathing. If swallowed immediately call a POISON CENTER or physician. Do NOT induce vomiting. In case of fire use CO₂, dry chemical, or foam for extinction.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents /container to an approved waste disposal plant.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

KEEP OUT OF REACH OF CHILDREN

**Refer to Safety Data Sheet for
additional health and safety information.**