Benjamin Moore®

FAST SANDING PRIMER

Acrylic Latex Interior Primer

In just one hour, Benjamin Moore® Fast Sanding Primer can be sanded to a powder, creating an ideal basecoat for an ultra-smooth top coat. This primer offers excellent flow and leveling and delivers outstanding enamel holdout. Fast Sanding Primer delivers on two fronts: efficiency and professional-quality results.

Key Features	Benefits
Ready to sand in 1 hour	Maximize your efficiency to complete more jobs
Excellent flow and leveling	Provides a consistent and smooth application
Excellent sealing properties and holdout	Provides an ultra smooth base for top coat

Ideal For

Code	Gloss/Sheen	Volume Solids	Vehicle Type	Coverage[1]	Dry Time[2]	VOC Range
507	Primer	34 +/- 1%	Acrylic	350-450 sq. ft.	Sand: 1 hour Recoat: 1-2 hours	<50 VOC

SDSs and TDSs are available at Benjaminmoore.com.

[1]Theoretical gallon coverage at recommended film thickness (sq. ft). [2]Dry time at 77°F (25°C) at 50% RH. High humidity and cool temperatures will result in longer dry, recoat and service times.

Benjamin Moore®

GENNEX® COLOR TECHNOLOGY

Your Benjamin Moore® representative is here to answer your questions about Fast Sanding Primer.
Find your rep: **1-866-708-9180** or **benjaminmoore.com.**

©2023 Benjamin Moore & Co. Benjamin Moore, Gennex, and the triangle "M" symbol are registered trademarks licensed to Benjamin Moore & Co. Printed in the USA. M2455006SB 5/23 HRP

0 23906 77864 4

Benjamin Moore®

IMPRIMADOR PARA LIJADO RÁPIDO

Imprimador de látex acrílico para interiores

En solo una hora, Benjamin Moore® Imprimador para lijado rápido se puede lijar y producir polvo, lo que crea una capa base ideal para aplicar una capa superior ultrapareja. Este imprimador ofrece excelente flujo y nivelado, y permite una excelente retención del esmalte. Imprimador para lijado rápido rinde en dos frentes: eficiencia y resultados de calidad profesional.

Características clave	Beneficios
Listo para lijar en 1 hora	Logre la mayor eficiencia para completar más trabajos
Excelente flujo y nivelado	Permite una aplicación consistente y pareja
Excelentes propiedades de sellado y retención	Proporciona una base ultrapareja para la capa superior

Ideal para

Código	Brillo/acabado	Volumen de sólidos	Tipo de vehículo	Cobertura[1]	Tiempo de secado[2]	Rango de COV
507	Imprimador	34 +/- 1%	Acrílico	350-450 pies cuadrados	Lijado: 1 hora Repintado: 1-2 horas	<50 COV

La Hoja de Datos de Seguridad (Safety Data Sheet, SDS) y la Ficha de Datos Técnicos (Technical Data Sheets, TDS) están disponible en Benjaminmoore.com.

[1]Cobertura teórica de un galón al espesor de pintura recomendado (pies cuadrados). [2]Tiempo de secado a 77°F (25°C) a 50% HR. La alta humedad y las bajas temperaturas aumentarán los tiempos de secado, repintado y vuelta al servicio.

Benjamin Moore®

GENNEX™ TECNOLOGÍA DEL COLOR

Su representante de Benjamin Moore® está disponible para responderle preguntas acerca de Imprimador para lijado rápido. Encuentre a su representante: **1-866-708-9180** o **benjaminmoore.com.**

©2023 Benjamin Moore & Co. Benjamin Moore, Gennex y el símbolo de la "M" en el triángulo son marcas registradas, licenciadas a Benjamin Moore & Co. Impreso en EE. UU. M2455006SB 5/23 HRP

0 23906 77864 4