

Revision Date: 23-May-2023

**Revision Number:** 4

1. PRODUCT AND COMPANY IDENTIFICATION

## **Product Name**

Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

# REGAL SELECT EXTERIOR HIGH BUILD PAINT SOFT GLOSS FINISH BASE 2

**F4032X** F4032X Water thinned paint All Paint No information available

Manufactured For Benjamin Moore & Co., Limited 8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.com/en-ca

## Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

## Emergency Telephone CHEMTREC: +1 703-741-5970 / 1-800-424-9300

+1 703-527-3887 (outside US & Canada) CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

## **Classification**

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Reproductive toxicity	Category 1B

## Label elements

## Danger

## Hazard statements

May cause an allergic skin reaction May cause genetic defects May damage fertility or the unborn child



Odor little or no odor

## **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves

### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention **Skin** 

IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

### **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Other information

No information available

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

## 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Titanium dioxide	13463-67-7	7 - 13%	-	-
Nepheline syenite	37244-96-5	1 - 5%	-	-
Sodium C14-C16 olefin sulfonate	68439-57-6	0.25 - 0.5%	-	-
Carbamic acid, 1H-benzimidazol-2-yl-, methyl	10605-21-7	0.1 - 0.25%	-	-

ester				
1-Methyl-2-pyrrolidinone	872-50-4	0.1 - 0.25%	-	-

\*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRS	T AID MEASURES
General Advice	If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No
Flash Point Data Flash point (°F) Flash Point (°C) Method	Not Applicable Not applicable Not applicable
Flammability Limits In Air	
Lower flammability limit: Upper flammability limit:	Not applicable Not applicable

#### **NFPA**

**Health hazards** Flammability Stability Special:

#### NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

## 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

**Other Information** 

**Environmental precautions** 

Methods for Cleaning Up

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Prevent further leakage or spillage if safe to do so.

See Section 12 for additional Ecological Information.

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

## 7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Keep container tightly closed. Keep out of the reach of

No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

children.

### **Exposure Limits**

**Incompatible Materials** 

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Titanium dioxide	TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter	10 mg/m³ - TWA	10 mg/m³ - TWA 3 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m³ - TWAEV

2 0 0 Not Applicable

Storage

Nepheline syenite	-	-	-	10 mg/m <sup>3</sup> - TWA	-
1-Methyl-2-pyrrolidinone	-	-	-	400 mg/m <sup>3</sup> - TWA	-
<u>egend</u> ACGIH - American Conference of Alberta - Alberta Occupational Exp British Columbia - British Columbia Ontario - Ontario Occupational Exp Quebec - Quebec Occupational Ex I/E - Not established	oosure Limits a Occupational Expos posure Limits	,,,			
Engineering Measures		Er	sure adequate v	entilation, especially in c	confined areas.
Personal Protective Equip	oment_				
Eye/Face Protection			fety glasses with		
Skin Protection Respiratory Protection				and impervious clothing. Juate ventilation. In oper-	
		res pe pro ap	spirator that has rson for the spec oduct or applying	e exceeded, use a NIOSI been selected by a tech cific work conditions. Wh g in confined areas, wear or specified for paint spra	nically qualified en spraying the r a NIOSH
Hygiene Measures		wa	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.		
	9. PHYSICA	L AND CHEI	VICAL PRO	PERTIES	
Appearance		liq	uid		
Odor		litt	e or no odor		
Odor Threshold		No	information ava	ilable	
Density (Ibs./gal)		9.5	5 - 9.9		
Specific Gravity		1.1	3 - 1.19		
PH		No	information ava	ilable	
Viscosity (cps)		No	information ava	ilable	
Solubility(ies)		No	information ava	ilable	
Water solubility		No	No information available		
Evaporation Rate		No	information ava	ilable	
Vapor pressure @20 °C (k	(Pa)	No	information ava	ilable	

Vapor pressure @20 °C (kPa) Relative vapor density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) Boiling Point (°F) Boiling Point (°C) Freezing Point (°C) Flash point (°C) Flash Point (°C) Method Flammability (solid, gas) little or no odor No information available 9.5 - 9.9 1.13 - 1.19 No information available 40 - 50 30 - 40 50 - 60 60 - 70 < 50 212 100 32 0 Not Applicable Not applicable Not applicable Not applicable Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) Decomposition Temperature (°F) Decomposition Temperature (°C) Partition coefficient Not applicable Not applicable No information available No information available No information available No information available No information available

## **10. STABILITY AND REACTIVITY**

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

#### Product Information Information on likely routes of exposure

Principal Routes of Exposure

Eye contact, skin contact and inhalation.

<u>Acute Toxicity</u> Product Information

No information available

No information available

### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Skin contact	May cause slight irritation Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization	May cause an allergic skin reaction.
Neurological Effects	No information available.
Mutagenic Effects	Suspected of causing genetic defects.
Reproductive Effects	May damage fertility or the unborn child.
Developmental Effects	No information available.
Target organ effects	No information available.
STOT - single exposure	No information available.

#### STOT - repeated exposure Other adverse effects Aspiration Hazard

No information available. No information available. No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

89526 mg/kg

#### Component Information

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Sodium C14-C16 olefin sulfonate 68439-57-6	= 2220 mg/kg (Rat)	> 740 mg/kg (Rabbit)	-
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester 10605-21-7	> 5050 mg/kg (Rat)	> 10000 mg/kg (Rabbit)	-
1-Methyl-2-pyrrolidinone 872-50-4	= 3914 mg/kg (Rat)	= 8 g/kg (Rabbit)	> 5.1 mg/L (Rat)4 h

### Chronic Toxicity

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP
	2B - Possible Human Carcinogen	
Titanium dioxide		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

## **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

### **Product Information**

### Acute Toxicity to Fish

No information available

### Acute Toxicity to Aquatic Invertebrates

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

#### Persistence / Degradability

No information available.

#### **Bioaccumulation**

There is no data for this product.

#### **Mobility in Environmental Media**

No information available.

#### Ozone

Not applicable

### **Component Information**

#### Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester</u> LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

#### Acute Toxicity to Aquatic Invertebrates

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester LC50: 0.22 mg/L (water flea - 48 hr.)

#### Acute Toxicity to Aquatic Plants

No information available

## 13. DISPOSAL CONSIDERATIONS

#### Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

## 14. TRANSPORT INFORMATION

TDG

Not regulated

ICAO / IATA

Not regulated

### IMDG / IMO

Not regulated

## **15. REGULATORY INFORMATION**

## International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

## National Pollutant Release Inventory (NPRI)

### NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical name	CAS No	Weight-%	NPRI Parts 1-4
1-Methyl-2-pyrrolidinone	872-50-4	0.1 - 0.25%	Listed

#### NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

#### WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

**16. OTHER INFORMATION** 

#### HMIS

Health hazards	2*
Flammability	0
Reactivity:	0
Personal protection	-

#### HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a

registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\_questions-questions\_posees-eng.php.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	23-May-2023
Reason for revision	Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

### End of Safety Data Sheet