

SAFETY DATA SHEET

Revision Date: 02-Aug-2018

Revision Number: 2

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

AURA WATERBORNE INTERIOR MATTE FINISH BASE 3

5223X 5223X WATER THINNED PAINT All Paint No information available

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

Emergency Telephone CHEMTREC (US): 800-424-9300

CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid

Odor little or no odor

Hazards not otherwise classified (HNOC) Not applicable

Other information No information available

Other hazards

May cause allergic skin reaction

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Silica, amorphous	7631-86-9	10
Titanium dioxide	13463-67-7	5
Limestone	1317-65-3	5
Hexanedioic acid, dihydrazide	1071-93-8	0.5
Sodium C14-C16 olefin sulfonate	68439-57-6	0.5
Zinc Pyrithione	13463-41-7	0.5

	4. FIRST AID MEASURES
General Advice	No hazards which require special first aid measures.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity To Mechanical Impact	No
Sensitivity To Static Discharge	No
Flash Point Data Flash Point (°F) Flash Point (°C) Method	Not applicable Not applicable Not applicable

Flammability Limits In Air

Lower flammability limit: Upper flammability limit:

Health: 1

Flammability: 0

Instability: 0

Not applicable

Not applicable

Special: Not Applicable

NFPA Legend

- 0 Not Hazardous
- 1 Slightly

NFPA

- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.	
Other Information	Prevent further leakage or spillage if safe to do so.	
Environmental precautions	See Section 12 for additional Ecological Information.	
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.	
	7. HANDLING AND STORAGE	
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.	
Storage	Keep container tightly closed. Keep out of the reach of children.	
Incompatible Materials	No information available	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Silica, amorphous	N/E	20 mppcf - TWA
Titanium dioxide	10 mg/m³ - TWA	15 mg/m³ - TWA
Limestone	N/E	15 mg/m³ - TWA 5 mg/m³ - TWA

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

Engineering Measures	Ensure adequate ventilation, especially in confined areas.	
Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection	Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.	
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	little or no odor
Odor Threshold	No information available
Density (Ibs/gal)	9.9 - 10.3
Specific Gravity	1.18 - 1.23
рН	No information available
Viscosity (cps)	No information available
Solubility(ies)	No information available
Water solubility	No information available
Evaporation Rate	No information available
Vapor pressure @20 °C (kPa)	No information available
Vapor density	No information available
Wt. % Solids	50 - 60
Vol. % Solids	40 - 50
Wt. % Volatiles	40 - 50
Vol. % Volatiles	50 - 60
VOC Regulatory Limit (g/L)	0
Boiling Point (°F)	212
Boiling Point (°C)	100
Freezing Point (°F)	32
Freezing Point (°C)	0
Flash Point (°F)	Not applicable
Flash Point (°C)	Not applicable
Method	Not applicable
Flammability (solid, gas)	Not applicable
Upper flammability limit:	Not applicable
Lower flammability limit:	Not applicable
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

10. STABILITY AND REACTIVITY

Reactivity

Not Applicable

Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information		
Information on likely routes of exposure		
Principal Routes of Exposure	Eye contact, skin contact and inhalation.	
Acute Toxicity		
Product Information	No information available	
Symptoms related to the physic	cal, chemical and toxicological characteristics	
Symptoms	No information available	
Delayed and immediate effects	as well as chronic effects from short and long-term exposure	
Eye contact Skin contact	May cause slight irritation. Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.	
Inhalation	May cause irritation of respiratory tract.	
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.	
Sensitization	May cause an allergic skin reaction	
Neurological Effects	No information available.	
Mutagenic Effects	No information available.	
Reproductive Effects	No information available.	
Developmental Effects	No information available.	
Target organ effects	No information available.	
STOT - single exposure	No information available.	
STOT - repeated exposure	No information available.	
Other adverse effects	No information available.	
Aspiration Hazard	No information available	
Numerical measures of toxicity		
The following values are calculated based on chapter 3.1 of the GHS document		

ATEmix (oral)	17585	mg/kg
ATEmix (dermal)	38793	mg/kg
ATEmix (inhalation-dust/mist)	450.5	

Component Information

Silica, amorphous

LD50 Oral: > 5000 mg/kg (Rat) LD50 Dermal: 2,000 mg/kg (Rabbit) LC50 Inhalation (Dust): > 2 mg/L <u>Titanium dioxide</u> LD50 Oral: > 10000 mg/kg (Rat) <u>Zinc Pyrithione</u> LD50 Oral: mg/kg (Rat) LD50 Dermal: mg/kg (Rabbit) LC50 Inhalation (Vapor): mg/L (Rat, 4 hr.)

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

No information available.

<u>Ozone</u>

No information available

Component Information

Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>Zinc Pyrithione</u> LC50: 0.0032 mg/L (Rainbow Trout - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Zinc Pyrithione LC50: 0.0082 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic Plants

Zinc Pyrithione EC50: 0.028 mg/L (Algae (Selenastrum capricornutum) - 120 hrs.)

	13. DISPOSAL CONSIDERATIONS	
Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.	
	14. TRANSPORT INFORMATION	
DOT	Not regulated	
ICAO / IATA	Not regulated	
IMDG / IMO	Not regulated	
	15. REGULATORY INFORMATION	
International Inventories		
TSCA: United States DSL: Canada	Yes - All components are listed or exempt. No - Not all of the components are listed. One or more component is listed on NDSL.	
Federal Regulations		
SARA 311/312 hazardous catego Acute health hazard Chronic Health Hazard Fire hazard Sudden release of pressure ha Reactive Hazard	No No No	

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

MARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Silica, amorphous	X	X	X
Titanium dioxide	X	X	X
Limestone	X	X	X

Legend

X - Listed

16. OTHER INFORMATION

<u>HMIS</u> -	Health: 1	Flammability: 0	Reactivity: 0	PPE: -
HMIS Legend 0 - Minimal Hazard 1 - Slight Hazard 2 - Moderate Hazard 3 - Serious Hazard	1			

- 3 4 - Severe Hazard
- * Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	02-Aug-2018
Revision Summary	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET