

SAFETY DATA SHEET

Revision Date: 13-Apr-2020 Revision Number: 4

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name ben, WATERBORNE EXTERIOR SOFT GLOSS FINISH BASE 4

Product Code K5434X
Alternate Product Code K5434X

Product Class Water thinned paint

Color All Recommended use Paint

Restrictions on use No information available

Manufactured For

Benjamin Moore & Co., Limited

8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898 www.benjaminmoore.com

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

Phone: 1-866-708-9180 www.benjaminmoore.com Emergency Telephone CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Germ cell mutagenicity	Category 1B
Reproductive toxicity	Category 1B

Label elements

Danger

Hazard statements

May cause genetic defects

May damage fertility or the unborn child

Revision Date: 13-Apr-2020



Appearance liquid Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Nepheline syenite	37244-96-5	1 - 5%	-	-
Zinc oxide	1314-13-2	0.5 - 1%	-	-
Sodium C14-C16 olefin sulfonate	68439-57-6	0.25 - 0.5%	-	-
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester	10605-21-7	0.25 - 0.5%	-	-
1-Methyl-2-pyrrolidinone	872-50-4	0.1 - 0.25%	-	-

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice If symptoms persist, call a physician. Show this safety data

sheet to the doctor in attendance.

Eye Contact Rinse thoroughly with plenty of water for at least 15

K5434X - ben, WATERBORNE EXTERIOR SOFT GLOSS FINISH BASE 4

minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes.

Revision Date: 13-Apr-2020

Inhalation Move to fresh air. If symptoms persist, call a physician.

Ingestion Clean mouth with water and afterwards drink plenty of

water. Consult a physician if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

Flash Point Data

Flash point (°F)

Flash Point (°C)

Method

Not applicable

Not applicable

Not applicable

Flammability Limits In Air

Lower flammability limit:

Upper flammability limit:

Not applicable

Not applicable

NFPA Health: 2 Flammability: 0 Instability: 0 Special: Not Applicable

NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental precautionsSee Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

Revision Date: 13-Apr-2020

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

Incompatible Materials No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Nepheline syenite	N/E	N/E	N/E	10 mg/m ³ - TWA	N/E
Zinc oxide	STEL: 10 mg/m ³	2 mg/m³ - TWA	2 mg/m³ - TWA	2 mg/m³ - TWA	10 mg/m ³ - TWAEV
	respirable particulate	10 mg/m ³ - STEL	10 mg/m ³ - STEL	10 mg/m ³ - STEL	5 mg/m³ - TWAEV
	matter				10 mg/m³ - STEV
	TWA: 2 mg/m ³				
	respirable particulate				
	matter				
1-Methyl-2-pyrrolidinone	N/E	N/E	N/E	400 mg/m ³ - TWA	N/E

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection
Skin Protection
Respiratory Protection

Protective gloves and impervious clothing.
Use only with adequate ventilation. In operations where

Safety glasses with side-shields.

exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH

approved respirator specified for paint spray or organic

Revision Date: 13-Apr-2020

vapors.

Hygiene Measures Avoid contact with skin, eyes and clothing. Remove and

wash contaminated clothing before re-use. Wash

thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Odor little or no odor

Odor Threshold No information available

Density (lbs/gal) 8.6 - 9.0 **Specific Gravity** 1.09 - 1.14

pH No information available Viscosity (cps) No information available

Solubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information available

Vapor pressureNo information availableVapor densityNo information available

 Wt. % Solids
 35 - 45

 Vol. % Solids
 30 - 40

 Wt. % Volatiles
 55 - 65

 Vol. % Volatiles
 60 - 70

 VOC Regulatory Limit (g/L)
 < 50</td>

Boiling Point (°F) 212
Boiling Point (°C) 100
Freezing point (°F) 32
Freezing Point (°C) 0

Flash point (°F)

Flash Point (°C)

Method

Flammability (solid, gas)

Upper flammability limit:

Not applicable

Not applicable

Not applicable

Lower flammability limit:Not applicableAutoignition Temperature (°F)No information availableAutoignition Temperature (°C)No information availableDecomposition Temperature (°F)No information availableDecomposition Temperature (°C)No information available

Partition coefficient No information available

10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

K5434X - ben. WATERBORNE EXTERIOR SOFT **GLOSS FINISH BASE 4**

Hazardous Decomposition Products None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

May cause slight irritation **Eve contact**

Skin contact Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

Revision Date: 13-Apr-2020

May cause irritation of respiratory tract. Inhalation

Ingestion Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea. No information available.

Sensitization **Neurological Effects** No information available.

Suspected of causing genetic defects. **Mutagenic Effects** May damage fertility or the unborn child. **Reproductive Effects**

Developmental Effects No information available. **Target organ effects** No information available. STOT - single exposure No information available. STOT - repeated exposure No information available. Other adverse effects No information available. **Aspiration Hazard** No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

483549 mg/kg ATEmix (dermal) ATEmix (inhalation-dust/mist) 351.1 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Zinc oxide 1314-13-2	> 5000 mg/kg (Rat)	-	-
Sodium C14-C16 olefin sulfonate 68439-57-6	= 2220 mg/kg (Rat)	> 740 mg/kg (Rabbit)	-
Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester	,	> 10000 mg/kg (Rabbit) = 2 g/kg (Rat) = 8500 mg/kg (Rabbit)	-

Revision Date: 13-Apr-2020

10605-21-7			
1-Methyl-2-pyrrolidinone 872-50-4	= 3914 mg/kg (Rat)	= 8 g/kg (Rabbit)	> 5.1 mg/L (Rat) 4 h

Chronic Toxicity

Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component Information

Acute Toxicity to Fish

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester

LC50: 1.5 mg/L (Rainbow Trout - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester

LC50: 0.22 mg/L (water flea - 48 hr.)

K5434X - ben, WATERBORNE EXTERIOR SOFT GLOSS FINISH BASE 4

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 13-Apr-2020

14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United StatesYes - All components are listed or exempt.

Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical nameCAS No.Weight-%NPRI Parts 1- 41-Methyl-2-pyrrolidinone872-50-40.1 - 0.25%Listed

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

Revision Date: 13-Apr-2020

16. OTHER INFORMATION

HMIS - Health: 2* Flammability: 0 Reactivity: 0 PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554

Revision Date: 13-Apr-2020 Reason for revision Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet