

# SAFETY DATA SHEET

Revision Date: 18-Feb-2021

**Revision Number:** 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

# ULTRA SPEC 500 INTERIOR PAINT - SEMI-GLOSS BASE 4 S5464X S5464X

Water thinned paint All Paint No information available

## Initial Supplier Identifier

Benjamin Moore & Co. Ltd. 8775 Keele Street Concord, ON L4K 2N1 www.benjaminmoore.ca Telephone: 1-800-361-5898

# Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

## Emergency Telephone CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1-703-527-3887 outside US & Canada CANUTEC: 613-996-6666 (Canada Transport Emergency Only)

2. HAZARDS IDENTIFICATION

## **Classification**

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

This chemical is not considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

## Label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid

Odor little or no odor

Hazards not otherwise classified (HNOC) Not applicable

Other information No information available

#### Other hazards

May cause allergic skin reaction

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

## 3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name                 | CAS No.    | Weight-%    | Hazardous Material<br>Information Review Act<br>registry number<br>(HMIRA registry #) | Date HMIRA filed and<br>date exemption granted<br>(if applicable) |
|-------------------------------|------------|-------------|---------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| Kaolin                        | 1332-58-7  | 3 - 7%      | -                                                                                     | -                                                                 |
| Titanium dioxide              | 13463-67-7 | 0.1 - 0.25% | -                                                                                     | -                                                                 |
| Hexanedioic acid, dihydrazide | 1071-93-8  | 0.1 - 0.25% | -                                                                                     | -                                                                 |

\*The exact percentage (concentration) of composition has been withheld as a trade secret

## 4. FIRST AID MEASURES **General Advice** No hazards which require special first aid measures. Rinse thoroughly with plenty of water for at least 15 **Eye Contact** minutes and consult a physician. **Skin Contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Inhalation Move to fresh air. If symptoms persist, call a physician. Ingestion Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary. May cause allergic skin reaction. Most Important Symptoms/Effects **Notes To Physician** Treat symptomatically. 5. FIRE-FIGHTING MEASURES Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. As in any fire, wear self-contained breathing apparatus Protective equipment and precautions for firefighters pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Closed containers may rupture if exposed to fire or **Specific Hazards Arising From The Chemical** extreme heat.

Sensitivity to mechanical impact

No

| Sensitivity to static discharge                                    |                 | No                                                 |                         |
|--------------------------------------------------------------------|-----------------|----------------------------------------------------|-------------------------|
| Flash Point Data<br>Flash point (°F)<br>Flash Point (°C)<br>Method |                 | Not applicable<br>Not applicable<br>Not applicable |                         |
| Flammability Limits In Air                                         |                 |                                                    |                         |
| Lower flammability limit:<br>Upper flammability limit:             |                 | Not applicable<br>Not applicable                   |                         |
| NFPA Health: 1                                                     | Flammability: 0 | Instability: 0                                     | Special: Not Applicable |

## NFPA Legend

- 0 Not Hazardous
- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** 

**Other Information** 

**Environmental precautions** 

Methods for Cleaning Up

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Prevent further leakage or spillage if safe to do so.

See Section 12 for additional Ecological Information.

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Keep container tightly closed. Keep out of the reach of

Storage

Incompatible Materials

No information available

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

children.

**Exposure Limits** 

| Chemical name    | OSHA PEL                        | ACGIH TLV                                                                                                                                      | Alberta        | British                                                 | Ontario        | Quebec              |
|------------------|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|----------------|---------------------------------------------------------|----------------|---------------------|
|                  |                                 |                                                                                                                                                |                | Columbia                                                |                |                     |
| Kaolin           | 15 mg/m³ - TWA<br>5 mg/m³ - TWA | TWA: 2 mg/m <sup>3</sup><br>particulate matter<br>containing no<br>asbestos and <1%<br>crystalline silica,<br>respirable<br>particulate matter | 2 mg/m³ - TWA  | 2 mg/m³ - TWA                                           | 2 mg/m³ - TWA  | 5 mg/m³ - TWAEV     |
| Titanium dioxide | 15 mg/m³ - TWA                  | TWA: 10 mg/m <sup>3</sup>                                                                                                                      | 10 mg/m³ - TWA | 10 mg/m <sup>3</sup> - TWA<br>3 mg/m <sup>3</sup> - TWA | 10 mg/m³ - TWA | 10 mg/m³ -<br>TWAEV |

#### Legend

OSHA - Occupational Safety & Health Administration Exposure Limits

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits

Quebec - Quebec Occupational Exposure Limits

N/E - Not Established

## **Engineering Measures**

## Personal Protective Equipment

Eye/Face Protection Skin Protection Respiratory Protection Ensure adequate ventilation, especially in confined areas.

Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

| 9. PHYSICAL AND CHEMICAL PROPERTIES |
|-------------------------------------|
|-------------------------------------|

| Appearance<br>Odor<br>Odor Threshold<br>Density (Ibs/gal)<br>Specific Gravity<br>pH<br>Viscosity (cps)<br>Solubility(ies) | liquid<br>little or no odor<br>No information available<br>9.05 - 9.15<br>1.08 - 1.10<br>No information available<br>No information available<br>No information available<br>No information available |
|---------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Water solubility<br>Evaporation Rate                                                                                      | No information available                                                                                                                                                                              |
| Vapor pressure                                                                                                            | No information available                                                                                                                                                                              |
| Vapor density                                                                                                             | No information available                                                                                                                                                                              |
| Wt. % Solids                                                                                                              | 35 - 45                                                                                                                                                                                               |
| Vol. % Solids                                                                                                             | 30 - 40                                                                                                                                                                                               |
| Wt. % Volatiles                                                                                                           | 55 - 65                                                                                                                                                                                               |
| Vol. % Volatiles                                                                                                          | 60 - 70                                                                                                                                                                                               |
| VOC Regulatory Limit (g/L)                                                                                                | 0                                                                                                                                                                                                     |
| Boiling Point (°F)                                                                                                        | 212                                                                                                                                                                                                   |
| Boiling Point (°C)                                                                                                        | 100                                                                                                                                                                                                   |

## Hygiene Measures

#### S5464X - ULTRA SPEC 500 INTERIOR PAINT -**SEMI-GLOSS BASE 4**

Freezing point (°F) Freezing Point (°C) Flash point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F) Decomposition Temperature (°C)** Partition coefficient

#### Revision Date: 18-Feb-2021

32

0 Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

# **10. STABILITY AND REACTIVITY**

| Reactivity                         | Not Applicable                           |
|------------------------------------|------------------------------------------|
| Chemical Stability                 | Stable under normal conditions.          |
| Conditions to avoid                | Prevent from freezing.                   |
| Incompatible Materials             | No materials to be especially mentioned. |
| Hazardous Decomposition Products   | None under normal use.                   |
| Possibility of hazardous reactions | None under normal conditions of use.     |

## **11. TOXICOLOGICAL INFORMATION**

## **Product Information** Information on likely routes of exposure

**Principal Routes of Exposure** 

Acute Toxicity **Product Information** 

Eye contact, skin contact and inhalation.

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** 

No information available

No information available

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eve contact Skin contact

Inhalation Ingestion

Sensitization **Neurological Effects Mutagenic Effects** 

May cause slight irritation Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation. May cause irritation of respiratory tract. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause an allergic skin reaction. No information available. No information available.

| Reproductive Effects     | No information available. |
|--------------------------|---------------------------|
| Developmental Effects    | No information available. |
| Target organ effects     | No information available. |
| STOT - single exposure   | No information available. |
| STOT - repeated exposure | No information available. |
| Other adverse effects    | No information available. |
| Aspiration Hazard        | No information available. |
|                          |                           |

### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

#### **Component Information**

| Chemical name                  | Oral LD50           | Dermal LD50        | Inhalation LC50 |
|--------------------------------|---------------------|--------------------|-----------------|
| Kaolin<br>1332-58-7            | > 5000 mg/kg (Rat)  | > 5000 mg/kg (Rat) | -               |
| Titanium dioxide<br>13463-67-7 | > 10000 mg/kg (Rat) | -                  | -               |

### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name    | IARC                | NTP | OSHA   |
|------------------|---------------------|-----|--------|
|                  | 2B - Possible Human |     | Listed |
| Titanium dioxide | Carcinogen          |     |        |

Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

## **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

#### Product Information

#### Acute Toxicity to Fish No information available

No information available

## Acute Toxicity to Aquatic Invertebrates

No information available

<u>Acute Toxicity to Aquatic Plants</u> No information available

#### Persistence / Degradability

No information available.

### **Bioaccumulation**

There is no data for this product.

## Mobility in Environmental Media

No information available.

#### **Ozone**

No information available

## **Component Information**

## Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

## Acute Toxicity to Aquatic Invertebrates

No information available

## Acute Toxicity to Aquatic Plants

No information available

# **13. DISPOSAL CONSIDERATIONS**

14 TRANSPORT INFORMATION

## Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

|             | 14. TRANSPORT INFORMATION |
|-------------|---------------------------|
| DOT         | Not regulated             |
| TDG         | Not regulated             |
| ICAO / IATA | Not regulated             |
| IMDG / IMO  | Not regulated             |

# 15. REGULATORY INFORMATION

International Inventories

| TSCA: United States | Yes - All components are listed or exempt. |
|---------------------|--------------------------------------------|
| DSL: Canada         | Yes - All components are listed or exempt. |

## Federal Regulations

| SARA 311/312 hazardous categorization |     |
|---------------------------------------|-----|
| Acute health hazard                   | Yes |
| Chronic Health Hazard                 | No  |
| Fire hazard                           | No  |
| Sudden release of pressure hazard     | No  |
| Reactive Hazard                       | No  |

## **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

## Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

## **US State Regulations**

## California Proposition 65

**MARNING:** Cancer and Reproductive Harm– www.P65warnings.ca.gov

#### State Right-to-Know

| Chemical name    | Massachusetts | New Jersey | Pennsylvania |
|------------------|---------------|------------|--------------|
| Kaolin           | Х             | Х          | Х            |
| Titanium dioxide | Х             | Х          | Х            |

Legend X - Listed

## National Pollutant Release Inventory (NPRI)

#### NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

None


## NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

None

## WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.



Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

| Prepared By         | Product Stewardship Department<br>Benjamin Moore & Co.<br>101 Paragon Drive<br>Montvale, NJ 07645<br>800-225-5554 |
|---------------------|-------------------------------------------------------------------------------------------------------------------|
| Revision Date:      | 18-Feb-2021                                                                                                       |
| Reason for revision | Not available                                                                                                     |

**Disclaimer** 

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

## **End of Safety Data Sheet**