



# Benjamin Moore®

## SAFETY DATA SHEET

Revision Date: 14-Nov-2022

Revision Number: 3

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** REGAL SELECT WATERBORNE INTERIOR PAINT - EGGSHELL SUPER WHITE

**Product Code** N54902

**Alternate Product Code** N54902

**Product Class** Water thinned paint

**Color** White

**Recommended use** Paint

**Restrictions on use** No information available

**Manufacturer**  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
Phone: 1-866-708-9180  
www.benjaminmoore.com

**Emergency Telephone**  
CHEMTREC: +1 703-741-5970 / 1-800-424-9300  
+1 703-527-3887 (outside US & Canada)

### 2. HAZARDS IDENTIFICATION

**Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Reproductive toxicity	Category 2
-----------------------	------------

**Label elements**

**Warning**

**Hazard statements**

Suspected of damaging fertility or the unborn child



**Appearance** liquid

**Odor** little or no odor

**Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other information**

No information available

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

**3. COMPOSITION INFORMATION ON COMPONENTS**

Chemical name	CAS No	Weight-%
Titanium dioxide	13463-67-7	20 - 25
Nepheline syenite	37244-96-5	5 - 10
Limestone	1317-65-3	1 - 5
Silica amorphous	7631-86-9	1 - 5
Kaolin, calcined	66402-68-4	1 - 5
Kaolin	1332-58-7	1 - 5
Trimethylolpropane	77-99-6	0.1 - 0.5

**4. FIRST AID MEASURES**

**General Advice**

No hazards which require special first aid measures.

**Eye Contact**

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**Skin Contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

**Inhalation**

Move to fresh air. If symptoms persist, call a physician.

**Ingestion**

Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.

**Most Important Symptoms/Effects** None known.

**Notes To Physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Protective equipment and precautions for firefighters</b>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
<b>Specific Hazards Arising From The Chemical</b>	Closed containers may rupture if exposed to fire or extreme heat.
<b>Sensitivity to mechanical impact</b>	No
<b>Sensitivity to static discharge</b>	No
<b>Flash Point Data</b>	
Flash point (°F)	Not applicable
Flash Point (°C)	Not applicable
Method	Not applicable
<b>Flammability Limits In Air</b>	
Lower flammability limit:	Not applicable
Upper flammability limit:	Not applicable
<b>NFPA</b>	
Health hazards	2
Flammability	0
Stability	0
Special:	Not Applicable

### NFPA Legend

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

*The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.*

*Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).*

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

<b>Other Information</b>	Prevent further leakage or spillage if safe to do so.
<b>Environmental precautions</b>	See Section 12 for additional Ecological Information.
<b>Methods for Cleaning Up</b>	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
<b>Storage</b>	Keep container tightly closed. Keep out of the reach of children.
<b>Incompatible Materials</b>	No information available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Titanium dioxide	TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter	15 mg/m <sup>3</sup> - TWA
Limestone	-	15 mg/m <sup>3</sup> - TWA 5 mg/m <sup>3</sup> - TWA
Silica amorphous	-	20 mppcf - TWA
Kaolin, calcined	STEL: 10 mg/m <sup>3</sup> Zr As Zirconium compounds [RR-00624-6] STEL: 10 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> Zr As Zirconium compounds [RR-00624-6] TWA: 0.02 mg/m <sup>3</sup> Mn respirable particulate matter As Manganese inorganic compounds [RR-03861-9] TWA: 0.1 mg/m <sup>3</sup> Mn inhalable particulate matter As Manganese inorganic compounds [RR-03861-9] TWA: 5 mg/m <sup>3</sup> Zr TWA: 0.02 mg/m <sup>3</sup> Mn respirable particulate matter TWA: 0.1 mg/m <sup>3</sup> Mn inhalable particulate matter	5 mg/m <sup>3</sup> - TWA 5 mg/m <sup>3</sup> - Ceiling
Kaolin	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	15 mg/m <sup>3</sup> - TWA 5 mg/m <sup>3</sup> - TWA

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits  
OSHA - Occupational Safety & Health Administration Exposure Limits  
N/E - Not Established

**Engineering Measures**                      Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment**

**Eye/Face Protection**                      Safety glasses with side-shields.  
**Skin Protection**                              Protective gloves and impervious clothing.  
**Respiratory Protection**                      In case of insufficient ventilation wear suitable respiratory equipment.

**Hygiene Measures**                              Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	liquid
<b>Odor</b>	little or no odor
<b>Odor Threshold</b>	No information available
<b>Density (lbs/gal)</b>	11.4 - 11.8
<b>Specific Gravity</b>	1.36 - 1.42
<b>pH</b>	No information available
<b>Viscosity (cps)</b>	No information available
<b>Solubility(ies)</b>	No information available
<b>Water solubility</b>	No information available
<b>Evaporation Rate</b>	No information available
<b>Vapor pressure @20 °C (kPa)</b>	No information available
<b>Relative vapor density</b>	No information available
<b>Wt. % Solids</b>	55 - 65
<b>Vol. % Solids</b>	40 - 50
<b>Wt. % Volatiles</b>	35 - 45
<b>Vol. % Volatiles</b>	50 - 60
<b>VOC Regulatory Limit (g/L)</b>	< 50
<b>Boiling Point (°F)</b>	212
<b>Boiling Point (°C)</b>	100
<b>Freezing point (°F)</b>	32
<b>Freezing Point (°C)</b>	0
<b>Flash point (°F)</b>	Not applicable
<b>Flash Point (°C)</b>	Not applicable
<b>Method</b>	Not applicable
<b>Flammability (solid, gas)</b>	Not applicable
<b>Upper flammability limit:</b>	Not applicable
<b>Lower flammability limit:</b>	Not applicable
<b>Autoignition Temperature (°F)</b>	No information available
<b>Autoignition Temperature (°C)</b>	No information available
<b>Decomposition Temperature (°F)</b>	No information available
<b>Decomposition Temperature (°C)</b>	No information available
<b>Partition coefficient</b>	No information available

**10. STABILITY AND REACTIVITY**

**Reactivity**    Not Applicable

**Chemical Stability**                                      Stable under normal conditions.

<b>Conditions to avoid</b>	Prevent from freezing.
<b>Incompatible Materials</b>	No materials to be especially mentioned.
<b>Hazardous Decomposition Products</b>	None under normal use.
<b>Possibility of hazardous reactions</b>	None under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

### Product Information

#### Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

#### Acute Toxicity

**Product Information** No information available

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Eye contact</b>	May cause slight irritation.
<b>Skin contact</b>	Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
<b>Inhalation</b>	May cause irritation of respiratory tract.
<b>Ingestion</b>	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
<b>Sensitization</b>	No information available
<b>Neurological Effects</b>	No information available.
<b>Mutagenic Effects</b>	No information available.
<b>Reproductive Effects</b>	Possible risk of impaired fertility. Possible risk of harm to the unborn child.
<b>Developmental Effects</b>	No information available.
<b>Target organ effects</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	No information available.
<b>Other adverse effects</b>	No information available.
<b>Aspiration Hazard</b>	No information available

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 35516 mg/kg

**Component Information** Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Silica amorphous 7631-86-9	= 7900 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	-

Kaolin 1332-58-7	> 5000 mg/kg ( Rat )	> 5000 mg/kg ( Rat )	-
Trimethylolpropane 77-99-6	= 14100 mg/kg ( Rat ) = 14000 mg/kg ( Rat )	-	> 0.29 mg/L ( Rat ) 4 h

**Chronic Toxicity**

**Carcinogenicity**

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
Titanium dioxide	2B - Possible Human Carcinogen		Listed

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

**Legend**

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

**Product Information**

**Acute Toxicity to Fish**

No information available

**Acute Toxicity to Aquatic Invertebrates**

No information available

**Acute Toxicity to Aquatic Plants**

No information available

**Persistence / Degradability**

No information available.

**Bioaccumulation**

There is no data for this product.

**Mobility in Environmental Media**

No information available.

**Ozone**

Not applicable

**Component Information**

**Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

**Acute Toxicity to Aquatic Invertebrates**

No information available

**Acute Toxicity to Aquatic Plants**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Method**

Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

**14. TRANSPORT INFORMATION**

**DOT**

Not regulated

**ICAO / IATA**

Not regulated

**IMDG / IMO**

Not regulated

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA: United States**

Yes - All components are listed or exempt.

**DSL: Canada**

Yes - All components are listed or exempt.

**Federal Regulations**

**SARA 311/312 Hazard Categories**

Acute health hazard	No
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name

CAS No

Weight-%

CERCLA/SARA 313  
(de minimis concentration)



Kaolin, calcined 66402-68-4 1 - 5 1.0


**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product contains the following HAPs:

<u>Chemical name</u>	<u>CAS No</u>	<u>Weight-%</u>	<u>Hazardous Air Pollutant (HAP)</u>
Kaolin, calcined	66402-68-4	1 - 5	Listed

**US State Regulations**

**California Proposition 65**

 **WARNING:** This product can expose you to chemicals including Titanium dioxide, which are known to the State of California to cause cancer, and Ethylene glycol which are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**U.S. State Right-to-Know Regulations**

<u>Chemical name</u>	<u>Massachusetts</u>	<u>New Jersey</u>	<u>Pennsylvania</u>
Titanium dioxide	X	X	X
Limestone	X	X	X
Silica amorphous	X		X
Kaolin, calcined		X	X
Kaolin	X	X	X

**Legend**

X - Listed

**16. OTHER INFORMATION**

**HMIS**

Health hazards 2\*  
 Flammability 0  
 Reactivity: 0  
 Personal protection -

**HMIS Legend**

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- \* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

---

*Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.*

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**Prepared By** Product Stewardship Department  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
800-225-5554

**Revision Date:** 14-Nov-2022  
**Revision Summary** Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**