

# SAFETY DATA SHEET

Revision Date: 10-Aug-2018

**Revision Number: 2** 

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

# AURA WATERBORNE EXTERIOR FLAT FINISH BASE 2

6292X 6292X WATER THINNED PAINT All Paint No information available

#### Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

#### **Emergency Telephone**

CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

### **Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1A
Carcinogenicity	Category 2

### Label elements

Warning

#### Hazard statements

May cause an allergic skin reaction Suspected of causing cancer



#### Appearance liquid

Odor little or no odor

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace Wear protective gloves

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention **Skin** IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

#### **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other information

No information available

#### Other hazards

May cause allergic skin reaction

### 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Titanium dioxide	13463-67-7	15
Barium sulfate	7727-43-7	5
Diatomaceous earth	61790-53-2	5
Zinc oxide	1314-13-2	5
Hexanedioic acid, dihydrazide	1071-93-8	0.5
Decanedioic acid,	41556-26-7	0.5
bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester		
Sodium C14-C16 olefin sulfonate	68439-57-6	0.5
Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-	330-54-1	0.5
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimeth ylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegah ydroxy-	104810-48-2	0.5

# 4. FIRST AID MEASURES

#### **General Advice**

No hazards which require special first aid measures.

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	May cause allergic skin reaction.
Notes To Physician	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity To Mechanical Impact	No
Sensitivity To Static Discharge	No
Flash Point Data Flash Point (°F) Flash Point (°C) Method	Not applicable Not applicable Not applicable
Flammability Limits In Air	
Lower flammability limit: Upper flammability limit:	Not applicable Not applicable
NFPA Health: 1 Flammability: 0	Instability: 0 Special: Not Applicable
NFPA Legend 0 - Not Hazardous 1 - Slightly 2 - Moderate 3 - High 4 - Severe	

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6	ACCIDENTAL RELEASE MEASURES
Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information	Prevent further leakage or spillage if safe to do so.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
	7. HANDLING AND STORAGE
Handling	Avoid contact with akin, avon and elething. Avoid breathing vanars, anrow mista or

Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage	Keep container tightly closed. Keep out of the reach of children.
Incompatible Materials	No information available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Titanium dioxide	10 mg/m³ - TWA	15 mg/m³ - TWA
Barium sulfate	5 mg/m³ - TWA	15 mg/m³ - TWA
	-	5 mg/m³ - TWA
Diatomaceous earth	N/E	-
		20 mppcf - TWA
Zinc oxide	2 mg/m³ - TWA	5 mg/m³ - TWA
	10 mg/m <sup>3</sup> - STEL	15 mg/m <sup>3</sup> - TWA
Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-	10 mg/m³ - TWA	N/E

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment	
Eye/Face Protection	Safety glasses with side-shields.
Skin Protection	Protective gloves and impervious clothing.
<b>Respiratory Protection</b>	In case of insufficient ventilation wear suitable respiratory equipment.
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor **Odor Threshold** Density (lbs/gal) **Specific Gravity** Hα Viscosity (cps) Solubility(ies) Water solubility **Evaporation Rate** Vapor pressure @20 °C (kPa) Vapor density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) **Boiling Point (°F) Boiling Point (°C)** Freezing Point (°F) Freezing Point (°C) Flash Point (°F) Flash Point (°C) Method Flammability (solid, gas) Upper flammability limit: Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F) Decomposition Temperature (°C) Partition coefficient** 

liquid little or no odor No information available 11.7 - 12.0 1.40 - 1.44 No information available 55 - 65 40 - 50 35 - 45 50 - 60 < 50 212 100 32 0 Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

# **10. STABILITY AND REACTIVITY**

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

### **11. TOXICOLOGICAL INFORMATION**

### **Product Information**

Information on likely routes of exposure		
Principal Routes of Exposure	Eye contact, skin contact and inhalation.	
Acute Toxicity		
Product Information	No information available	
Symptoms related to the physic	al, chemical and toxicological characteristics	
Symptoms	No information available	
Delayed and immediate effects a	as well as chronic effects from short and long-term exposure	
Eye contactMay cause slight irritation.Skin contactSubstance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.InhalationMay cause irritation of respiratory tract.IngestionIngestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.SensitizationMay cause an allergic skin reactionNeurological EffectsNo information available.Mutagenic EffectsNo information available.Developmental EffectsNo information available.STOT - single exposureNo information available.STOT - repeated exposureNo information available.Other adverse effectsNo information available.No information available.No information available.Stort - repeated exposureNo information available.No information available.No information available.Stort - repeated exposureNo information available.No information available.No information available.Stort - repeated exposureNo information available.Other adverse effectsNo information available.No information available.No information available.Stort - repeated exposureNo information available.No information available.No information available.Stort - repeated exposureNo information available.No information available.		
Numerical measures of toxicity The following values are calcula	ted based on chapter 3.1 of the GHS document	
ATEmix (oral) ATEmix (inhalation-dust/mist)	10012 mg/kg 45.4 mg/L	
Component Information		
Titanium dioxide   LD50 Oral: > 10000 mg/kg (Rat)   Barium sulfate   LD50 Oral: > 5,000 g/kg (Rat) vendor data   Zinc oxide   LD50 Oral: 5000 mg/kg (Rat)   LC50 Inhalation (Dust): > 5700 mg/m³ (Rat, 4 hr.)   Decanedioic acid, bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester   Sensitization May cause sensitization by skin contact   Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-   LD50 Oral: 1017 mg/kg (Rat)   LD50 Dermal: > 5000 mg/kg (Rat)   Poly(oxy-1,2-ethanediyl),   .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegahydroxy-   Sensitization May cause sensitization by skin contact		

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

**12. ECOLOGICAL INFORMATION** 

## **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

#### **Product Information**

#### Acute Toxicity to Fish

No information available

#### Acute Toxicity to Aquatic Invertebrates

No information available

#### Acute Toxicity to Aquatic Plants

No information available

### Persistence / Degradability

No information available.

#### **Bioaccumulation**

There is no data for this product.

#### Mobility in Environmental Media

No information available.

#### <u>Ozone</u>

No information available

#### **Component Information**

#### Acute Toxicity to Fish

# Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>Urea, N-(3,4-dichlorophenyl)-N,N-dimethyl-</u> LC50: 3.5 mg/L (Rainbow Trout - 96 hr.)

# Acute Toxicity to Aquatic Invertebrates

No information available

#### Acute Toxicity to Aquatic Plants

No information available

	13. DISPOSAL CONSIDERATIONS
Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.
	14. TRANSPORT INFORMATION
DOT	Not regulated
ICAO / IATA	Not regulated
IMDG / IMO	Not regulated
	15. REGULATORY INFORMATION

# International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	No - Not all of the components are listed.
	One or more component is listed on NDSL.

# Federal Regulations

SARA 311/312 hazardous categorization	
Acute health hazard	

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical name	CAS No.	Weight-%	CERCLA/SARA 313 (de minimis concentration)
Barium sulfate	7727-43-7	5	1.0
Zinc oxide	1314-13-2	5	1.0

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

### US State Regulations

#### California Proposition 65

# **WARNING:** Cancer and Reproductive Harm– www.P65warnings.ca.gov

#### State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Titanium dioxide	Х	Х	X
Barium sulfate	Х	X	X
Diatomaceous earth		Х	
Zinc oxide	Х	X	X
Urea,	Х	X	Х
N-(3,4-dichlorophenyl)-N,N-dimethyl-			

#### Legend

X - Listed

## **16. OTHER INFORMATION**

HMIS -

Flammability: 0

Reactivity: 0 PPE: -

#### HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Health: 1\*

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	10-Aug-2018
Revision Summary	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

### **END OF SAFETY DATA SHEET**