



LENMAR[®]

SAFETY DATA SHEET

Revision Date: 21-Apr-2021

Revision Number: 2

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name ULTRALAQ PRECATALYZED WATER WHITE LACQUER FLAT
Product Code 1D-351FR
Alternate Product Code HL5648
Product Class LACQUER
Color Clear
Recommended use Clear coating
Restrictions on use No information available

Manufactured For

Benjamin Moore & Co., Limited
8775 Keele Street
Concord ON L4K 2N1
Phone: 1-800-361-5898
www.lenmar-coatings.ca

Manufacturer

Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 1-866-708-9180
www.lenmar-coatings.com

Emergency Telephone

CHEMTREC: +1 703-741-5970 / 1-800-424-9300
+1 703-527-3887 (outside US & Canada)
CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

| | |
|--|------------|
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 1 |
| Carcinogenicity | Category 2 |
| Reproductive toxicity | Category 2 |
| Specific target organ toxicity (single exposure) | Category 3 |
| Specific target organ toxicity (repeated exposure) | Category 2 |
| Flammable liquids | Category 2 |
| Physical hazard not otherwise classified | Category 1 |

Label elements

Danger

Hazard statements

Causes skin irritation
Causes serious eye damage
Suspected of causing cancer
Suspected of damaging fertility or the unborn child
May cause drowsiness or dizziness
May cause damage to organs through prolonged or repeated exposure
Highly flammable liquid and vapor
Reactive flammable material



Appearance liquid

Odor solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing

Immediately call a POISON CENTER or doctor/physician

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical name | CAS No. | Weight-% | Hazardous Material Information Review Act registry number (HMIRA registry #) | Date HMIRA filed and date exemption granted (if applicable) |
|---|-----------|-------------|--|---|
| Ethanol | 64-17-5 | 10 - 30% | - | - |
| n-Butyl acetate | 123-86-4 | 10 - 30% | - | - |
| Acetone | 67-64-1 | 7 - 13% | - | - |
| cellulose, nitrate | 9004-70-0 | 5 - 10% | - | - |
| Isopropyl alcohol | 67-63-0 | 3 - 7% | - | - |
| Isobutyl alcohol | 78-83-1 | 1 - 5% | - | - |
| Propylene glycol monomethyl ether acetate | 108-65-6 | 1 - 5% | - | - |
| 2-Butoxyethanol | 111-76-2 | 1 - 5% | - | - |
| Toluene | 108-88-3 | 1 - 5% | - | - |
| Xylene | 1330-20-7 | 1 - 5% | - | - |
| Silica amorphous | 7631-86-9 | 1 - 5% | - | - |
| Ethyl benzene | 100-41-4 | 0.25 - 0.5% | - | - |

Confidential Business Information note

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediate medical attention is required. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes.

Skin Contact

Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Inhalation

Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.

Ingestion

Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.

| | |
|--|------------------------------------|
| Protection Of First-Aiders | Use personal protective equipment. |
| Most Important Symptoms/Effects | No information available. |
| Notes To Physician | Treat symptomatically. |

5. FIRE-FIGHTING MEASURES

| | |
|--|---|
| Flammable Properties | Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause flash fire. |
| Suitable Extinguishing Media | Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Protective equipment and precautions for firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| Hazardous combustion products | Burning may result in carbon dioxide, carbon monoxide and other combustion products of varying composition which may be toxic and/or irritating. |
| Specific Hazards Arising From The Chemical | Flammable. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. Closed containers may rupture if exposed to fire or extreme heat. Thermal decomposition can lead to release of irritating gases and vapors. |
| Sensitivity to mechanical impact | No |
| Sensitivity to static discharge | Yes |
| Flash Point Data | |
| Flash point (°F) | 29 |
| Flash Point (°C) | -2 |
| Method | PMCC |
| Flammability Limits In Air | |
| Lower flammability limit: | Not available |
| Upper flammability limit: | Not available |

NFPA Health: 2 Flammability: 3 Instability: 1 Special: Not Applicable

NFPA Legend
 0 - Not Hazardous
 1 - Slightly
 2 - Moderate
 3 - High
 4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Remove all sources of ignition. Take precautions to prevent flashback. Ground and bond all containers and handling equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.

Other Information

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Environmental precautions

See Section 12 for additional Ecological Information.

Methods for Cleaning Up

Dam up. Soak up with inert absorbent material. Use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling

Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe vapors or spray mist. Use only in ventilated areas. Prevent vapor build-up by providing adequate ventilation during and after use.

Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Ignition and/or flash back may occur.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.

Incompatible Materials

Incompatible with strong acids and bases and strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

| Chemical name | ACGIH TLV | Alberta | British Columbia | Ontario | Quebec |
|---|-------------------------------|--|---|---|--|
| Ethanol | STEL: 1000 ppm | 1000 ppm - TWA 1880 mg/m ³ - TWA | 1000 ppm - STEL | 1000 ppm - STEL | 1000 ppm - TWAEV 1880 mg/m ³ - TWAEV |
| n-Butyl acetate | STEL: 150 ppm TWA: 50 ppm | 150 ppm - TWA 713 mg/m ³ - TWA 200 ppm - STEL 950 mg/m ³ - STEL | 20 ppm - TWA | 150 ppm - TWA 200 ppm - STEL | 150 ppm - TWAEV 713 mg/m ³ - TWAEV 200 ppm - STEV 950 mg/m ³ - STEV |
| Acetone | STEL: 500 ppm TWA: 250 ppm | 500 ppm - TWA 1200 mg/m ³ - TWA 750 ppm - STEL 1800 mg/m ³ - STEL | 250 ppm - TWA 500 ppm - STEL | 250 ppm - TWA 500 ppm - STEL | 500 ppm - TWAEV 1190 mg/m ³ - TWAEV 1000 ppm - STEV 2380 mg/m ³ - STEV |
| Isopropyl alcohol | STEL: 400 ppm TWA: 200 ppm | 200 ppm - TWA 492 mg/m ³ - TWA 400 ppm - STEL 984 mg/m ³ - STEL | 200 ppm - TWA 400 ppm - STEL | 200 ppm - TWA 400 ppm - STEL | 400 ppm - TWAEV 985 mg/m ³ - TWAEV 500 ppm - STEV 1230 mg/m ³ - STEV |
| Isobutyl alcohol | TWA: 50 ppm | 50 ppm - TWA 152 mg/m ³ - TWA | 50 ppm - TWA | 50 ppm - TWA | 50 ppm - TWAEV 152 mg/m ³ - TWAEV |
| Propylene glycol monomethyl ether acetate | N/E | N/E | 50 ppm - TWA 75 ppm - STEL | 50 ppm - TWA 270 mg/m ³ - TWA | N/E |
| 2-Butoxyethanol | TWA: 20 ppm | 20 ppm - TWA 97 mg/m ³ - TWA | 20 ppm - TWA | 20 ppm - TWA | 20 ppm - TWAEV 97 mg/m ³ - TWAEV |
| Toluene | TWA: 20 ppm | 50 ppm - TWA 188 mg/m ³ - TWA Substance may be readily absorbed through intact skin | 20 ppm - TWA Adverse reproductive effect | 20 ppm - TWA | 50 ppm - TWAEV 188 mg/m ³ - TWAEV Skin absorption can contribute to overall exposure. |
| Xylene | STEL: 150 ppm TWA: 100 ppm | 100 ppm - TWA 434 mg/m ³ - TWA 150 ppm - STEL 651 mg/m ³ - STEL | 100 ppm - TWA 150 ppm - STEL | 100 ppm - TWA 150 ppm - STEL | 100 ppm - TWAEV 434 mg/m ³ - TWAEV 150 ppm - STEV 651 mg/m ³ - STEV |
| Ethyl benzene | TWA: 20 ppm | 100 ppm - TWA 434 mg/m ³ - TWA 125 ppm - STEL 543 mg/m ³ - STEL | 20 ppm - TWA | 20 ppm - TWA | 100 ppm - TWAEV 434 mg/m ³ - TWAEV 125 ppm - STEV 543 mg/m ³ - STEV |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
 Alberta - Alberta Occupational Exposure Limits
 British Columbia - British Columbia Occupational Exposure Limits
 Ontario - Ontario Occupational Exposure Limits
 Quebec - Quebec Occupational Exposure Limits
 N/E - Not established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields. If splashes are likely to occur, wear: Tightly fitting safety goggles

Skin Protection

Protective gloves and impervious clothing.

Respiratory Protection

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------|--------------------------|
| Appearance | liquid |
| Odor | solvent |
| Odor Threshold | No information available |
| Density (lbs/gal) | 7.75 - 7.85 |
| Specific Gravity | 0.92 - 0.94 |
| pH | No information available |
| Viscosity (cps) | No information available |
| Solubility(ies) | No information available |
| Water solubility | No information available |
| Evaporation Rate | No information available |
| Vapor pressure | No information available |
| Vapor density | No information available |
| Wt. % Solids | 25 - 35 |
| Vol. % Solids | 20 - 30 |
| Wt. % Volatiles | 65 - 75 |
| Vol. % Volatiles | 70 - 80 |
| VOC Regulatory Limit (g/L) | < 680 |
| Boiling Point (°F) | 136 |
| Boiling Point (°C) | 58 |
| Freezing point (°F) | No information available |
| Freezing Point (°C) | No information available |
| Flash point (°F) | 29 |
| Flash Point (°C) | -2 |
| Method | PMCC |
| Flammability (solid, gas) | Not applicable |
| Upper flammability limit: | Not applicable |
| Lower flammability limit: | Not applicable |
| Autoignition Temperature (°F) | No information available |
| Autoignition Temperature (°C) | No information available |
| Decomposition Temperature (°F) | No information available |
| Decomposition Temperature (°C) | No information available |
| Partition coefficient | No information available |

10. STABILITY AND REACTIVITY

| | |
|------------------------|---|
| Reactivity | Not Applicable |
| Chemical Stability | Stable under normal conditions. Hazardous polymerisation does not occur. |
| Conditions to avoid | Keep away from open flames, hot surfaces, static electricity and sources of ignition. Sparks. Elevated temperature. |
| Incompatible Materials | Incompatible with strong acids and bases and strong |

| | |
|---|---|
| | oxidizing agents. |
| Hazardous Decomposition Products | Thermal decomposition can lead to release of irritating gases and vapors. |
| Possibility of hazardous reactions | None under normal conditions of use. |

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure

Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact

Severely irritating to eyes. May cause burns. Risk of serious damage to eyes.

Skin contact

May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the skin and produce dermatitis.

Inhalation

Harmful by inhalation. High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.

Ingestion

Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Sensitization

No information available.

Neurological Effects

No information available.

Mutagenic Effects

No information available.

Reproductive Effects

Possible risk of impaired fertility. Possible risk of harm to the unborn child.

Developmental Effects

No information available.

Target organ effects

No information available.

STOT - single exposure

May cause disorder and damage to the, Respiratory system, Central nervous system.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled, May cause disorder and damage to the, liver, kidney, spleen, blood, Causes damage to organs through prolonged or repeated exposure if swallowed,

Other adverse effects
Aspiration Hazard

Causes damage to organs through prolonged or repeated exposure in contact with skin, Causes damage to organs through prolonged or repeated exposure.

No information available.

May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

| | |
|-------------------------------|------------|
| ATEmix (oral) | 4882 mg/kg |
| ATEmix (dermal) | 7621 mg/kg |
| ATEmix (inhalation-dust/mist) | 96.5 mg/L |
| ATEmix (inhalation-vapor) | 428.9 mg/L |

Component Information

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|-----------------------|--------------------------|---------------------------------------|
| Ethanol 64-17-5 | = 7060 mg/kg (Rat) | - | = 124.7 mg/L (Rat) 4 h |
| n-Butyl acetate 123-86-4 | = 10768 mg/kg (Rat) | > 17600 mg/kg (Rabbit) | - |
| Acetone 67-64-1 | = 5800 mg/kg (Rat) | > 15700 mg/kg (Rabbit) | = 50100 mg/m ³ (Rat) 8 h |
| cellulose, nitrate 9004-70-0 | 5 g/kg (Rat) | - | - |
| Isopropyl alcohol 67-63-0 | = 1870 mg/kg (Rat) | = 4059 mg/kg (Rabbit) | = 72600 mg/m ³ (Rat) 4 h |
| Isobutyl alcohol 78-83-1 | = 2460 mg/kg (Rat) | = 3400 mg/kg (Rabbit) | > 6.5 mg/L (Rat) 4 h |
| Propylene glycol monomethyl ether acetate 108-65-6 | = 8532 mg/kg (Rat) | > 5 g/kg (Rabbit) | - |
| 2-Butoxyethanol 111-76-2 | = 1300 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 4.9 mg/L (Rat) 3H |
| Toluene 108-88-3 | = 2600 mg/kg (Rat) | = 12000 mg/kg (Rabbit) | - |
| Xylene 1330-20-7 | = 3500 mg/kg (Rat) | > 4350 mg/kg (Rabbit) | = 29.08 mg/L (Rat) 4 h |
| Silica amorphous 7631-86-9 | = 7900 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 2.2 mg/L (Rat) 1 h |
| Ethyl benzene 100-41-4 | = 3500 mg/kg (Rat) | = 15400 mg/kg (Rabbit) | = 17.4 mg/L (Rat) 4 h |

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen.:

| Chemical name | IARC | NTP |
|---------------|--------------------------------|-----|
| Ethyl benzene | 2B - Possible Human Carcinogen | |

Legend

IARC - International Agency for Research on Cancer
NTP - National Toxicity Program
OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component Information

Acute Toxicity to Fish

n-Butyl acetate

LC50: 18 mg/L (Fathead Minnow - 96 hr.)

Acetone

LC50: 8300 (Bluegill - 96 hr.) mg/L

2-Butoxyethanol

LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

Xylene

LC50: 13.5 mg/L (Rainbow Trout - 96 hr.)

Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

n-Butyl acetate

EC50: 72.8 mg/L (Daphnia magna - 48 hr.)
Acetone
EC50: 12600 mg/L (Daphnia magna - 48 hr.)
Ethyl benzene
EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic Plants

n-Butyl acetate
EC50: 674.7 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)
Ethyl benzene
EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Empty Container Warning

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

14. TRANSPORT INFORMATION

TDG

Proper Shipping Name
Hazard class
UN-No.
Packing Group
Description

PAINT
3
UN1263
II
UN1263, PAINT, 3, II

ICAO / IATA

Contact the preparer for further information.

IMDG / IMO

Contact the preparer for further information.

15. REGULATORY INFORMATION

International Inventories

TSCA: United States
DSL: Canada

Yes - All components are listed or exempt.
Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1- 4

This product contains the following Parts 1-4 NPRI chemicals:

| <u>Chemical name</u> | <u>CAS No.</u> | <u>Weight-%</u> | <u>NPRI Parts 1- 4</u> |
|----------------------|----------------|-----------------|------------------------|
| Isopropyl alcohol | 67-63-0 | 3 - 7% | Listed |
| Isobutyl alcohol | 78-83-1 | 1 - 5% | Listed |
| 2-Butoxyethanol | 111-76-2 | 1 - 5% | Listed |
| Toluene | 108-88-3 | 1 - 5% | Listed |
| Xylene | 1330-20-7 | 1 - 5% | Listed |
| Ethyl benzene | 100-41-4 | 0.25 - 0.5% | Listed |

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

| <u>Chemical name</u> | <u>CAS No.</u> | <u>Weight-%</u> | <u>NPRI Part 5</u> |
|---|----------------|-----------------|--------------------|
| Ethanol | 64-17-5 | 10 - 30% | Listed |
| n-Butyl acetate | 123-86-4 | 10 - 30% | Listed |
| Isopropyl alcohol | 67-63-0 | 3 - 7% | Listed |
| Propylene glycol monomethyl ether acetate | 108-65-6 | 1 - 5% | Listed |
| 2-Butoxyethanol | 111-76-2 | 1 - 5% | Listed |
| Toluene | 108-88-3 | 1 - 5% | Listed |
| Xylene | 1330-20-7 | 1 - 5% | Listed |

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

16. OTHER INFORMATION

HMIS - Health: 2* Flammability: 3 Reactivity: 1 PPE: -

HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
800-225-5554

Revision Date: 21-Apr-2021
Reason for revision Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet