



LENMAR[®]

SAFETY DATA SHEET

Revision Date: 31-Mar-2021

Revision Number: 4

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name QUICKSTAIN LACQUER WIPING STAINS SPICE BROWN
Product Code 1LS-1206
Alternate Product Code TE7077
Product Class STAIN
Color brown
Recommended use STAIN
Restrictions on use No information available

Manufacturer

Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 1-866-708-9180
www.lenmar-coatings.com

Emergency Telephone

CHEMTREC: +1 703-741-5970 / 1-800-424-9300
+1 703-527-3887 (outside US & Canada)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements

Danger

Hazard statements

Harmful if swallowed
Causes skin irritation
Causes serious eye irritation
Suspected of causing cancer
May cause respiratory irritation. May cause drowsiness or dizziness
Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



Appearance liquid

Odor solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Wear eye/face protection
Do not breathe dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Rinse mouth

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
2-Butoxyethanol	111-76-2	30 - 35
Distillates, petroleum, hydrotreated light	64742-47-8	10 - 15
n-Butyl acetate	123-86-4	5 - 10
Stoddard solvent	8052-41-3	1 - 5
Acetone	67-64-1	1 - 5
cellulose, nitrate	9004-70-0	1 - 5
VM&P naphtha	64742-89-8	1 - 5
Iron oxide	1309-37-1	1 - 5
Isopropyl alcohol	67-63-0	1 - 5
Odorless Mineral Spirits	64741-65-7	1 - 5
Solvent naphtha, petroleum, medium aliphatic	64742-88-7	1 - 5
Carbon black	1333-86-4	0.1 - 0.5

4. FIRST AID MEASURES

Description of first aid measures

General Advice

If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

Skin Contact

Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Inhalation

Move to fresh air. If symptoms persist, call a physician.
 If not breathing, give artificial respiration. Call a physician immediately.

Ingestion

Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.

Protection Of First-Aiders

Use personal protective equipment.

Most Important Symptoms/Effects

No information available.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause flash fire.
Suitable Extinguishing Media	Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Hazardous combustion products	Burning may result in carbon dioxide, carbon monoxide and other combustion products of varying composition which may be toxic and/or irritating.
Specific Hazards Arising From The Chemical	Flammable. Flash back possible over considerable distance. Keep product and empty container away from heat and sources of ignition. Closed containers may rupture if exposed to fire or extreme heat. Thermal decomposition can lead to release of irritating gases and vapors.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	Yes
Flash Point Data	
Flash point (°F)	47
Flash Point (°C)	8
Method	PMCC
Flammability Limits In Air	
Lower flammability limit:	Not available
Upper flammability limit:	Not available

NFPA **Health:** 3 **Flammability:** 3 **Instability:** 1 **Special:** Not Applicable

- NFPA Legend**
 0 - Not Hazardous
 1 - Slightly
 2 - Moderate
 3 - High
 4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used. Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Remove all sources of ignition. Take precautions to prevent flashback. Ground and bond all containers and handling equipment. Take precautionary measures against static discharges. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Use personal protective equipment.
Other Information	Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Dam up. Soak up with inert absorbent material. Use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Handling	<p>Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe vapors or spray mist. Use only in ventilated areas. Prevent vapor build-up by providing adequate ventilation during and after use.</p> <p>Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Ignition and/or flash back may occur.</p>
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Technical measures/Precautions	<p>Ensure adequate ventilation. Use only where airflow will keep vapors from building up in or near the work area in adjoining rooms. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing and disposal of flammable liquids.</p> <p>Dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. All equipment should be non-sparking and explosion proof. Use explosion proof electrical equipment for ventilation, lighting and material handling.</p>

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
2-Butoxyethanol	TWA: 20 ppm	50 ppm - TWA 240 mg/m ³ - TWA

		prevent or reduce skin absorption
n-Butyl acetate	STEL: 150 ppm TWA: 50 ppm	150 ppm - TWA 710 mg/m ³ - TWA
Stoddard solvent	TWA: 100 ppm	500 ppm - TWA 2900 mg/m ³ - TWA
Acetone	STEL: 500 ppm TWA: 250 ppm	1000 ppm - TWA 2400 mg/m ³ - TWA
Iron oxide	TWA: 5 mg/m ³ respirable particulate matter	10 mg/m ³ - TWA 15 mg/m ³ - TWA Rouge 5 mg/m ³ - TWA Rouge
Isopropyl alcohol	STEL: 400 ppm TWA: 200 ppm	400 ppm - TWA 980 mg/m ³ - TWA
Carbon black	TWA: 3 mg/m ³ inhalable particulate matter	3.5 mg/m ³ - TWA

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits
 OSHA - Occupational Safety & Health Administration Exposure Limits
 N/E - Not Established

Appropriate engineering controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields. If splashes are likely to occur, wear:. Tightly fitting safety goggles.

Skin Protection

Long sleeved clothing. Protective gloves.

Respiratory Protection

Use only with adequate ventilation. In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	liquid
Odor	solvent
Odor Threshold	No information available
Density (lbs/gal)	7.7 - 7.8
Specific Gravity	0.92 - 0.94
pH	No information available
Viscosity (cps)	No information available
Solubility(ies)	No information available
Water solubility	No information available
Evaporation Rate	No information available
Vapor pressure	No information available
Vapor density	No information available
Wt. % Solids	10 - 20
Vol. % Solids	5 - 15
Wt. % Volatiles	80 - 90

Vol. % Volatiles	85 - 95
VOC Regulatory Limit (g/L)	<850
Boiling Point (°F)	248
Boiling Point (°C)	120
Freezing point (°F)	No information available
Freezing Point (°C)	No information available
Flash point (°F)	47
Flash Point (°C)	8
Method	PMCC
Flammability (solid, gas)	Not applicable
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Autoignition Temperature (°F)	No information available
Autoignition Temperature (°C)	No information available
Decomposition Temperature (°F)	No information available
Decomposition Temperature (°C)	No information available
Partition coefficient	No information available

10. STABILITY AND REACTIVITY

Reactivity	No data available
Chemical Stability	Stable under normal conditions. Hazardous polymerisation does not occur.
Conditions to avoid	Keep away from open flames, hot surfaces, static electricity and sources of ignition. Sparks. Elevated temperature.
Incompatible Materials	Incompatible with strong acids and bases and strong oxidizing agents.
Hazardous Decomposition Products	Thermal decomposition can lead to release of irritating gases and vapors.
Possibility of hazardous reactions	None under normal conditions of use.

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Contact with eyes may cause irritation. Vapor may cause irritation.
Skin contact May cause skin irritation and/or dermatitis. Prolonged skin contact may defat the skin and produce dermatitis.
Ingestion Harmful if swallowed. Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.
Inhalation Harmful by inhalation. High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.
Sensitization No information available
Neurological Effects No information available.
Mutagenic Effects No information available.
Reproductive Effects No information available.
Developmental Effects No information available.
Target organ effects No information available.
STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure if inhaled, May cause disorder and damage to the, liver, kidney, spleen, blood, Central nervous system, Causes damage to organs through prolonged or repeated exposure if swallowed, Causes damage to organs through prolonged or repeated exposure in contact with skin.
STOT - single exposure May cause disorder and damage to the, Respiratory system, Central nervous system.
Other adverse effects No information available.
Aspiration Hazard May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 1344 mg/kg
ATEmix (dermal) 2287 mg/kg
ATEmix (inhalation-dust/mist) 1952.7 mg/L
ATEmix (inhalation-vapor) 25.2 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butoxyethanol 111-76-2	= 1300 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 4.9 mg/L (Rat) 3H
Distillates, petroleum, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
n-Butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	-
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
cellulose, nitrate 9004-70-0	5 g/kg (Rat)	-	-

VM&P naphtha 64742-89-8	-	= 3000 mg/kg (Rabbit)	-
Iron oxide 1309-37-1	> 10000 mg/kg (Rat)	-	-
Isopropyl alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
Odorless Mineral Spirits 64741-65-7	> 7000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.04 mg/L (Rat) 4 h
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	> 25 mL/kg (Rat)	> 3000 mg/kg (Rabbit)	-
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen.:

Chemical name	IARC	NTP	OSHA
Carbon black	2B - Possible Human Carcinogen		Listed

Legend

IARC - International Agency for Research on Cancer
 NTP - National Toxicity Program
 OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

Not applicable

Component Information

Acute Toxicity to Fish

2-Butoxyethanol

LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

n-Butyl acetate

LC50: 18 mg/L (Fathead Minnow - 96 hr.)

Acetone

LC50: 8300 (Bluegill - 96 hr.) mg/L

Acute Toxicity to Aquatic Invertebrates

n-Butyl acetate

EC50: 72.8 mg/L (Daphnia magna - 48 hr.)

Acetone

EC50: 12600 mg/L (Daphnia magna - 48 hr.)

Acute Toxicity to Aquatic Plants

n-Butyl acetate

EC50: 674.7 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Empty Container Warning

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name	PAINT
Hazard class	3
UN-No.	UN1263
Packing Group	II
Description	UN1263, PAINT, 3, II

ICAO / IATA

Contact the preparer for further information.

IMDG / IMO

Contact the preparer for further information.

15. REGULATORY INFORMATION

International Inventories

TSCA: United States Yes - All components are listed or exempt.
DSL: Canada Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

<u>Chemical name</u>	<u>CAS No.</u>	<u>Weight-%</u>	<u>CERCLA/SARA 313 (de minimis concentration)</u>
2-Butoxyethanol	111-76-2	30 - 35	1.0
Isopropyl alcohol	67-63-0	1 - 5	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

<u>Chemical name</u>	<u>CAS No.</u>	<u>Weight-%</u>	<u>Hazardous Air Pollutant (HAP)</u>
2-Butoxyethanol	111-76-2	30 - 35	Listed

US State Regulations

California Proposition 65



WARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

State Right-to-Know

<u>Chemical name</u>	<u>Massachusetts</u>	<u>New Jersey</u>	<u>Pennsylvania</u>
2-Butoxyethanol	X	X	X
n-Butyl acetate	X	X	X
Stoddard solvent	X	X	X
Acetone	X	X	X
cellulose, nitrate	X	X	X
Iron oxide	X	X	X
Isopropyl alcohol	X	X	X
Carbon black	X	X	X

Legend

X - Listed

16. OTHER INFORMATION

HMIS - Health: 3* Flammability: 3 Reactivity: 1 PPE: -

HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
800-225-5554

Revision Date: 31-Mar-2021
Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet