



SAFETY DATA SHEET

Revision Date: 04-Nov-2016

Revision Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name TOUGH WALLS ACRYLIC PAINT & PRIMER SEMI-GLOSS DEEP
BASE
Product Code 22-34
Alternate Product Code TV0534
Product Class WATER THINNED PAINT
Color All
Recommended use Paint
Restrictions on use No information available

Manufacturer
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
Phone: 800-225-5554
coronadopaint.com

Emergency Telephone Number(s)
CHEMTREC (US): 800-424-9300
CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid

Odor little or no odor

Hazards not otherwise classified (HNOC)

Not Applicable

Other information

No information available

3. COMPOSITION INFORMATION ON COMPONENTS

| Chemical Name | CAS-No | Weight % (max) |
|---|------------|----------------|
| Kaolin | 1332-58-7 | 10 |
| Titanium dioxide | 13463-67-7 | 10 |
| Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol | 25265-77-4 | 5 |
| Sodium C14-C16 olefin sulfonate | 68439-57-6 | 0.5 |

4. FIRST AID MEASURES

| | |
|--|---|
| General Advice | No hazards which require special first aid measures. |
| Eye Contact | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. |
| Skin Contact | Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. |
| Inhalation | Move to fresh air. If symptoms persist, call a physician. |
| Ingestion | Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary. |
| Most Important Symptoms/Effects | None known. |
| Notes To Physician | Treat symptomatically. |

5. FIRE-FIGHTING MEASURES

| | |
|--|--|
| Suitable Extinguishing Media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Protective Equipment And Precautions For Firefighters | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| Specific Hazards Arising From The Chemical | Closed containers may rupture if exposed to fire or extreme heat. |
| Sensitivity To Mechanical Impact | No |
| Sensitivity To Static Discharge | No |
| Flash Point Data | |
| Flash Point (°F) | Not applicable |
| Flash Point (°C) | Not applicable |
| Flash Point Method | Not applicable |
| Flammability Limits In Air | |
| Lower Explosion Limit | Not applicable |
| Upper Explosion Limit | Not applicable |

NFPA **Health:** 1 **Flammability:** 0 **Instability:** 0 **Special:** Not Applicable

NFPA Legend

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

- Personal Precautions** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
- Other Information** Prevent further leakage or spillage if safe to do so.
- Environmental Precautions** See Section 12 for additional Ecological Information.
- Methods For Clean-Up** Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

- Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
- Storage** Keep container tightly closed. Keep out of the reach of children.
- Incompatible Materials** No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

| Chemical Name | ACGIH | OSHA |
|------------------|----------------------------|---|
| Kaolin | 2 mg/m ³ - TWA | 15 mg/m ³ - TWA 5 mg/m ³ - TWA |
| Titanium dioxide | 10 mg/m ³ - TWA | 15 mg/m ³ - TWA |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits
OSHA - Occupational Safety & Health Administration Exposure Limits
N/E - Not Established

- Engineering Measures** Ensure adequate ventilation, especially in confined areas.
- Personal Protective Equipment**
 - Eye/Face Protection** Safety glasses with side-shields.
 - Skin Protection** Protective gloves and impervious clothing.
 - Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment.
- Hygiene Measures** Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--------------------------|
| Appearance | liquid |
| Odor | little or no odor |
| Odor Threshold | No information available |
| Density (lbs/gal) | 9.6 - 9.7 |
| Specific Gravity | 1.15 - 1.17 |
| pH | No information available |
| Viscosity (cps) | No information available |
| Solubility | No information available |
| Water Solubility | No information available |
| Evaporation Rate | No information available |
| Vapor Pressure | No information available |
| Vapor Density | No information available |
| Wt. % Solids | 35 - 45 |
| Vol. % Solids | 25 - 35 |
| Wt. % Volatiles | 55 - 65 |
| Vol. % Volatiles | 65 - 75 |
| VOC Regulatory Limit (g/L) | < 100 |
| Boiling Point (°F) | 212 |
| Boiling Point (°C) | 100 |
| Freezing Point (°F) | 32 |
| Freezing Point (°C) | 0 |
| Flash Point (°F) | Not applicable |
| Flash Point (°C) | Not applicable |
| Flash Point Method | Not applicable |
| Flammability (solid, gas) | Not applicable |
| Upper Explosion Limit | Not applicable |
| Lower Explosion Limit | Not applicable |
| Autoignition Temperature (°F) | No information available |
| Autoignition Temperature (°C) | No information available |
| Decomposition Temperature (°F) | No information available |
| Decomposition Temperature (°C) | No information available |
| Partition Coefficient (n-octanol/water) | No information available |

10. STABILITY AND REACTIVITY

| | |
|------------------------------------|--|
| Reactivity | Not Applicable |
| Chemical Stability | Stable under normal conditions. |
| Conditions To Avoid | Prevent from freezing. |
| Incompatible Materials | No materials to be especially mentioned. |
| Hazardous Decomposition Products | None under normal use. |
| Possibility Of Hazardous Reactions | None under normal conditions of use. |

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Information on toxicological effects

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact May cause slight irritation.
Skin contact Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation May cause irritation of respiratory tract.
Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization: No information available
Neurological Effects No information available.
Mutagenic Effects No information available.
Reproductive Effects No information available.
Developmental Effects No information available.
Target Organ Effects No information available.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Other adverse effects No information available.
Aspiration Hazard No information available

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 94103 mg/kg
ATEmix (dermal) 1223382 mg/kg

Component

Kaolin

LD50 Oral: > 5000 mg/kg (Rat)

Titanium dioxide

LD50 Oral: > 10000 mg/kg (Rat)

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:

| Chemical Name | IARC | NTP | OSHA Carcinogen |
|------------------|--------------------------------|-----|-----------------|
| Titanium dioxide | 2B - Possible Human Carcinogen | | Listed |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer
 NTP - National Toxicity Program
 OSHA - Occupational Safety & Health Administration

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation / Accumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT

Not regulated

ICAO / IATA

Not regulated

IMDG / IMO

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States Yes - All components are listed or exempt.
DSL: Canada Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization

| | |
|-----------------------------------|----|
| Acute Health Hazard | No |
| Chronic Health Hazard | No |
| Fire Hazard | No |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

None

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

State Regulations

California Proposition 65

This product may contain small amounts of materials known to the state of California to cause cancer or reproductive harm.

State Right-to-Know

| Chemical Name | Massachusetts | New Jersey | Pennsylvania |
|------------------|---------------|------------|--------------|
| Kaolin | X | X | X |
| Titanium dioxide | X | X | X |

Legend

X - Listed

16. OTHER INFORMATION

HMIS - Health: 1 Flammability: 0 Reactivity: 0 PPE: -

HMIS Legend

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- * - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or

risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By Product Stewardship Department
Benjamin Moore & Co.
101 Paragon Drive
Montvale, NJ 07645
855-724-6802

Revision Date: 04-Nov-2016
Revision Summary Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET