

# SAFETY DATA SHEET

Revision Date: 24-Apr-2020

**Revision Number: 4** 

1. PRODUCT AND COMPANY IDENTIFICATION

## Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

## Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com/Coronado

**28-6** TV4206 Water thinned paint White Paint No information available

> Emergency Telephone CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

SUPER KOTE 5000 ACRYLIC LATEX PAINT FLAT BRITE WHITE

2. HAZARDS IDENTIFICATION

## **Classification**

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

## Label elements

Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Appearance liquid

Odor little or no odor

Hazards not otherwise classified (HNOC) Not applicable

Other information

No information available

# 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Kaolin, calcined	92704-41-1	10 - 15
Nepheline syenite	37244-96-5	10 - 15
Titanium dioxide	13463-67-7	5 - 10
Limestone	1317-65-3	5 - 10
Diatomaceous earth	61790-53-2	1 - 5
Propylene glycol	57-55-6	1 - 5

	4. FIRST AID MEASURES
General Advice	No hazards which require special first aid measures.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects	None known.
Notes To Physician	Treat symptomatically.
	5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity to mechanical impact	No
Sensitivity to static discharge	No
Flash Point Data Flash point (°F) Flash Point (°C)	Not applicable Not applicable

# 28-6 - SUPER KOTE 5000 ACRYLIC LATEX PAINT FLAT BRITE WHITE

Metho	od		Not applicable	
Flammat	oility Limits In Air			
	r flammability limit: r flammability limit:		Not applicable Not applicable	
<u>NFPA</u>	Health: 1	Flammability: 0	Instability: 0	Special: Not Applicable
<b>NFPA Le</b> 0 - Not Ha				

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

# 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information	Prevent further leakage or spillage if safe to do so.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
	7. HANDLING AND STORAGE
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage	Keep container tightly closed. Keep out of the reach of children.
Incompatible Materials	No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	15 mg/m³ - TWA
Limestone	N/E	15 mg/m³ - TWA 5 mg/m³ - TWA
Diatomaceous earth	N/E	- 20 mppcf - TWA

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits

 $\mathsf{OSHA}$  -  $\mathsf{Occupational}$  Safety & Health Administration Exposure Limits  $\mathsf{N/E}$  - Not Established

Engineering Measures	Ensure adequate ventilation, especially in confined areas.
Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection	Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Odorlittle or no odorOdor ThresholdNo information availableDensity (lbs/gal)11.5 - 11.9Specific Gravity1.38 - 1.42pHNo information availableViscosity (cps)No information availableSolubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information availableVapor pressureNo information availableVapor densityNo information availableWt. % Solids50 - 60Vol. % Solids30 - 40Wt. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50Boiling Point (°F)212Boiling Point (°C)100Freezing point (°C)0Flash point (°C)Not applicableFlash Point (°C)Not applicableFlash Point (°C)Not applicableFlash point (°C)Not applicableJupper flammability (solid, gas)Not applicableLower flammability limit:Not applicableLower flammability limit:Not applicable
Density (lbs/gal)11.5 - 11.9Specific Gravity1.38 - 1.42pHNo information availableViscosity (cps)No information availableSolubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information availableVapor pressureNo information availableVapor densityNo information availableWt. % Solids50 - 60Vol. % Solids30 - 40Wt. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50Boiling Point (°F)212Boiling Point (°F)32Freezing point (°F)0Flash point (°F)Not applicableFlash Point (°C)Not applicable
Specific Gravity1.38 - 1.42pHNo information availableViscosity (cps)No information availableSolubility(ies)No information availableWater solubilityNo information availableWater solubilityNo information availableEvaporation RateNo information availableVapor pressureNo information availableVapor densityNo information availableVapor densityNo information availableWt. % Solids50 - 60Vol. % Solids30 - 40Wt. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50Boiling Point (°F)212Boiling Point (°C)100Freezing point (°F)32Freezing Point (°C)0Flash point (°F)Not applicableFlash Point (°C)Not applicableMethodNot applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
pHNo information availableViscosity (cps)No information availableSolubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information availableVapor pressureNo information availableVapor densityNo information availableVapor densityNo information availableWt. % Solids50 - 60Vol. % Solids30 - 40Wt. % Volatiles40 - 50Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50Boiling Point (°F)212Boiling Point (°C)100Freezing point (°F)32Freezing Point (°C)0Flash point (°C)Not applicableFlash Point (°C)Not applicableFlash Point (°C)Not applicableFlash Point (°C)Not applicableFlash Point (°C)Not applicablePlash Point (°C)Not applicable <tr< th=""></tr<>
Viscosity (cps)No information availableSolubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information availableVapor pressureNo information availableVapor densityNo information availableWt. % Solids50 - 60Vol. % Solids30 - 40Wt. % Volatiles40 - 50Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50Boiling Point (°F)212Boiling Point (°C)100Freezing point (°F)32Freezing Point (°C)0Flash point (°C)Not applicableFlash Point (°C)Not applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
Solubility(ies)No information availableWater solubilityNo information availableEvaporation RateNo information availableVapor pressureNo information availableVapor densityNo information availableWt. % Solids50 - 60Vol. % Solids30 - 40Wt. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50Boiling Point (°F)212Boiling Point (°C)100Freezing point (°C)0Flash point (°C)0Flash point (°C)Not applicableFlash point (°C)Not applicable
Water solubilityNo information availableEvaporation RateNo information availableVapor pressureNo information availableVapor densityNo information availableWt. % Solids50 - 60Vol. % Solids30 - 40Wt. % Volatiles40 - 50Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50Boiling Point (°F)212Boiling Point (°F)32Freezing point (°F)32Freezing Point (°C)0Flash point (°C)Not applicableFlash Point (°C)<
Evaporation RateNo information availableVapor pressureNo information availableVapor densityNo information availableWt. % Solids50 - 60Vol. % Solids30 - 40Wt. % Volatiles40 - 50Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50
Vapor pressureNo information availableVapor densityNo information availableWt. % Solids50 - 60Vol. % Solids30 - 40Wt. % Volatiles40 - 50Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50
Vapor densityNo information availableWt. % Solids50 - 60Vol. % Solids30 - 40Wt. % Volatiles40 - 50Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50Boiling Point (°F)212Boiling Point (°C)100Freezing point (°F)32Freezing Point (°C)0Flash point (°F)Not applicableFlash point (°C)Not applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
Wt. % Solids50 - 60Vol. % Solids30 - 40Wt. % Volatiles40 - 50Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50Boiling Point (°F)212Boiling Point (°C)100Freezing point (°F)32Freezing Point (°C)0Flash point (°F)Not applicableFlash point (°C)Not applicableFlash point (°C)Not applicableFlash point (°C)Not applicableJudethodNot applicableMethodNot applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
Vol. % Solids30 - 40Wt. % Volatiles40 - 50Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50Boiling Point (°F)212Boiling Point (°C)100Freezing point (°F)32Freezing Point (°C)0Flash point (°F)Not applicableFlash point (°C)Not applicableFlash point (°C)Not applicableFlash point (°C)Not applicableJude HoodNot applicable
Wt. % Volatiles40 - 50Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50Boiling Point (°F)212Boiling Point (°C)100Freezing point (°F)32Freezing Point (°C)0Flash point (°F)Not applicableFlash Point (°C)Not applicableFlash Point (°C)Not applicableFlash point (°C)Not applicableJunchNot applicableMethodNot applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
Vol. % Volatiles60 - 70VOC Regulatory Limit (g/L)< 50
VOC Regulatory Limit (g/L)< 50Boiling Point (°F)212Boiling Point (°C)100Freezing point (°F)32Freezing Point (°C)0Flash point (°F)Not applicableFlash Point (°C)Not applicableMethodNot applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
Boiling Point (°F)212Boiling Point (°C)100Freezing point (°F)32Freezing Point (°C)0Flash point (°F)Not applicableFlash Point (°C)Not applicableMethodNot applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
Boiling Point (°C)100Freezing point (°F)32Freezing Point (°C)0Flash point (°F)Not applicableFlash Point (°C)Not applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
Freezing point (°F)32Freezing Point (°C)0Flash point (°F)Not applicableFlash Point (°C)Not applicableMethodNot applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
Freezing Point (°C)0Flash point (°F)Not applicableFlash Point (°C)Not applicableMethodNot applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
Flash point (°F)Not applicableFlash Point (°C)Not applicableMethodNot applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
Flash Point (°C)Not applicableMethodNot applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
MethodNot applicableFlammability (solid, gas)Not applicableUpper flammability limit:Not applicable
Flammability (solid, gas)Not applicableUpper flammability limit:Not applicable
Upper flammability limit: Not applicable
Lower flammability limit: Not applicable
Autoignition Temperature (°F) No information available
Autoignition Temperature (°C) No information available
Decomposition Temperature (°F) No information available
Decomposition Temperature (°C) No information available
Partition coefficient No information available

# **10. STABILITY AND REACTIVITY**

## Reactivity

Not Applicable

Chemical Stability	Stable under normal conditions.
Conditions to avoid	Prevent from freezing.
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.
Possibility of hazardous reactions	None under normal conditions of use.

# 11. TOXICOLOGICAL INFORMATION

Product Information		
Information on likely routes of	exposure	
Principal Routes of Exposure	Eye contact, skin contact and inhalation.	
Acute Toxicity		
Product Information	No information available	
Symptoms related to the physic	cal, chemical and toxicological characteristics	
Symptoms	No information available	
Delayed and immediate effects	as well as chronic effects from short and long-term exposure	
Eye contact Skin contact	May cause slight irritation. Substance may cause slight skin irritation. Prolonged or repeated contact may dry	
Inhalation Ingestion Sensitization Neurological Effects Mutagenic Effects Reproductive Effects Developmental Effects Target organ effects STOT - single exposure STOT - repeated exposure Other adverse effects Aspiration Hazard	skin and cause irritation. May cause irritation of respiratory tract. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. No information available No information available. No information available.	
Numerical measures of toxicity	<u>_</u>	
The following values are calculated based on chapter 3.1 of the GHS document		
ATEmix (oral) ATEmix (dermal)	15172 mg/kg 2029225 mg/kg	
Component Information		

Chemical name Oral LD50 Dermal LD50 Inhalation LC50

Kaolin, calcined 92704-41-1	> 2000 mg/kg (Rat)	-	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Propylene glycol 57-55-6	= 20 g/kg (Rat)	= 20800 mg/kg (Rabbit)	-

#### Chronic Toxicity

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

# Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

#### **Product Information**

#### Acute Toxicity to Fish

No information available

#### Acute Toxicity to Aquatic Invertebrates

No information available

#### Acute Toxicity to Aquatic Plants

No information available

#### Persistence / Degradability

No information available.

#### **Bioaccumulation**

No information available.

## Mobility in Environmental Media

No information available.

#### <u>Ozone</u>

No information available

#### **Component Information**

## Acute Toxicity to Fish

<u>Titanium dioxide</u> LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) <u>Propylene glycol</u> LC50: 710 mg/L (Fathead Minnow - 96 hr.)

#### Acute Toxicity to Aquatic Invertebrates

Propylene glycol EC50: > 10000 mg/L (Daphnia magna - 24 hr.)

#### Acute Toxicity to Aquatic Plants

No information available

	15. REGULATORY INFORMATION	
IMDG / IMO	Not regulated	
ICAO / IATA	Not regulated	
DOT	Not regulated	
	14. TRANSPORT INFORMATION	
Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.	
	13. DISPOSAL CONSIDERATIONS	

# International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

# **Federal Regulations**

#### SARA 311/312 hazardous categorization

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

# SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal

Regulations, Part 372:

None

# Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

# US State Regulations

## **California Proposition 65**

MARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

## State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Titanium dioxide	X	X	Х
Limestone	X	X	Х
Diatomaceous earth		X	

#### Legend

X - Listed

# **16. OTHER INFORMATION**

HMIS -	Health: 1	Flammability: 0	Reactivity: 0	PPE: -	
--------	-----------	-----------------	---------------	--------	--

#### HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to

www.epa.gov/lead.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	24-Apr-2020
Revision Summary	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

## **End of Safety Data Sheet**