

# **SAFETY DATA SHEET**

Revision Date: 10-May-2019 Revision Number: 6

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

ULTRA SPEC HP D.T.M. ACRYLIC GLOSS ENAMEL BASE 4

Product Code

HP284X

Product Code HP284X
Alternate Product Code HP284X

Product Class Water thinned paint

Color

Recommended use Industrial paint

Restrictions on use No information available

Manufacturer Emergency Telephone

Benjamin Moore & Co. CHEMTREC (US): 800-424-9300
101 Paragon Drive CHEMTREC (outside US): (703)-527-3887

ΑII

Montvale, NJ 07645 Phone: 1-866-708-9180 www.benjaminmoore.com

# 2. HAZARDS IDENTIFICATION

## Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Reproductive toxicity Category 2

#### Label elements

#### Warning

#### Hazard statements

Suspected of damaging fertility or the unborn child



Appearance liquid Odor little or no odor

HP284X - ULTRA SPEC HP D.T.M. ACRYLIC GLOSS

**ENAMEL BASE 4** 

**Precautionary Statements - Prevention** 

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

**Precautionary Statements - Response** 

IF exposed or concerned: Get medical advice/attention

**Precautionary Statements - Storage** 

Store locked up

**Precautionary Statements - Disposal** 

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

## 3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
2,2,4-trimethyl-1,3-propanediol diisobutyrate	6846-50-0	1 - 5
Zinc phosphate	7779-90-0	1 - 5

## 4. FIRST AID MEASURES

**General Advice** No hazards which require special first aid measures.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a

physician.

Skin Contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes.

**Inhalation** Move to fresh air. If symptoms persist, call a physician.

**Ingestion** Clean mouth with water and afterwards drink plenty of water. Consult a physician

if necessary.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Revision Date: 10-May-2019

HP284X - ULTRA SPEC HP D.T.M. ACRYLIC GLOSS ENAMEL BASE 4

**Protective equipment and precautions for firefighters** As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

Revision Date: 10-May-2019

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Sensitivity to mechanical impact No

Sensitivity to static discharge No

**Flash Point Data** 

Flash point (°F) 250
Flash Point (°C) 121
Method PMCC

Flammability Limits In Air

Lower flammability limit:Not applicableUpper flammability limit:Not applicable

NFPA Health: 1 Flammability: 1 Instability: 0 Special: Not Applicable

#### **NFPA Legend**

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information** Prevent further leakage or spillage if safe to do so.

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

#### 7. HANDLING AND STORAGE

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or

sanding dust. In case of insufficient ventilation, wear suitable respiratory

equipment.

**Storage** Keep container tightly closed. Keep out of the reach of children.

Revision Date: 10-May-2019

**Incompatible Materials** No information available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Limits**

No exposure limits have been established for this product.

Legend

N/A - Not applicable

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Safety glasses with side-shields. **Eye/Face Protection** 

**Skin Protection** Protective gloves and impervious clothing.

In case of insufficient ventilation wear suitable respiratory equipment. **Respiratory Protection** 

Avoid contact with skin, eyes and clothing. Remove and wash contaminated **Hygiene Measures** 

clothing before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** liquid

Odor little or no odor

**Odor Threshold** No information available

Density (lbs/gal) 83-87 1.00 - 1.04 **Specific Gravity** 

Hq No information available

Viscosity (cps) No information available Solubility(ies) No information available Water solubility No information available **Evaporation Rate** No information available

Vapor pressure No information available Vapor density No information available

Wt. % Solids 35 - 45 35 - 45 Vol. % Solids Wt. % Volatiles 55 - 65

Vol. % Volatiles 55 - 65 VOC Regulatory Limit (g/L) < 150 **Boiling Point (°F)** 212 **Boiling Point (°C)** 100 Freezing point (°F) 32 Freezing Point (°C) 0 250 Flash point (°F) Flash Point (°C) 121

Method Flammability (solid, gas) Not applicable **Upper flammability limit:** Not applicable Lower flammability limit: Not applicable

**Autoignition Temperature (°F)** No information available

**PMCC** 

HP284X - ULTRA SPEC HP D.T.M. ACRYLIC GLOSS

**ENAMEL BASE 4** 

Revision Date: 10-May-2019

Autoignition Temperature (°C)No information availableDecomposition Temperature (°F)No information availableDecomposition Temperature (°C)No information availablePartition coefficientNo information available

## 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

Possibility of hazardous reactions None under normal conditions of use.

## 11. TOXICOLOGICAL INFORMATION

#### **Product Information**

Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Toxicity** 

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eye contact** May cause slight irritation.

**Skin contact** Substance may cause slight skin irritation. Prolonged or repeated contact may dry

skin and cause irritation.

**Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

SensitizationNo information availableNeurological EffectsNo information availableMutagenic EffectsNo information available

**Reproductive Effects** Possible risk of impaired fertility. Possible risk of harm to the unborn child.

Developmental EffectsNo information available.Target organ effectsNo information available.STOT - single exposureNo information available.STOT - repeated exposureNo information available.Other adverse effectsNo information available.Aspiration HazardNo information available

HP284X - ULTRA SPEC HP D.T.M. ACRYLIC GLOSS

**ENAMEL BASE 4** 

Revision Date: 10-May-2019

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 47969 mg/kg ATEmix (dermal) 162726 mg/kg

## **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2,2,4-trimethyl-1,3-propanediol diisobutyrate 6846-50-0	> 3200 mg/kg ( Rat )	-	-
Zinc phosphate 7779-90-0	> 5000 mg/kg (Rat)	-	-

#### Carcinogenicity

There are no known carcinogenic chemicals in this product above reportable levels.

## 12. ECOLOGICAL INFORMATION

## **Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

#### **Product Information**

## **Acute Toxicity to Fish**

No information available

## **Acute Toxicity to Aquatic Invertebrates**

No information available

#### **Acute Toxicity to Aquatic Plants**

No information available

#### Persistence / Degradability

No information available.

#### **Bioaccumulation**

No information available.

#### **Mobility in Environmental Media**

No information available.

#### Ozone

No information available

# **Component Information**

#### **Acute Toxicity to Fish**

No information available

HP284X - ULTRA SPEC HP D.T.M. ACRYLIC GLOSS ENAMEL BASE 4

#### **Acute Toxicity to Aquatic Invertebrates**

No information available

## **Acute Toxicity to Aquatic Plants**

No information available

#### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with federal, state, and local regulations. Local

requirements may vary, consult your sanitation department or state-designated

Revision Date: 10-May-2019

environmental protection agency for more disposal options.

## 14. TRANSPORT INFORMATION

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

#### 15. REGULATORY INFORMATION

# **International Inventories**

**TSCA: United States**Yes - All components are listed or exempt.
Yes - All components are listed or exempt.

# Federal Regulations

## SARA 311/312 hazardous categorization

Acute health hazard No
Chronic Health Hazard Yes
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical name	CAS No.	Weight-%	CERCLA/SARA 313
			(de minimis concentration)
Zinc phosphate	7779-90-0	1 - 5	1.0

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Revision Date: 10-May-2019

None

# **US State Regulations**

#### **California Proposition 65**



⚠ WARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

#### State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Zinc phosphate		X	X

## Legend

X - Listed

#### 16. OTHER INFORMATION

HMIS -Health: 1\* Flammability: 1 Reactivity: 0 PPE: -

## **HMIS Legend**

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- \* Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

**Product Stewardship Department** Prepared By

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

**Revision Date:** 10-May-2019

HP284X - ULTRA SPEC HP D.T.M. ACRYLIC GLOSS ENAMEL BASE 4

Revision Date: 10-May-2019

Revision Summary

Not available

#### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**