



Revision Date: 17-Oct-2023 Revision Number: 4

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name WATERBORNE AMINE EPOXY PASTEL BASE

Product Code V440-85FR

Alternate Product Code A44085

Product Class WATERBORNE EPOXY

Color All

Recommended use Industrial paint

Restrictions on use No information available

Manufactured For

Benjamin Moore & Co., Limited

8775 Keele Street Concord ON L4K 2N1 Phone: 1-800-361-5898

www.benjaminmoore.ca/corotech

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

Phone: 1-866-708-9180

www.benjaminmoore.com/Corotech

Emergency Telephone

CHEMTREC: +1 703-741-5970 / 1-800-424-9300 +1 703-527-3887 (outside US & Canada)

CANUTEC: 613-996-6666 (Transport Emergency Only)

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

Label elements

Danger		

V440-85FR - WATERBORNE AMINE EPOXY PASTEL BASE

Hazard statements

Causes skin irritation

Causes serious eye damage

May cause cancer

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure



Appearance liquid

Odor little or no odor

Revision Date: 17-Oct-2023

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsina

Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

No information available

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

CAUTION: All floor coatings may become slippery when wet. Where non-skid characteristics are desired, use an appropriate anti-slip aggregate.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Titanium dioxide	13463-67-7	10 - 30%	-	-
Aliphatic polyamine	-	10 - 30%	HMIRC # 9649	Granted: April 21, 2016
Silica, crystalline	14808-60-7	7 - 13%	-	-
2-Propoxyethanol	2807-30-9	1 - 5%	-	-
2-Butoxyethanol	111-76-2	1 - 5%	-	-
Dipropylene glycol monomethyl ether	34590-94-8	1 - 5%	-	-

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice Immediately call a POISON CENTER or doctor/physician.

Eye Contact Immediate medical attention is required. Immediately flush

with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15

Revision Date: 17-Oct-2023

minutes. Keep eye wide open while rinsing.

Skin Contact Immediate medical attention is required. Wash off

immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash clothing before

reuse.

Inhalation Call a physician or poison control center immediately.

Move to fresh air. If not breathing, give artificial respiration.

Ingestion Never give anything by mouth to an unconscious person.

Immediate medical attention is required. Drink 1 or 2 glasses of water. Do not induce vomiting without medical

advice.

Protection Of First-Aiders

Use personal protective equipment.

Most Important Symptoms/Effects None known.

Notes To Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective equipment and precautions for firefighters As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent)

and full protective gear.

Specific Hazards Arising From The Chemical Closed containers may rupture if exposed to fire or

extreme heat.

Revision Date: 17-Oct-2023

Sensitivity to mechanical impact No

Sensitivity to static discharge No

Flash Point Data

Flash point (°F) Not Applicable Flash Point (°C) Not applicable Method Not applicable

Flammability Limits In Air

Lower flammability limit:Not applicableUpper flammability limit:Not applicable

NFPA

Health hazards 2
Flammability 0
Stability 0

Special: Not Applicable

NFPA Legend

0 - Not Hazardous

- 1 Slightly
- 2 Moderate
- 3 High
- 4 Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Avoid contact with skin, eyes and clothing. Ensure

adequate ventilation.

Other Information Prevent further leakage or spillage if safe to do so.

Environmental precautionsSee Section 12 for additional Ecological Information.

Methods for Cleaning Up Soak up with inert absorbent material. Sweep up and

shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling Avoid contact with skin, eyes and clothing. Avoid breathing

vapors, spray mists or sanding dust. In case of insufficient

ventilation, wear suitable respiratory equipment.

Storage Keep container tightly closed. Keep out of the reach of

children.

Incompatible Materials

No information available

Revision Date: 17-Oct-2023

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	Alberta	British Columbia	Ontario	Quebec
Titanium dioxide	TWA: 0.2 mg/m³ nanoscale respirable particulate matter TWA: 2.5 mg/m³ finescale respirable particulate matter	10 mg/m³ - TWA	10 mg/m³ - TWA 3 mg/m³ - TWA	10 mg/m³ - TWA	10 mg/m³ - TWAEV
Silica, crystalline	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.1 mg/m ³
2-Propoxyethanol	-	-	-	25 ppm - TWA 110 mg/m³ - TWA Danger of cutaneous absorption	-
2-Butoxyethanol	TWA: 20 ppm	TWA: 20 ppm TWA: 97 mg/m ³	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm
Dipropylene glycol monomethyl ether	TWA: 50 ppm	100 ppm - TWA 606 mg/m³ - TWA 150 ppm - STEL 909 mg/m³ - STEL Substance may be readily absorbed through intact skin	100 ppm - TWA 150 ppm - STEL Skin absorption can contribute to overall exposure.	100 ppm - TWA 150 ppm - STEL Danger of cutaneous absorption	100 ppm - TWAEV 606 mg/m³ - TWAEV 150 ppm - STEV 909 mg/m³ - STEV Skin absorption can contribute to overall exposure.

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Alberta - Alberta Occupational Exposure Limits

British Columbia - British Columbia Occupational Exposure Limits

Ontario - Ontario Occupational Exposure Limits Quebec - Quebec Occupational Exposure Limits

N/E - Not established

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Skin Protection

Respiratory Protection

Safety glasses with side-shields

Protective gloves and impervious clothing.

In case of insufficient ventilation wear suitable respiratory

equipment.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash

thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor

Odor Threshold

liauid

little or no odor

No information available

V440-85FR - WATERBORNE AMINE EPOXY PASTEL **BASE**

Revision Date: 17-Oct-2023

11.8 - 12.2 Density (lbs./qal) **Specific Gravity** 1.41 - 1.46

No information available pН Viscosity (cps) No information available Solubility(ies) No information available Water solubility No information available

No information available **Evaporation Rate** Vapor pressure @20 °C (kPa) No information available Relative vapor density No information available

55 - 65 Wt. % Solids Vol. % Solids 35 - 45 Wt. % Volatiles 35 - 45 Vol. % Volatiles 55 - 65 VOC Regulatory Limit (g/L) < 250 **Boiling Point (°F)** 212 100 **Boiling Point (°C)** Freezing point (°F) 32 Freezing Point (°C) 0

Flash point (°F) Not Applicable Flash Point (°C) Not applicable Method Not applicable Flammability (solid, gas) Not applicable Not applicable

Upper flammability limit: Not applicable Lower flammability limit:

No information available **Autoignition Temperature (°F) Autoignition Temperature (°C)** No information available **Decomposition Temperature (°F)** No information available **Decomposition Temperature (°C)** No information available **Partition coefficient** No information available

10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Conditions to avoid Prevent from freezing.

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products None under normal use.

None under normal conditions of use. Possibility of hazardous reactions

11. TOXICOLOGICAL INFORMATION

Product Information

Information on likely routes of exposure

Principal Routes of Exposure Eye contact, skin contact and inhalation.

Acute Toxicity

Product Information No information available

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Causes eye irritation Risk of serious damage to eyes May

cause burns Severely irritating to eyes

Skin contact Irritating to skin. Prolonged skin contact may cause skin

irritation and/or dermatitis. May cause burns.

Inhalation Harmful by inhalation. Causes respiratory tract irritation.

Vapours may be irritating to eyes, nose, throat, and lungs. May cause additional affects as listed under "Ingestion".

Revision Date: 17-Oct-2023

IngestionHarmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Can burn mouth,

throat, and stomach.

Sensitization
No information available.
Neurological Effects
No information available.

Developmental Effects

No information available.

Target organ effects

Liver, Kidney, Respiratory system, Eyes, Skin, Central nervous system, Blood, hematopoietic system, Lungs.

STOT - single exposure

May cause disorder and damage to the. Respiratory

system. Digestive System.

STOT - repeated exposure Causes damage to organs through prolonged or repeated

exposure if inhaled. Causes damage to organs through prolonged or repeated exposure if swallowed. kidney.

Other adverse effects

Aspiration Hazard

No information available.

No information available.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

ATEmix (dermal)

ATEmix (inhalation-dust/mist)

ATEmix (inhalation-vapor)

2208 mg/kg

14003 mg/kg

8.4 mg/l

343.6 mg/l

Component Information

Caution - This mixture contains a substance not yet fully tested

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg(Rat)	-	•
2-Propoxyethanol 2807-30-9	= 3089 mg/kg(Rat)	= 870 mg/kg (Rabbit)= 960 μL/kg (Rabbit)	= 1530 ppm (Rat) 7 h
2-Butoxyethanol 111-76-2	= 1300 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	> 4.9 mg/L (Rat) 3H
Dipropylene glycol monomethyl ether 34590-94-8	= 5.35 g/kg(Rat)	= 9500 mg/kg(Rabbit)	-

Revision Date: 17-Oct-2023

Chronic Toxicity

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP
	2B - Possible Human Carcinogen	
Titanium dioxide	_	
	1 - Human Carcinogen	Known
Silica, crystalline	_	

- Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
- Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available.

Bioaccumulation

There is no data for this product.

Mobility in Environmental Media

No information available.

Ozone

Not applicable

V440-85FR - WATERBORNE AMINE EPOXY PASTEL

BASE

Component Information

Acute Toxicity to Fish

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

2-Butoxyethanol

LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Revision Date: 17-Oct-2023

14. TRANSPORT INFORMATION

TDG Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United StatesYes - All components are listed or exempt.
Yes - All components are listed or exempt.

National Pollutant Release Inventory (NPRI)

NPRI Parts 1-4

This product contains the following Parts 1-4 NPRI chemicals:

Chemical nameCAS NoWeight-%NPRI Parts 1- 42-Butoxyethanol111-76-21 - 5%Listed

Revision Date: 17-Oct-2023

NPRI Part 5

This product contains the following NPRI Part 5 Chemicals:

Chemical nameCAS NoWeight-%NPRI Part 52-Butoxyethanol111-76-21 - 5%Listed

WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

16. OTHER INFORMATION

HMIS

Health hazards 2*
Flammability 0
Reactivity: 0
Personal protection -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at

http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked questions-questions posees-eng.php.

Prepared By Product Stewardship Department

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645

800-225-5554

Revision Date: 17-Oct-2023

V440-85FR - WATERBORNE AMINE EPOXY PASTEL BASE

Revision Date: 17-Oct-2023

Reason for revision Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

End of Safety Data Sheet