



Revision Date: 20-Sep-2018

Revision Number: 5

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Code Alternate Product Code Product Class Color Recommended use Restrictions on use

Manufacturer

Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 Phone: 1-866-708-9180 corotechcoatings.com

WATERBORNE AMINE EPOXY DEEP BASE

V440-87 V44087 WATERBORNE EPOXY All Industrial paint No information available

Emergency Telephone

CHEMTREC (US): 800-424-9300 CHEMTREC (outside US): (703)-527-3887

2. HAZARDS IDENTIFICATION

Classification


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

Label elements

Danger

Hazard statements Harmful if swallowed Causes skin irritation Causes serious eye damage May cause cancer



Odor little or no odor

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician **Eves**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Rinse mouth

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other information

No information available

Other hazards

IMPORTANT: Designed to be mixed with other components. Mixture will have hazards of all components. Before opening packages, read all warning labels. Follow all precautions.

CAUTION: All floor coatings may become slippery when wet. Where non-skid characteristics are desired, a small amount of clean sand may be added. Stir often during application.

3. COMPOSITION INFORMATION ON COMPONENTS

Chemical name	CAS No.	Weight-%
Aliphatic polyamine	-	25
Silica, crystalline	14808-60-7	15
Titanium dioxide	13463-67-7	10
2-Propoxyethanol	2807-30-9	10
2-Butoxyethanol	111-76-2	5
Dipropylene glycol monomethyl ether	34590-94-8	5
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	0.5

	4. FIRST AID MEASURES
General Advice	Immediately call a POISON CENTER or doctor/physician.
Eye Contact	Immediate medical attention is required. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.
Skin Contact	Immediate medical attention is required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash clothing before reuse.
Inhalation	Call a physician or Poison Control Center immediately. Move to fresh air. If not breathing, give artificial respiration.
Ingestion	Never give anything by mouth to an unconscious person. Immediate medical attention is required. Drink 1 or 2 glasses of water. Do not induce vomiting without medical advice.
Protection Of First-Aiders	Use personal protective equipment.
Most Important Symptoms/Effects	None known.
Notes To Physician	Treat symptomatically.
	5. FIRE-FIGHTING MEASURES

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical	Closed containers may rupture if exposed to fire or extreme heat.
Sensitivity To Mechanical Impact	No
Sensitivity To Static Discharge	No

Flash Point Data Flash Point (°F) Flash Point (°C) Method		Not applicable Not applicable Not applicable	
Flammability Limits In Air			
Lower flammability limit: Upper flammability limit:		Not applicable Not applicable	
NFPA Health: 1	Flammability: 0	Instability: 0	Special: Not Applicable
NFPA Legend 0 - Not Hazardous 1 - Slightly 2 - Moderate			

- 3 High

4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at www.nfpa.org.

6	. ACCIDENTAL RELEASE MEASURES
Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
Other Information	Prevent further leakage or spillage if safe to do so.
Environmental precautions	See Section 12 for additional Ecological Information.
Methods for Cleaning Up	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
	7. HANDLING AND STORAGE
Handling	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage	Keep container tightly closed. Keep out of the reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL
Silica, crystalline	0.025 mg/m ³ - TWA	-
Titanium dioxide	10 mg/m³ - TWA	15 mg/m³ - TWA
2-Butoxyethanol	20 ppm - TWA	50 ppm - TWA 240 mg/m³ - TWA prevent or reduce skin absorption

V440-87 - WATERBORNE AMINE EPOXY DEEP BASE

Dipropylene glycol monomethyl ether	100 ppm - TWA 150 ppm - STEL	100 ppm - TWA 600 mg/m³ - TWA
	Skin	prevent or reduce skin absorption

Legend

ACGIH - American Conference of Governmental Industrial Hygienists Exposure Limits OSHA - Occupational Safety & Health Administration Exposure Limits N/E - Not Established

Engineering Measures	Ensure adequate ventilation, especially in confined areas.
Personal Protective Equipment Eye/Face Protection Skin Protection Respiratory Protection	Safety glasses with side-shields. Protective gloves and impervious clothing. In case of insufficient ventilation wear suitable respiratory equipment.
Hygiene Measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor **Odor Threshold** Density (lbs/gal) **Specific Gravity** Hα Viscosity (cps) Solubility(ies) Water solubility **Evaporation Rate** Vapor pressure @20 °C (kPa) Vapor density Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles VOC Regulatory Limit (g/L) Boiling Point (°F) Boiling Point (°C) Freezing Point (°F) Freezing Point (°C) Flash Point (°F) Flash Point (°C) Method Flammability (solid, gas) **Upper flammability limit:** Lower flammability limit: Autoignition Temperature (°F) Autoignition Temperature (°C) **Decomposition Temperature (°F) Decomposition Temperature (°C)** Partition coefficient

liquid little or no odor No information available 10.0 - 10.1 1.19 - 1.22 No information available 40 - 50 30 - 40 50 - 60 60 - 70 <250 212 100 32 0 Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable No information available No information available No information available No information available No information available

10. STABILITY AND REACTIVITY Not Applicable Reactivity **Chemical Stability** Stable under normal conditions. Conditions to avoid Prevent from freezing. **Incompatible Materials** No materials to be especially mentioned. **Hazardous Decomposition Products** None under normal use. None under normal conditions of use. Possibility of hazardous reactions **11. TOXICOLOGICAL INFORMATION Product Information** Information on likely routes of exposure Principal Routes of Exposure Eye contact, skin contact and inhalation. Acute Toxicity **Product Information** No information available Symptoms related to the physical, chemical and toxicological characteristics **Symptoms** No information available Delayed and immediate effects as well as chronic effects from short and long-term exposure Causes eye irritation. Risk of serious damage to eyes. May cause burns. Severely Eye contact irritating to eyes. Irritating to skin. Prolonged skin contact may cause skin irritation and/or dermatitis. Skin contact May cause burns. Harmful by inhalation. Causes respiratory tract irritation. Vapours may be irritating Inhalation to eyes, nose, throat, and lungs. May cause additional affects as listed under "Indestion". Harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, Ingestion vomiting and diarrhea. Can burn mouth, throat, and stomach. No information available Sensitization No information available. **Neurological Effects Mutagenic Effects** No information available. Possible risk of impaired fertility. Possible risk of harm to the unborn child. **Reproductive Effects Developmental Effects** No information available. **Target organ effects** No information available. STOT - single exposure May cause disorder and damage to the. Respiratory system. Digestive System. **STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure if inhaled. Causes damage to organs through prolonged or repeated exposure if swallowed. kidnev. No information available. Other adverse effects No information available **Aspiration Hazard**

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	1296 mg/kg	
ATEmix (dermal)	11796 mg/kg	
ATEmix (inhalation-dust/mist)	6.6 mg/L	
ATEmix (inhalation-vapor)	316 mg/L	

Component Information

Silica, crystalline LD50 Oral: 500 mg/kg (Rat) Titanium dioxide LD50 Oral: > 10000 mg/kg (Rat) 2-Propoxyethanol LD50 Oral: 3089-3090 mg/kg (Rat) LD50 Dermal: 960 µL/kg (Rabbit) LC50 Inhalation (Vapor): 9060 mg/m³ (Rat) 2-Butoxyethanol LD50 Oral: 470 mg/kg (Rat) LD50 Dermal: 220 mg/kg (Rabbit) LC50 Inhalation (Vapor): 450 ppm (Rat, 4 hr.) Dipropylene glycol monomethyl ether LD50 Oral: 5400 µL/kg (Rat) LD50 Dermal: 10 mL/kg (Rabbit) Distillates (petroleum), solvent-refined light paraffinic LD50 Oral: > 15 g/kg (Rat) LD50 Dermal: > 5 g/kg (Rabbit)

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical name	IARC	NTP	OSHA
	1 - Human Carcinogen	Known Human	Listed
Silica, crystalline		Carcinogen	
	2B - Possible Human		Listed
Titanium dioxide	Carcinogen		

Crystalline Silica has been determined to be carcinogenic to humans by IARC (1) when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to spray mist or dust from sanding the dried paint.
Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Product Information

Acute Toxicity to Fish

No information available

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants No information available

Persistence / Degradability

No information available.

Bioaccumulation

No information available.

Mobility in Environmental Media

No information available.

Ozone

No information available

Component Information

Acute Toxicity to Fish

Titanium dioxide LC50: > 1000 mg/L (Fathead Minnow - 96 hr.) 2-Butoxyethanol LC50: 1490 mg/L (Bluegill sunfish - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

	13. DISPOSAL CONSIDERATIONS
Waste Disposal Method	Dispose of in accordance with federal, state, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.
	14. TRANSPORT INFORMATION
DOT	Not regulated
ICAO / IATA	Not regulated
IMDG / IMO	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical name	CAS No.	Weight-%	CERCLA/SARA 313 (de minimis concentration)
2-Propoxyethanol	2807-30-9	10	1.0
2-Butoxyethanol	111-76-2	5	1.0
Dipropylene glycol monomethyl ether	34590-94-8	5	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

None

US State Regulations

California Proposition 65

WARNING: Cancer and Reproductive Harm– www.P65warnings.ca.gov

State Right-to-Know

Chemical name	Massachusetts	New Jersey	Pennsylvania
Silica, crystalline	Х	Х	Х
Titanium dioxide	Х	Х	Х
2-Propoxyethanol		Х	Х
2-Butoxyethanol	Х	Х	Х
Dipropylene glycol monomethyl ether	Х	Х	Х

Legend

X - Listed

16. OTHER INFORMATION

HMIS	Health: 1*	Flammability: 0	Reactivity: 0	PPE: -

HMIS Legend

- 0 Minimal Hazard
- 1 Slight Hazard
- 2 Moderate Hazard
- 3 Serious Hazard
- 4 Severe Hazard
- * Chronic Hazard
- X Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Prepared By	Product Stewardship Department Benjamin Moore & Co. 101 Paragon Drive Montvale, NJ 07645 800-225-5554
Revision Date:	20-Sep-2018
Revision Summary	Not available

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

END OF SAFETY DATA SHEET