

## SAFETY DATA SHEET

Revision Date: 21-Nov-2022

Revision Number: 2

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** RUST-A-VOID ALKYD SEMI-GLOSS - TINT BASE  
**Product Code** R13-33FR  
**Alternate Product Code** HR7833  
**Product Class** SOLVENT THINNED PAINT  
**Color** All  
**Recommended use** Paint  
**Restrictions on use** No information available

#### **Manufactured For**

Complementary Coatings Corp.  
360 Route 206  
Flanders, NJ 07836  
Phone: 1-866-708-9180  
www.coronadopaint.ca

#### **Distributor**

Benjamin Moore & Co., Limited  
8775 Keele Street  
Concord ON L4K 2N1  
Phone: 1-800-361-5898  
www.coronadopaints.ca

#### **Emergency Telephone**

CHEMTREC: +1 703-741-5970 / 1-800-424-9300  
+1 703-527-3887 (outside US & Canada)  
CANUTEC: 613-996-6666 (Transport Emergency Only)

### 2. HAZARDS IDENTIFICATION

#### **Classification**

This chemical is considered hazardous by the Hazardous Products Regulations (HPR: SOR/2015-17)

|  |             |
|--|-------------|
| Skin sensitization                                 | Category 1  |
| Carcinogenicity                                    | Category 1B |
| Reproductive toxicity                              | Category 2  |
| Specific target organ toxicity (repeated exposure) | Category 2  |
| Aspiration hazard                                  | Category 1  |
| Flammable liquids                                  | Category 3  |
| Physical hazard not otherwise classified           | Category 1  |

#### **Label elements**

**Danger**

**Hazard statements**

May cause an allergic skin reaction  
May cause cancer  
Suspected of damaging fertility or the unborn child  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Flammable liquid and vapor  
Risk of spontaneous combustion



**Appearance** liquid

**Odor** solvent

**Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Contaminated work clothing must not be allowed out of the workplace  
Wear protective gloves  
Do not breathe dust/fume/gas/mist/vapors/spray  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Keep container closed  
Ground and bond container and receiving equipment  
Use only non-sparking tools  
Take action to prevent static discharges  
Immediately after use, place rags, steel wool or waste used with this product in a sealed water-filled metal container or lay flat to dry.

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

**Skin**

If skin irritation or rash occurs: Get medical advice/attention  
Wash contaminated clothing before reuse  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

**Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do NOT induce vomiting

**Fire**

In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

**Other information**

No information available

**3. COMPOSITION INFORMATION ON COMPONENTS**

| Chemical name   | CAS No     | Weight-%    | Hazardous Material Information Review Act registry number (HMIRA registry #) | Date HMIRA filed and date exemption granted (if applicable) |
|---|------------|-------------|--|---|
| Hydrotreated heavy naphtha, petroleum                   | 64742-48-9 | 10 - 30%    | -  | -   |
| Nepheline syenite                                       | 37244-96-5 | 10 - 30%    | -  | -   |
| Titanium dioxide  | 13463-67-7 | 7 - 13%     | -  | -   |
| Distillates, petroleum, hydrotreated light              | 64742-47-8 | 7 - 13%     | -  | -   |
| Zinc phosphate  | 7779-90-0  | 1 - 5%      | -  | -   |
| Xylene  | 1330-20-7  | 1 - 5%      | -  | -   |
| 1H-imidazole-1-ethanol, 2-(8-heptadecenyl)-4,5-dihydro- | 95-38-5    | 0.5 - 1%    | -  | -   |
| Hexanoic acid, 2-ethyl-, zirconium salt                 | 22464-99-9 | 0.25 - 0.5% | -  | -   |
| Ethyl benzene   | 100-41-4   | 0.25 - 0.5% | -  | -   |
| Methyl ethyl ketoxime                                   | 96-29-7    | 0.1 - 0.25% | -  | -   |

**Confidential Business Information note**

\*The exact percentage (concentration) of composition has been withheld as a trade secret

**4. FIRST AID MEASURES**

**General Advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

**Eye Contact**

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

**Skin Contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash clothing before reuse. Destroy contaminated articles such as shoes. For severe burns, immediate medical attention is required.

**Inhalation**

Move to fresh air. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.

|  |   |
|--|---|
| <b>Ingestion</b>                       | Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician. |
| <b>Protection Of First-Aiders</b>      | Use personal protective equipment.  |
| <b>Most Important Symptoms/Effects</b> | May cause allergic skin reaction.   |
| <b>Notes To Physician</b>              | Treat symptomatically.  |

## 5. FIRE-FIGHTING MEASURES

|  |  |
|--|--|
| <b>Suitable Extinguishing Media</b>                          | Foam, dry powder or water. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.   |
| <b>Protective equipment and precautions for firefighters</b> | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.   |
| <b>Specific Hazards Arising From The Chemical</b>            | Combustible material. Closed containers may rupture if exposed to fire or extreme heat. Keep product and empty container away from heat and sources of ignition. Thermal decomposition can lead to release of irritating gases and vapors. |
| <b>Sensitivity to mechanical impact</b>                      | No   |
| <b>Sensitivity to static discharge</b>                       | Yes  |
| <b>Flash Point Data</b>                                      |  |
| Flash point (°F)   | 105  |
| Flash Point (°C)   | 41   |
| Method   | PMCC   |
| <b>Flammability Limits In Air</b>                            |  |
| Lower flammability limit:                                    | No data available  |
| Upper flammability limit:                                    | No data available  |
| <b>NFPA</b>  |  |
| Health hazards   | 2  |
| Flammability   | 2  |
| Stability  | 0  |
| Special:   | Not Applicable   |

**NFPA Legend**

- 0 - Not Hazardous
- 1 - Slightly
- 2 - Moderate
- 3 - High
- 4 - Severe

The ratings assigned are only suggested ratings, the contractor/employer has ultimate responsibilities for NFPA ratings where this system is used.

Additional information regarding the NFPA rating system is available from the National Fire Protection Agency (NFPA) at [www.nfpa.org](http://www.nfpa.org).

## 6. ACCIDENTAL RELEASE MEASURES

### Personal Precautions

Use personal protective equipment. Remove all sources of ignition.

### Other Information

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

### Environmental precautions

See Section 12 for additional Ecological Information.

### Methods for Cleaning Up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

## 7. HANDLING AND STORAGE

### Handling

Use only in area provided with appropriate exhaust ventilation. Do not breathe vapors or spray mist. Wear personal protective equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from open flames, hot surfaces and sources of ignition.

### Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Keep in properly labeled containers. Keep out of the reach of children.

**DANGER** - Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container.

### Incompatible Materials

Incompatible with strong acids and bases and strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Limits

| Chemical name                           | ACGIH TLV  | Alberta  | British Columbia   | Ontario  | Quebec   |
|---|--|--|--|--|--|
| Nepheline syenite                       | -  | -  | -  | 10 mg/m <sup>3</sup> - TWA                               | -  |
| Titanium dioxide                        | TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter<br>TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter   | 10 mg/m <sup>3</sup> - TWA   | 10 mg/m <sup>3</sup> - TWA<br>3 mg/m <sup>3</sup> - TWA  | 10 mg/m <sup>3</sup> - TWA                               | 10 mg/m <sup>3</sup> - TWAEV   |
| Xylene                                  | TWA: 20 ppm  | 100 ppm - TWA<br>434 mg/m <sup>3</sup> - TWA<br>150 ppm - STEL<br>651 mg/m <sup>3</sup> - STEL | 100 ppm - TWA<br>150 ppm - STEL                          | 100 ppm - TWA<br>150 ppm - STEL                          | 100 ppm - TWAEV<br>434 mg/m <sup>3</sup> - TWAEV<br>150 ppm - STEV<br>651 mg/m <sup>3</sup> - STEV |
| Hexanoic acid, 2-ethyl-, zirconium salt | STEL: 10 mg/m <sup>3</sup> Zr As Zirconium compounds [RR-00624-6]<br>STEL: 10 mg/m <sup>3</sup> Zr<br>TWA: 5 mg/m <sup>3</sup> Zr As Zirconium compounds [RR-00624-6]<br>TWA: 5 mg/m <sup>3</sup> Zr | 5 mg/m <sup>3</sup> - TWA<br>10 mg/m <sup>3</sup> - STEL                                       | 5 mg/m <sup>3</sup> - TWA<br>10 mg/m <sup>3</sup> - STEL | 5 mg/m <sup>3</sup> - TWA<br>10 mg/m <sup>3</sup> - STEL | 5 mg/m <sup>3</sup> - TWAEV<br>10 mg/m <sup>3</sup> - STEV   |
| Ethyl benzene                           | Ototoxicant - potential to cause hearing disorders<br>TWA: 20 ppm  | 100 ppm - TWA<br>434 mg/m <sup>3</sup> - TWA<br>125 ppm - STEL<br>543 mg/m <sup>3</sup> - STEL | 20 ppm - TWA   | 20 ppm - TWA   | 100 ppm - TWAEV<br>434 mg/m <sup>3</sup> - TWAEV<br>125 ppm - STEV<br>543 mg/m <sup>3</sup> - STEV |

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists  
 Alberta - Alberta Occupational Exposure Limits  
 British Columbia - British Columbia Occupational Exposure Limits  
 Ontario - Ontario Occupational Exposure Limits  
 Quebec - Quebec Occupational Exposure Limits  
 N/E - Not established

**Engineering Measures**

Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment**

**Eye/Face Protection**

Tightly fitting safety goggles If splashes are likely to occur, wear: Safety glasses with side-shields

**Skin Protection**

Long sleeved clothing. Protective gloves.

**Respiratory Protection**

In operations where exposure limits are exceeded, use a NIOSH approved respirator that has been selected by a technically qualified person for the specific work conditions. When spraying the product or applying in confined areas, wear a NIOSH approved respirator specified for paint spray or organic vapors.

**Hygiene Measures**

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling. When using do not eat, drink or smoke.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance**

liquid

**Odor**

solvent

**Odor Threshold**

No information available

**Density (lbs/gal)**

9.8 - 10.2

**Specific Gravity**

1.17 - 1.23

|                                |                          |
|--------------------------------|--------------------------|
| pH                             | No information available |
| Viscosity (cps)                | No information available |
| Solubility(ies)                | No information available |
| Water solubility               | No information available |
| Evaporation Rate               | No information available |
| Vapor pressure @20 °C (kPa)    | No information available |
| Relative vapor density         | No information available |
| Wt. % Solids                   | 65 - 75                  |
| Vol. % Solids                  | 45 - 55                  |
| Wt. % Volatiles                | 25 - 35                  |
| Vol. % Volatiles               | 45 - 55                  |
| VOC Regulatory Limit (g/L)     | < 400                    |
| Boiling Point (°F)             | 279                      |
| Boiling Point (°C)             | 137                      |
| Freezing point (°F)            | No information available |
| Freezing Point (°C)            | No information available |
| Flash point (°F)               | 105                      |
| Flash Point (°C)               | 41                       |
| Method                         | PMCC                     |
| Flammability (solid, gas)      | Not applicable           |
| Upper flammability limit:      | Not applicable           |
| Lower flammability limit:      | Not applicable           |
| Autoignition Temperature (°F)  | No information available |
| Autoignition Temperature (°C)  | No information available |
| Decomposition Temperature (°F) | No information available |
| Decomposition Temperature (°C) | No information available |
| Partition coefficient          | No information available |

## 10. STABILITY AND REACTIVITY

|   |   |
|---|---|
| <b>Reactivity</b>                         | Not Applicable  |
| <b>Chemical Stability</b>                 | Stable under normal conditions. Hazardous polymerisation does not occur.              |
| <b>Conditions to avoid</b>                | Keep away from open flames, hot surfaces, static electricity and sources of ignition. |
| <b>Incompatible Materials</b>             | Incompatible with strong acids and bases and strong oxidizing agents.                 |
| <b>Hazardous Decomposition Products</b>   | Thermal decomposition can lead to release of irritating gases and vapors.             |
| <b>Possibility of hazardous reactions</b> | None under normal conditions of use.  |

## 11. TOXICOLOGICAL INFORMATION

### Product Information

#### Information on likely routes of exposure

**Principal Routes of Exposure** Eye contact, skin contact and inhalation.

**Acute Toxicity**

**Product Information**

Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Symptoms**

No information available

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Eye contact**

Contact with eyes may cause irritation.

**Skin contact**

May cause skin irritation and/or dermatitis. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

**Inhalation**

High vapor / aerosol concentrations are irritating to the eyes, nose, throat and lungs and may cause headaches, dizziness, drowsiness, unconsciousness, and other central nervous system effects.

**Ingestion**

Ingestion may cause irritation to mucous membranes. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death. May cause an allergic skin reaction.

**Sensitization**

No information available.

**Neurological Effects**

No information available.

**Mutagenic Effects**

**Reproductive Effects**

Possible risk of impaired fertility. Possible risk of harm to the unborn child.

**Developmental Effects**

No information available.

**Target organ effects**

No information available.

**STOT - single exposure**

May cause disorder and damage to the. Respiratory system. Central nervous system.

**STOT - repeated exposure**

Causes damage to organs through prolonged or repeated exposure. Causes damage to organs through prolonged or repeated exposure if inhaled.

**Other adverse effects**

No information available.

**Aspiration Hazard**

May be harmful if swallowed and enters airways. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)**

14712 mg/kg

**ATEmix (inhalation-dust/mist)**

139.4 mg/l

**ATEmix (inhalation-vapor)**

2324.2 mg/l

**Component Information**

Caution - This mixture contains a substance not yet fully tested



| Chemical name  | Oral LD50             | Dermal LD50                  | Inhalation LC50                      |
|--|-----------------------|------------------------------|--------------------------------------|
| Hydrotreated heavy naphtha, petroleum<br>64742-48-9      | > 6000 mg/kg ( Rat )  | > 3160 mg/kg ( Rabbit )      | > 8500 mg/m <sup>3</sup> ( Rat ) 4 h |
| Titanium dioxide<br>13463-67-7                           | > 10000 mg/kg ( Rat ) | -                            | -                                    |
| Distillates, petroleum, hydrotreated light<br>64742-47-8 | > 5000 mg/kg ( Rat )  | > 2000 mg/kg ( Rabbit )      | > 5.2 mg/L ( Rat ) 4 h               |
| Zinc phosphate<br>7779-90-0                              | > 5000 mg/kg ( Rat )  | -                            | -                                    |
| Xylene<br>1330-20-7                                      | = 3500 mg/kg ( Rat )  | > 4350 mg/kg ( Rabbit )      | = 29.08 mg/L ( Rat ) 4 h             |
| Ethyl benzene<br>100-41-4                                | = 3500 mg/kg ( Rat )  | = 15400 mg/kg ( Rabbit )     | = 17.4 mg/L ( Rat ) 4 h              |
| Methyl ethyl ketoxime<br>96-29-7                         | = 930 mg/kg ( Rat )   | 1000 - 1800 mg/kg ( Rabbit ) | > 4.83 mg/L ( Rat ) 4 h              |

**Chronic Toxicity**

**Carcinogenicity**

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

| Chemical name    | IARC                           | NTP |
|------------------|--------------------------------|-----|
| Titanium dioxide | 2B - Possible Human Carcinogen |     |
| Ethyl benzene    | 2B - Possible Human Carcinogen |     |

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

**Legend**

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity Effects**

The environmental impact of this product has not been fully investigated.

**Product Information**

**Acute Toxicity to Fish**

No information available

**Acute Toxicity to Aquatic Invertebrates**

No information available

**Acute Toxicity to Aquatic Plants**

No information available

**Persistence / Degradability**

No information available.

**Bioaccumulation**

There is no data for this product.

**Mobility in Environmental Media**

No information available.

**Ozone**

Not applicable

**Component Information**

**Acute Toxicity to Fish**

Titanium dioxide

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Xylene

LC50: 13.5 mg/L (Rainbow Trout - 96 hr.)

Ethyl benzene

LC50: 12.1 mg/L (Fathead Minnow - 96 hr.)

Methyl ethyl ketoxime

LC50: 48 mg/L (Bluegill sunfish - 96 hr.)

**Acute Toxicity to Aquatic Invertebrates**

Ethyl benzene

EC50: 1.8 mg/L (Daphnia magna - 48 hr.)

Methyl ethyl ketoxime

EC50: 750 mg/L (Daphnia magna - 48 hr.)

**Acute Toxicity to Aquatic Plants**

Ethyl benzene

EC50: 4.6 mg/L (Green algae (Scenedesmus subspicatus), 72 hrs.)

**13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Method**

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

**Empty Container Warning**

Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

**14. TRANSPORT INFORMATION**

**TDG**

**Proper Shipping Name** Paint  
**Transport hazard class(es)** 3  
**UN-No** UN1263  
**Packing Group** III  
**Description** UN1263, Paint, 3, III

In Canada, Class 3 flammable liquids may be reclassified as non-regulated for domestic ground transportation if they meet the requirements of TDG General Exemption SOR/2008-34.

**ICAO / IATA** Contact the preparer for further information.

**IMDG / IMO** Contact the preparer for further information.

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA: United States** Yes - All components are listed or exempt.  
**DSL: Canada** Yes - All components are listed or exempt.

**National Pollutant Release Inventory (NPRI)**

**NPRI Parts 1- 4**

This product contains the following Parts 1-4 NPRI chemicals:

| <u>Chemical name</u> | <u>CAS No</u> | <u>Weight-%</u> | <u>NPRI Parts 1- 4</u> |
|----------------------|---------------|-----------------|------------------------|
| Xylene               | 1330-20-7     | 1 - 5%          | Listed                 |
| Ethyl benzene        | 100-41-4      | 0.25 - 0.5%     | Listed                 |

**NPRI Part 5**

This product contains the following NPRI Part 5 Chemicals:

| <u>Chemical name</u>                       | <u>CAS No</u> | <u>Weight-%</u> | <u>NPRI Part 5</u> |
|--|---------------|-----------------|--------------------|
| Hydrotreated heavy naphtha, petroleum      | 64742-48-9    | 10 - 30%        | Listed             |
| Distillates, petroleum, hydrotreated light | 64742-47-8    | 7 - 13%         | Listed             |
| Xylene                                     | 1330-20-7     | 1 - 5%          | Listed             |

**WHMIS Regulatory Status**

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

**16. OTHER INFORMATION**

---

**HMIS**

|                     |    |
|---------------------|----|
| Health hazards      | 2* |
| Flammability        | 2  |
| Reactivity:         | 0  |
| Personal protection | -  |

**HMIS Legend**

- 0 - Minimal Hazard
- 1 - Slight Hazard
- 2 - Moderate Hazard
- 3 - Serious Hazard
- 4 - Severe Hazard
- \* - Chronic Hazard

X - Consult your supervisor or S.O.P. for "Special" handling instructions.

Note: The PPE rating has intentionally been left blank. Choose appropriate PPE that will protect employees from the hazards the material will present under the actual normal conditions of use.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer, has chosen to provide them. HMIS® ratings are to be used only in conjunction with a fully implemented HMIS® program by workers who have received appropriate HMIS® training. HMIS® is a registered trade and service mark of the NPCA. HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada at [http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\\_questions-questions\\_posees-eng.php](http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php).

**Prepared By** Product Stewardship Department  
Benjamin Moore & Co.  
101 Paragon Drive  
Montvale, NJ 07645  
800-225-5554

**Revision Date:** 21-Nov-2022  
**Reason for revision** Not available

**Disclaimer**

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

**End of Safety Data Sheet**