



SUPER KOTE 5000[®]

LATEX FIELD MARKING PAINT

INTERIOR/EXTERIOR FLAT 58 LINE

Features

- Latex Field Marking Paint
- Concrete
- Natural Turf
- Asphalt
- Artificial Turf
- Fast Drying

General Description

Super Kote 5000[®] Latex Field Marking Paint is specifically designed for use on natural or artificial turf, concrete and asphalt, as a semi-permanent coating for line marking or artistic graphics.

Recommended For

Super Kote 5000[®] Latex Field Marking Paint is specifically designed for use on natural or artificial turf, concrete and asphalt, as a semi-permanent coating for line marking or artistic graphics. For use on interior or exterior surfaces such as athletic fields or other areas requiring a semi-permanent marking.

Limitations

- Do not apply when surface or air temperatures are below 50°F (10°C)

Product Information

<p>Colors — Standard: White, Yellow</p> <hr/> <p>— Tint Bases: N/A</p> <hr/> <p>— Special Colors: Contact your dealer.</p> <hr/> <p>Certification: The products supported by this data sheet contain a maximum of 50 grams per liter VOC / VOS (0.42 lbs/gal.) excluding water & exempt solvents This product is compliant under the Ozone Transport Commission regulations as a Flat Coating. This product does not meet qualifications for LEED (Leadership in Energy and Environmental Design) projects as a flat coating.</p> <hr/> <p>Technical Assistance: Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-225-5554, or visit www.coronadopaint.com.</p>	<table border="1"> <thead> <tr> <th colspan="2">Technical Data◇</th> <th>White</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td></td> <td>Latex</td> </tr> <tr> <td>Pigment Type</td> <td></td> <td>Titanium Dioxide</td> </tr> <tr> <td>Volume Solids</td> <td></td> <td>22.3 ± 1.0%</td> </tr> <tr> <td rowspan="4">Coverage per Gallon at Recommended Film Thickness</td> <td></td> <td>3" Line – 400 Ft.</td> </tr> <tr> <td></td> <td>4" Line – 300 Ft.</td> </tr> <tr> <td></td> <td>5" Line – 240 Ft.</td> </tr> <tr> <td></td> <td>6" Line – 200 Ft.</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Dry</td> <td>.09 – 1.8</td> </tr> <tr> <td colspan="3">Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.</td> </tr> <tr> <td>Dry Time @ 70°F (21.1°C) @ 50% RH</td> <td>– Tack Free</td> <td>1 Hour</td> </tr> <tr> <td></td> <td>– To Recoat</td> <td>4 Hours</td> </tr> <tr> <td colspan="3">High humidity and cool temperatures will result in longer dry, recoat and service times.</td> </tr> <tr> <td>Dries By</td> <td></td> <td>Evaporation</td> </tr> <tr> <td>Viscosity</td> <td></td> <td>White: 110 – 115 KU (Krebs Units) Yellow: 75-85 KU</td> </tr> <tr> <td>Flash Point</td> <td></td> <td>N/A</td> </tr> <tr> <td>Gloss / Sheen</td> <td></td> <td>Flat</td> </tr> <tr> <td rowspan="2">Surface Temperature at Application</td> <td>– Min.</td> <td>50°F</td> </tr> <tr> <td>– Max.</td> <td>90°F</td> </tr> <tr> <td>Thin With</td> <td></td> <td>Clean Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td></td> <td>Warm Soapy Water</td> </tr> <tr> <td>Weight Per Gallon</td> <td></td> <td>10.5 lbs</td> </tr> <tr> <td rowspan="2">Storage Temperature</td> <td>– Min.</td> <td>45°F</td> </tr> <tr> <td>– Max.</td> <td>95°F</td> </tr> <tr> <td colspan="3">Volatile Organic Compounds (VOC)</td> </tr> <tr> <td></td> <td>21 Grams/Liter</td> <td>0.18 Lbs./Gallon</td> </tr> </tbody> </table>	Technical Data◇		White	Vehicle Type		Latex	Pigment Type		Titanium Dioxide	Volume Solids		22.3 ± 1.0%	Coverage per Gallon at Recommended Film Thickness		3" Line – 400 Ft.		4" Line – 300 Ft.		5" Line – 240 Ft.		6" Line – 200 Ft.	Recommended Film Thickness	– Dry	.09 – 1.8	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.			Dry Time @ 70°F (21.1°C) @ 50% RH	– Tack Free	1 Hour		– To Recoat	4 Hours	High humidity and cool temperatures will result in longer dry, recoat and service times.			Dries By		Evaporation	Viscosity		White: 110 – 115 KU (Krebs Units) Yellow: 75-85 KU	Flash Point		N/A	Gloss / Sheen		Flat	Surface Temperature at Application	– Min.	50°F	– Max.	90°F	Thin With		Clean Water	Clean Up Thinner		Warm Soapy Water	Weight Per Gallon		10.5 lbs	Storage Temperature	– Min.	45°F	– Max.	95°F	Volatile Organic Compounds (VOC)				21 Grams/Liter	0.18 Lbs./Gallon
Technical Data◇		White																																																																								
Vehicle Type		Latex																																																																								
Pigment Type		Titanium Dioxide																																																																								
Volume Solids		22.3 ± 1.0%																																																																								
Coverage per Gallon at Recommended Film Thickness		3" Line – 400 Ft.																																																																								
		4" Line – 300 Ft.																																																																								
		5" Line – 240 Ft.																																																																								
		6" Line – 200 Ft.																																																																								
Recommended Film Thickness	– Dry	.09 – 1.8																																																																								
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.																																																																										
Dry Time @ 70°F (21.1°C) @ 50% RH	– Tack Free	1 Hour																																																																								
	– To Recoat	4 Hours																																																																								
High humidity and cool temperatures will result in longer dry, recoat and service times.																																																																										
Dries By		Evaporation																																																																								
Viscosity		White: 110 – 115 KU (Krebs Units) Yellow: 75-85 KU																																																																								
Flash Point		N/A																																																																								
Gloss / Sheen		Flat																																																																								
Surface Temperature at Application	– Min.	50°F																																																																								
	– Max.	90°F																																																																								
Thin With		Clean Water																																																																								
Clean Up Thinner		Warm Soapy Water																																																																								
Weight Per Gallon		10.5 lbs																																																																								
Storage Temperature	– Min.	45°F																																																																								
	– Max.	95°F																																																																								
Volatile Organic Compounds (VOC)																																																																										
	21 Grams/Liter	0.18 Lbs./Gallon																																																																								

◇ Reported values are for White. Contact dealer for values of other bases or colors.

Super Kote 5000® Latex Field Marking Paint Interior Exterior Flat 58 Line

Surface Preparation

Surface to be marked must be clean and free of dust, grease, wax and other contamination that could affect adhesion. For best results, grass should be cut short.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Super Kote 5000® Field Marking Paint may be brushed, rolled, or sprayed (conventional or airless) or applied with gravity feed line marker. Do not apply when surface or air temperatures are below 50°F. Do not apply to a hot surface. Thin with one quart of water per gallon when applying with spray or gravity feed marker.

THEORETICAL SPREAD RATE:

3" Line - 400 Ft.*

4" Line – 300 Ft.*

5" Line – 240 Ft.*

6" Line – 200 Ft.*

***NOTE ON SPREAD RATE:** Actual spread rate will vary based upon numerous factors, including texture of the substrate, application method, waste, surface porosity and thinning.

Clean Up

Clean all tools and equipment with clean warm soapy water.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Clean Up"

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**