



SUPER HIDE[®]

LATEX SEMI-GLOSS ENAMEL

283

Features

- Decorative and uniform semi-gloss finish
- Excellent hiding and touch up
- Durable
- Washable film
- Spatter resistant
- Quick dry
- Easy application
- Soap and water cleanup

Recommended For

- For commercial and residential applications.
- For new or previously painted interior trim, doors, cabinets, walls and ceilings. Ideal for a wide variety of surfaces including drywall, masonry, and primed or previously painted wood, metal; and cured plaster.

General Description

A quality acrylic blended latex semi-gloss enamel designed for application to a wide variety of interior surfaces. Super Hide[®] Latex Semi-Gloss Enamel (283) has a decorative and functional semi-gloss finish along with high hiding and a durable, washable film.

Limitations

- Do not apply when air and surface temperatures are below 50 °F (10 °C)

Product Information

Colors — Standard:

White (01), Bone White (03), Linen White (70), Navajo White (73), China White (74), Atrium White (79)

(May be tinted with up to 2.0 fl. oz. of Benjamin Moore[®] Color Preview[®] colorants per gallon.)

— Tint Bases:

Benjamin Moore[®] Color Preview[®] Bases 1B, 2B, 3B, & 4B.

— Special Colors:

Contact your Benjamin Moore representative.

Certifications & Qualifications:

VOC REGION	COMPLIANT
FEDERAL	YES
OTC	YES
OTCII	YES
CARB	YES
CARB07	YES
UTAH	YES
AZMC	YES
SCAQMD	NO

Technical Assistance

Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-866-708-9180 or visit www.benjaminmoore.com

Technical Data[◇]

	White
Vehicle Type	Acrylic Blended Latex
Pigment Type	Titanium Dioxide
Volume Solids	27%
Coverage per Gallon at Recommended Film Thickness	400 – 450 Sq. Ft.
Recommended Film Thickness	– Wet 3.8 mils – Dry 1.0 mils
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.	
Dry Time @ 77 °F (25 °C) @ 50% RH	– To Touch 2 Hours – To Recoat 24 Hours
Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.	
Dries By	Coalescence
Viscosity	110 ± 3 KU
Flash Point	None
Gloss / Sheen	Semi-Gloss (35 – 50 @ 60°)
Surface Temperature at Application	– Min. 50 °F – Max 90 °F
Thin With	Clean Water
Clean Up Thinner	Clean Water
Weight Per Gallon	10.2 lbs
Storage Temperature	– Min. 40 °F – Max 90 °F
Volatile Organic Compounds (VOC)	
99.1 Grams/Liter .82 lbs./Gallon	

[◇] Reported values are for White. Contact Benjamin Moore for values of other bases or colors

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming.

Difficult Substrates: Benjamin Moore offers a variety of specialty primers for use over difficult substrates such as plaster, bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore® retailer can recommend the right problem-solving primer for your special needs.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Primer/Finish Systems

New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary. For best hiding results, tint the primer to the approximate shade of the finish coat, especially when a significant color change is desired. **Special Note:** Certain custom colors require a Deep Color Base Primer tinted to a special prescription formula to achieve the desired color. Consult your retailer.

Wood and engineered wood products:

Primer: Super Hide® Latex Primer / Undercoater (284) or Fresh Start® Multi-Purpose Oil Based Primer (024)

Finish: 1 or 2 coats Super Hide® Latex Semi-Gloss Enamel (283)

Bleeding Type Woods, (Redwood and Cedar):

Primer: Fresh Start® Multi-Purpose Oil Based Primer (024) or 1-2 coats of Fresh Start® High-Hiding All Purpose Primer (046)

Drywall:

Primer: Super Hide® Latex Primer / Undercoater (284).

Finish: 1 or 2 coats Super Hide® Latex Semi-Gloss Enamel (283)

Plaster:

Primer: Fresh Start® Multi-Purpose Latex Primer (N023) or Fresh Start® High-Hiding All Purpose Primer (046)

Finish: 1 or 2 coats Super Hide® Latex Semi-Gloss Enamel (283)

Rough or Pitted Masonry:

Primer: Ultra Spec® Masonry Interior/Exterior Hi-Build Block Filler (571)

Finish: 1 or 2 coats Super Hide® Latex Semi-Gloss Enamel (283)

Smooth Poured or Pre-cast Concrete:

Primer: Ultra Spec® Masonry Interior / Exterior 100% Acrylic Masonry Sealer (608)

Finish: 1 or 2 coats Super Hide® Latex Semi-Gloss Enamel (283)

Ferrous Metal (Steel and Iron):

Primer: Ultra Spec® HP Acrylic Metal Primer (HP04) or Super Spec HP® Alkyd Metal Primer (P06)

Finish: 1 or 2 coats Super Hide® Latex Semi-Gloss Enamel (283)

Non-Ferrous Metal (Galvanized & Aluminum): All new metal surfaces must be thoroughly cleaned with an Oil & Grease Emulsifier Corotech® V600 to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion.

Primer: Ultra Spec® HP Acrylic Metal Primer (HP04)

Finish: 1 or 2 coats Super Hide® Latex Semi-Gloss Enamel

Repaint, All Substrates: Prime bare areas with the primer recommended for the substrate above.

Application

Stir thoroughly before use. Apply one or two coats. For best results, use a Benjamin Moore® Professional custom-blended nylon/polyester brush, Benjamin Moore® Professional roller, or a similar product. This product can also be sprayed. Two coats provide maximum hiding and film durability.

Spray, Airless: Fluid Pressure — 1,500 to 3,000 PSI;

Tip — .013-.017 Orifice

Thinning/Clean up

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents.

Clean brushes, rollers and other painting tools in warm soapy water after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under “Clean Up”.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional
health and safety information**