



ben[®] CHALKBOARD PAINT 308

Features

- Goes on easily and is washable
- Resists spattering during application
- Zero VOC, Low odor
- Qualifies for LEED v4 credit
- Dries to a decorative finish that is extremely durable
- Soap and water clean-up
- Dries quickly
- Available in any color

Recommended For

For interior use on previously painted surfaces. Use wherever a chalkboard finish is desired. For best results, use traditional, non-liquid chalk, in lighter colors.

General Descriptions

ben[®] Chalkboard Paint (308) is acrylic-based, tintable topcoat and turns virtually any interior surface into a chalkboard.

Limitations

- Do not apply when air and surface temperatures are below 50 °F (10 °C)

Product Information

Colors — Standard: N/A	Technical Data[◇]		Pastel Base	
— Tint Bases: Benjamin Moore [®] Gennex [®] Bases 1X, 2X, 3X, & 4X	Vehicle Type	100% Acrylic		
— Special Colors: N/A	Pigment Type	Titanium Dioxide		
Certifications & Qualifications: VOC compliant in all regulated areas Zero VOC Qualifies for LEED [®] v4 Credit Qualifies for CHPS low emitting credit (Collaborative for High Performance Schools) CDPH v1 Emission Certified Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84	Volume Solids	40%		
	Coverage per quart at Recommended Film Thickness	100 – 110 Sq. Ft.		
Technical Assistance: Available through your local authorized independent Benjamin Moore [®] retailer. For the location of the retailer nearest you, call 1-866-708-9180, see www.benjaminmoore.com , or consult your local Yellow Pages.	Recommended Film Thickness	– Wet	3.8 mils	
	Thickness	– Dry	1.5 mils	
	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.			
	Dry Time @ 77 °F (25 °C) @ 50% RH	– To Touch	2 Hours	
		– To Recoat	4 Hours	
	Allow painted area to cure for 3 days before using. Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.			
	Dries By	Evaporation, Coalescence		
	Viscosity	95 ± 2 KU		
	Flash Point	None		
	Gloss / Sheen	Eggshell (5 – 10 @ 85°)		
Surface Temperature at Application	– Min.	50 °F		
	– Max.	90 °F		
Thin With	Clean Water			
Clean Up Thinner	Clean Water			
Weight Per Gallon	10.5 lbs			
Storage Temperature	– Min.	40 °F		
	– Max.	90 °F		
Volatile Organic Compounds (VOC) 0g/L Zero VOC Post tint (any base and any color)				

[◇] Reported values are for Pastel Base. Contact Benjamin Moore for values of other bases or colors.

Surface Preparation

Surfaces must be clean, dry and free of wax, grease, dust, mildew, water-soluble materials and scaling paint. Hard, glossy areas should be dulled with sandpaper to ensure proper adhesion.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

Primer/Finish Systems

Use the appropriate Benjamin Moore® Fresh Start® primer if a primer is required. Follow label directions. For previously painted surfaces in good condition, apply one or two coats of this product. Otherwise, before and after filling in nail holes, cracks and other surface imperfections, spot prime with the appropriate Benjamin Moore® Fresh Start® primer. When dry, apply one or two finish coats of ben® Chalkboard Paint (308).

Application

Stir thoroughly. Apply one or two coats. For best results, use a Benjamin Moore® custom-blended nylon/polyester brush, Benjamin Moore® short nap roller, or a similar product. This product can also be sprayed. When brushing or rolling, apply generously using short overlapping strokes, always moving from unpainted into painted areas. Do not over apply. Let paint dry before touching up. Do not apply in temperatures below 50 °F (10 °C).

Before Using

Allow painted area to cure for a minimum of 3 days before using. Prior to initial use, rub entire surface with a piece of white chalk and then erase using a clean, damp cloth. Because of the additives used in some varieties of chalk, which can leave a residue when erased. For best results, use traditional, non-liquid chalk, in lighter colors.

Thinning/Clean Up

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents. Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting or follow state/local guidelines on solvent use.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary, consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF: SPILL – Absorb with inert material and dispose of as specified under “**THINNING/CLEAN UP**”.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional
health and safety information**