



STUDIO FINISHES® GLITTER EFFECT 311

Features

- Studio Finishes® Latex Glitter Effect (311) is a topcoat that adds an iridescent sparkle to any previously painted interior surface
- Resists spattering during application
- Dries quickly
- Dries to a decorative finish that is extremely durable
- Soap and water clean-up
- Goes on easily and is washable

General Descriptions

Studio Finishes® Latex Glitter Effect (311) is a clear, low lustre topcoat that adds a whimsical, iridescent sparkle to any paintable surface or room in your home.

Recommended For

For interior use on previously painted surfaces, including ceilings, walls, trim and furniture. Use wherever a glitter finish is desired.

Limitations

- Do not apply when air and surface temperatures are below 50 °F (10 °C).

Product Information	
Colors — Standard: Clear	Technical Data ◇ Clear
— Tint Bases: Not available	Vehicle Type Vinyl Acrylic / Water Pigment Type None Volume Solids 30% Coverage per Quart at Recommended Film Thickness 100 – 110 Sq. Ft.
— Special Colors: Contact your Benjamin Moore representative.	Recommended Film Thickness – Wet 3.8 mils – Dry 1.1 mils Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.
Certifications & Qualifications: VOC compliant in all regulated areas	Dry Time @ 77 °F (25 °C) @ 50% RH – To Touch 1 Hour – To Recoat 2 -3 Hour Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.
Technical Assistance: Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 866-708-9180, see www.benjaminmoore.com or consult your local Yellow Pages.	Dries By Evaporation, Coalescence Viscosity 85 ± 1 KU Flash Point None Gloss / Sheen Low Lustre (35–45 @ 60°) Surface Temperature at Application – Min. 50 °F – Max. 90 °F Thin With Clean Water Clean Up Thinner Clean Water Weight Per Gallon 8.69 lbs Storage Temperature – Min. 40 °F – Max. 90 °F Volatile Organic Compounds (VOC) 118 Grams/Liter .98 lbs./Gallon

◇ Reported values are for Clear. Contact Benjamin Moore for values of other bases or colors.

Surface Preparation

Surfaces must be clean, dry and free of wax, grease, dust, mildew, water-soluble materials and scaling paint. Hard, glossy areas should be dulled with sandpaper to ensure proper adhesion.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

Primer/Finish Systems

Use the appropriate Fresh Start® primer. Follow label directions. For best results when significant color change is desired, tint the primer to the approximate base color. When dry, apply one or two finish coats of Benjamin Moore® Regal® Select Eggshell (549), Regal® Select Pearl (550), or Regal® Select Semi-Gloss (551) or other premium Benjamin Moore® products. Finish with one or two coats of Studio Finishes® Latex Glitter Effect (311).

Application

Stir thoroughly. Apply one or two coats. For best results, use a Benjamin Moore® custom-blended nylon/polyester brush, Benjamin Moore® roller, or a similar product. When brushing or rolling, apply generously using short overlapping strokes, always moving from unpainted into painted areas. Do not over apply. Let paint dry before touching up. Do not apply in temperatures below 50 °F (10 °C).

Thinning/Cleanup

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents. Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary, consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental, Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application or sanding. A dust/particulate respirator approved by NIOSH should be worn when sanding or spraying. Close container after each use.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, call physician immediately.

IN CASE OF: SPILL – Absorb with inert material and dispose of as specified under “**THINNING/CLEAN UP**”.

KEEP OUT OF REACH OF CHILDREN

Refer to Safety Data Sheet for additional health and safety information.