



ARBORCOAT®

EXTERIOR WATERPROOFER

320

Features

- Water-based
- Fills pores
- Penetrating silicone
- Cross links with moisture in the air, resulting in a long-term sealant/treatment
- Fast drying
- Easy to apply
- Resists dirt pick-up
- Can be applied to new or restored wood surfaces
- Contains trans-oxide pigments for protection against UV light

General Description

Arborcoat® Exterior Waterproofer is a water-based sealer that provides excellent protection from moisture and sun damage on exterior wood decking, siding, fencing, shingles and furniture. Arborcoat® Exterior Waterproofer is a penetrating, non-yellowing coating with silicone that fills the pores of wood surfaces and trans-oxide pigments that protect against UV damage. Arborcoat® Exterior Waterproofer may be used on properly prepared new or reconditioned wood surfaces. Ideal for protecting all types of wood from water and sun damage, as well as stains from grease, oil, dirt and mildew.

Recommended For

For exterior use on wood decking, siding, fencing, shakes and furniture.

Limitations

- Do not apply when air and surface temperatures are below 50 °F (10 °C)

Product Information

Colors — Standard: Clear (00)	Technical Data Clear
— Tint Bases: N/A	Film Thickness - Dry Minimal
— Special Colors: N/A	Coverage per Gallon 100 – 200 sq. ft. (9.3 – 18.6 sq. m.)
Certifications & Qualifications: VOC compliant in all regulated areas	Dry Time @ 77 °F – To Touch 2 – 3 Hours (25 °C) @ 50% RH – To Service Overnight
Technical Assistance Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-866-708-9180 or visit www.benjaminmoore.com	Depending on dilution and surface conditions. Dry and Service times will vary depending on temperature and humidity
	Flash Point None
	Gloss / Sheen Flat
	Surface Temperature – Min. 50 °F (10 °C) at Application – Max 90 °F (32 °C)
	Thin With Clean Water
	Clean Up Thinner Clean Water
	Weight Per Gallon 8.3 lbs
	Storage Temperature – Min. 40 °F (4.4 °C) – Max 90 °F (32 °C)
	<p style="text-align: center;">Volatile Organic Compounds (VOC)</p> <p style="text-align: center;">34 Grams/Liter .29 Lbs. / Gallons</p>

◇ Reported values are for Clear.

Surface Preparation

Surfaces must be free of all dirt, mildew, mold and other contaminants, including previous paint, stains and clear coatings. Prior to application, thoroughly clean and prepare surfaces with the appropriate Benjamin Moore® prep product according to label directions. Thoroughly rinse surface and remove all excess water to ensure there is no puddling. It is not necessary for the wood surface to dry completely before application of this product. **The moisture content of the wood should not exceed 25%.**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Do not use with other waterproofing products. Shake or stir contents thoroughly before use. May be applied by brush, roller or spray. If spraying, back-brushing is required. **DO NOT THIN.** Apply one coat only. Do not over-apply. Over-application, or additional coats, will NOT improve performance or appearance. Tackiness may result if product is over-applied or if temperature falls below 50°F (10°C) within 48 hours of application.

Thinning/Clean Up

THINNING: DO NOT THIN.

CLEAN UP: Clean brushes and equipment with soap and water. Dry product can be removed with mineral spirits or follow state/local guidelines on solvent use. Close container after each use.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "CLEAN UP".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional
health and safety information.**