



ECO SPEC[®] WB

INTERIOR LATEX PEARL FINISH

F375

Features

- Minimal Odour
- Zero VOC's
- Quick return to service
- Spatter-resistant
- 100% Acrylic
- Dries quickly to a beautiful pearl finish with the washability of a semi-gloss

Recommended For

For use on primed or previously painted drywall, masonry, plaster, wood, metal and wallpapered surfaces. Use Eco Spec[®] WB Interior Latex Primer (F372) as a first coat when a low odour, solvent free primer/ finish system is desired.


General Description

A low odour, zero VOC, 100% acrylic interior latex pearl finish that provides a high hiding, excellent touch up and a uniform pearl finish. Its resulting film combines the beauty of a Pearl finish with washability of a semi-gloss finish. Eco Spec[®] WB Interior Latex Pearl Finish (F375) is ideally suited for commercial, facility management and residential applications. Eco Spec[®] WB Interior Latex Pearl Finish (F375) does not have the odour of conventional paints that contain ingredients known as Volatile Organic Compounds (VOC's).

Limitations

- Do not paint when temperature of air and surface is below 10° C (50 °F)

Product Information

Colours — Standard: White (01)				Technical Data[◇]		Pastel Base	
— Tint Bases: Gennex [®] Waterborne Colorant Bases 1X, 2X, 3X and 4X.				Vehicle Type		100% Acrylic Latex	
— Special Colours: Contact your Benjamin Moore representative				Pigment Type		Titanium Dioxide	
Certifications & Qualifications: VOC compliant in all regulated areas				Volume Solids		38%	
Zero VOC				Coverage per 3.79 L at		37.2 – 41.8 sq. m.	
Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84				Recommended Film Thickness		(400 – 450 sq. ft.)	
 <p>Benjamin Moore's Green Promise[®] designation is our company's assurance that this product meets – and often exceeds – rigorous environmental and performance criteria regarding VOCs, emissions, application, washability, scrubability and packaging, while also delivering the premium levels of performance you expect from Benjamin Moore.</p>				Recommended Film Thickness		– Wet 3.8 mils	
				– Dry 1.4 mils		Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint	
				Dry Time @ 25 °C (77 °F) @ 50% RH		– To Touch ½ – 1 Hour	
				– To Recoat		1 – 2 Hours	
				Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times			
				Dries By		Evaporation, Coalescence	
				Viscosity		90 ± 2 KU	
				Flash Point		None	
				Gloss / Sheen		Pearl (15 – 20 @ 60°)	
				Surface Temperature at Application		– Min. 10 °C (50 °F)	
				– Max		32.2 °C (90 °F)	
				Thin With		See Chart	
				Clean Up Thinner		Clean Water	
				Weight Per 3.79 L		4.8 kg (10.5 lbs)	
				Storage Temperature		– Min. 4.4 °C (40 °F)	
				– Max		32.2 °C (90 °F)	
				Volatile Organic Compounds (VOC)			
				0 g/L			
				Zero VOC post tint (any base and any colour)			
Customer Information Centre: 1-800-361-5898, info@benjaminmoore.ca , www.benjaminmoore.ca							

[◇]Reported values are for Pastel Base. Contact Benjamin Moore for values of other bases or Colours.

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming.

Difficult Substrates: Benjamin Moore® offers a variety of specialty primers for use over difficult substrates such as plaster, bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore® retailer can recommend the right problem-solving primer for your special needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Primer/Finish Systems

Eco Spec® WB Interior Latex Primer (F372) is the preferred primer in most situations. For best hiding results use Eco Spec® WB Primer tinted to the approximate finish coat colour. **Special Note:** Certain custom Colours require a Deep Colour Base Primer tinted to a special prescription formula to achieve the desired colour. Consult your retailer.

Wood, and engineered wood products

Primer: Eco Spec® WB Interior Latex Primer (F372) or Fresh Start® All-Purpose Alkyd Primer (F024)
Finish: 1 or 2 coats Eco Spec® WB Interior Latex Pearl Finish (F375)

Drywall

Primer: Eco Spec® WB Interior Latex Primer (F372)
Finish: 1 or 2 coats Eco Spec® WB Interior Latex Pearl Finish (F375)

Plaster

Primer: Eco Spec® WB Interior Latex Primer (F372)
Finish: 1 or 2 coats Eco Spec® WB Interior Latex Pearl Finish (F375)

Rough or Pitted Masonry

Primer: Ultra Spec® Masonry Interior/Exterior Hi-Build Block Filler (K571)
Finish: 1 or 2 coats Eco Spec® WB Interior Latex Pearl Finish (F375)

Smooth Poured or Pre-cast Concrete

Primer: Eco Spec® WB Interior Latex Primer (F372) or Fresh Start® Multi-Purpose Latex Primer (F023)
Finish: 1 or 2 coats Eco Spec® WB Interior Latex Pearl Finish (F375)

Ferrous Metal (Steel and Iron):

Primer: Ultra Spec® HP Acrylic Metal Primer (FP04) or Super Spec HP® Alkyd Metal Primer (KP06)
Finish: 1 or 2 coats Eco Spec® WB Interior Latex Pearl Finish (F375)

Non-Ferrous Metal (Galvanized & Aluminium). All new metal surfaces must be thoroughly cleaned with Corotech® Oil & Grease Emulsifier (V600) to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion.

Primer: Ultra Spec® HP Acrylic Metal Primer (FP04)
Finish: 1 or 2 coats Eco Spec® WB Interior Latex Pearl Finish (F375)

Repaint, All Substrates: Prime bare areas with the primer recommended above for the substrate

Application

Mixing of Paint: Stir thoroughly before and during use. Apply one or two coats. Use the same brushing techniques as you would for any zero-VOC compliant interior coating. For best results, use a premium Benjamin Moore® custom-blended nylon/polyester brush, premium Benjamin Moore® roller or a similar product. Apply paint generously from unpainted area into wet area. Eco Spec® WB dries faster than other acrylic paints, so avoid lap marks by maintaining a wet edge.

This product can also be sprayed; refer to the chart below for spray recommendations.

Thinning/Cleaning

Conditioning with Benjamin Moore® K518 Extender may be necessary under certain conditions to adjust open time or spray characteristics. The chart below is for general guidance		
	Mild conditions	Severe conditions
	Humid (RH> 50%) with no direct sunlight & with little to no wind	Dry (RH<50%), in direct sunlight, or windy conditions
Brush: Nylon / Polyester	No thinning necessary	Add K518 Extender or water: Max of 236 ml (8 fl. oz.) to a 3.79 L Never add other paints or solvents.
Roller: Premium Quality		
Spray: Airless Pressure: 1500 -2500 psi Tip: 0.013-0.017		

Cleanup: Wash brushes, rollers, and other painting tools in warm, soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.

Environmental Health & Safety Information

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN
 PROTECT FROM FREEZING**

Refer to Safety Data Sheet for additional health and safety information.