



# ULTRA SPEC<sup>®</sup> 500

## INTERIOR SATIN/PEARL FINISH

### T545

#### Features

- Zero VOC
- Low odor
- Excellent hiding
- Great touch up
- Spatter resistant
- Decorative and uniform satin/pearl finish
- Quick dry
- Easy application
- Soap and water clean up
- MPI Approved
- Washable
- Eligible for LEED<sup>®</sup> v4 credit

#### Recommended For

Interior door, trim, cabinet, wall and ceiling surfaces in commercial and institutional environments where a washable satin/Pearl finish is desired. For use on primed or previously painted drywall, plaster, wood, masonry, metal and wallpapered surfaces.


#### General Description

A professional-quality interior waterborne satin/pearl finish based on a proprietary cross-linking acrylic resin that tints on the Gennex<sup>®</sup> zero VOC colorant system. This waterborne interior satin/Pearl has excellent stain release so it washes clean easily. The product is eligible for LEED<sup>®</sup> v4 credit and passes the most stringent environmental standards in any color. Because it tints on our Gennex<sup>®</sup> waterborne colorant system all Ultra Spec<sup>®</sup> 500 finishes are available in any color without an increase in VOC.

#### Limitations

- Do not apply when air and surface temperatures are below 50 °F (10 °C)

### Product Information

<b>Colors — Standard:</b> White (01)		<b>Technical Data<sup>Δ</sup></b>		<b>Base 1</b>												
<b>— Tint Bases:</b> Benjamin Moore <sup>®</sup> Gennex <sup>®</sup> bases 1X – 4X		Vehicle Type		Acrylic Copolymer												
<b>— Special Colors:</b> Contact your Benjamin Moore representative		Pigment Type		Titanium Dioxide												
<b>Certifications &amp; Qualifications:</b> <b>VOC compliant in all regulated areas</b> Zero VOC Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84 Master Painters Institute MPI # 43, 43 X-Green <sup>™</sup> , 140, 140 X-Green <sup>™</sup> , 146, 146 X-Green <sup>™</sup> Anti-microbial - This product contains antimicrobial additives that inhibit the growth of mold and mildew on the surface of the paint film.		Volume Solids		39.6 ± 2%												
 Benjamin Moore's Green Promise <sup>®</sup> designation is our company's assurance that this product meets – and often exceeds – rigorous environmental and performance criteria regarding VOCs, emissions, application, washability, scrubability and packaging, while also delivering the premium levels of performance you expect from Benjamin Moore.		Coverage per Gallon at Recommended Film Thickness		350 – 400 sq. ft.												
<table border="1"> <tr> <td>Eligible for LEED<sup>®</sup> v4 Credit</td> <td>CDPH v1 Emissions Certified</td> <td>Qualifies for CHPS low emitting credit (Collaborative for High Performance Schools)</td> <td>VOC (in any color)</td> </tr> <tr> <td>YES</td> <td>YES</td> <td>YES</td> <td>&lt; 50 g/L</td> </tr> </table>		Eligible for LEED <sup>®</sup> v4 Credit	CDPH v1 Emissions Certified	Qualifies for CHPS low emitting credit (Collaborative for High Performance Schools)	VOC (in any color)	YES	YES	YES	< 50 g/L	Recommended Film Thickness		<table border="1"> <tr> <td>– Wet</td> <td>3.9 – 4.3 mils</td> </tr> <tr> <td>– Dry</td> <td>1.6 – 1.8 mils</td> </tr> </table>	– Wet	3.9 – 4.3 mils	– Dry	1.6 – 1.8 mils
Eligible for LEED <sup>®</sup> v4 Credit	CDPH v1 Emissions Certified	Qualifies for CHPS low emitting credit (Collaborative for High Performance Schools)	VOC (in any color)													
YES	YES	YES	< 50 g/L													
– Wet	3.9 – 4.3 mils															
– Dry	1.6 – 1.8 mils															
This Benjamin Moore product has been tested by independent third parties and meets or exceeds the published chemical restriction and performance criteria of the Green Seal <sup>™</sup> GS-11 2015 standard		Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.														
<b>Technical Assistance</b> Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-866-708-9180 or visit <a href="http://www.benjaminmoore.com">www.benjaminmoore.com</a>		Dry Time @ 77 °F (25 °C) @ 50% RH		<table border="1"> <tr> <td>– To Touch</td> <td>2 Hours</td> </tr> <tr> <td>– To Recoat</td> <td>4 Hours</td> </tr> </table>	– To Touch	2 Hours	– To Recoat	4 Hours								
– To Touch	2 Hours															
– To Recoat	4 Hours															
		Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.														
		Dries By		Coalescence												
		Viscosity		93 ± 3 KU												
		Flash Point		N/A												
		Gloss / Sheen		Satin/Pearl (20 – 35 @ 60°)												
		Surface Temperature at Application		<table border="1"> <tr> <td>– Min.</td> <td>50 °F</td> </tr> <tr> <td>– Max.</td> <td>90 °F</td> </tr> </table>	– Min.	50 °F	– Max.	90 °F								
– Min.	50 °F															
– Max.	90 °F															
		Thin With		See Chart												
		Clean Up Thinner		Clean Water												
		Weight Per Gallon		11.2 lbs												
		Storage Temperature		<table border="1"> <tr> <td>– Min.</td> <td>40 °F</td> </tr> <tr> <td>– Max.</td> <td>90 °F</td> </tr> </table>	– Min.	40 °F	– Max.	90 °F								
– Min.	40 °F															
– Max.	90 °F															
		<b>Volatile Organic Compounds (VOC)</b> 0 Grams/Liter 0 Lbs./Gallon <b>Zero VOC post tint (any base and any color)</b>														

**Surface Preparation**

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure 30 days before applying base coat. Cured plaster should be hard, have a slight sheen and maximum PH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming. Wood substrates must be thoroughly dry.

**Difficult Substrates:** Benjamin Moore offers a variety of specialty primers for use over difficult substrates such as bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore® retailer can recommend the right problem-solving primer for your special needs.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**Primer/Finish Systems**

New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary. For best hiding results, tint the primer to the approximate shade of the finish coat, especially when a significant color change is desired. **Special Note:** Certain custom colors require a Deep Color Base Primer tinted to a special prescription formula to achieve the desired color. Consult your retailer or a Benjamin Moore representative.

**Wood, and engineered wood products:**

**Primer:** Ultra Spec® 500 Interior Latex Primer (N534) or Fresh Start® Multi-Purpose Oil Based Primer (024)  
**Finish:** 1 or 2 coats Ultra Spec® 500 Interior Satin/Pearl Finish (T545)

**Drywall:**

**Primer:** Ultra Spec® 500 Interior Latex Primer (N534) or Fresh Start® Multi-Purpose Latex Primer (N023)  
**Finish:** 1 or 2 coats Ultra Spec® 500 Interior Satin/Pearl Finish (T545)

**Plaster (Cured):**

**Primer:** Ultra Spec® 500 Interior Latex Primer (N534) or Fresh Start® Multi-Purpose Latex Primer (N023)  
**Finish:** 1 or 2 coats Ultra Spec® 500 Interior Satin/Pearl Finish (T545)

**Rough or Pitted Masonry:**

**Primer:** Ultra Spec® Masonry Interior/Exterior Hi-Build Block Filler (571)  
**Finish:** 1 or 2 coats Ultra Spec® 500 Interior Satin/Pearl Finish (T545)

**Smooth Poured or Precast Concrete:**

**Primer:** Ultra Spec® Masonry Interior / Exterior 100% Acrylic Masonry Sealer (608)  
**Finish:** 1 or 2 coats Ultra Spec® 500 Interior Satin/Pearl Finish (T545)

**Ferrous Metal (Steel and Iron):**

**Primer:** Ultra Spec® HP Acrylic Metal Primer (HP04) or Super Spec HP® Alkyd Metal Primer (P06)  
**Finish:** 1 or 2 coats Ultra Spec® 500 Interior Satin/Pearl Finish (T545)

**Non-Ferrous Metal (Galvanized & Aluminum):** All new metal surfaces must be thoroughly cleaned with an oil & grease emulsifier to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion.

**Primer:** Ultra Spec® HP Acrylic Metal Primer (HP04)  
**Finish:** 1 or 2 coats Ultra Spec® 500 Interior Satin/Pearl Finish (T545)

**Repaint, All Substrates:** Prime bare areas with the primer recommended for the substrate above.

**Application**

Stir thoroughly before use. Apply one or two coats. For best results, use a Benjamin Moore® Professional custom-blended nylon/polyester brush, Benjamin Moore® Professional roller, or a similar product. This product can also be sprayed.

<b>Conditioning with Benjamin Moore® 518 Extender may be necessary under certain conditions to adjust open time or spray characteristics. The chart below is for general guidance</b>		
	<b>Mild conditions</b>	<b>Severe conditions</b>
	Humid (RH> 50%) with no direct sunlight & with little to no wind	Dry (RH<50%), in direct sunlight, or windy conditions
<b>Brush:</b> Nylon / Polyester	No thinning necessary	Add <b>518 Extender</b> or <b>water:</b>  Max of 8 fl. oz. to a gallon of paint  <b>Never add other paints or solvents.</b>
<b>Roller:</b> Premium Quality 3/8" roller cover		
<b>Spray: Airless</b> Pressure: 1500-2500 psi Tip: 0.013-0.017		

**Thinning/Clean up**

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents.

**Clean up:** Use soap and water. Spray equipment should be given a final rinse with mineral spirits to prevent corrosion.

**USE COMPLETELY OR DISPOSE OF PROPERLY.** Dry empty containers may be recycled in a can recycling program. Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.

**Environmental Health & Safety Information**

**Use only with adequate ventilation.** Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



**WARNING:** Cancer and Reproductive Harm—  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

**FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL –** Absorb with inert material and dispose of as specified under “Clean up”.

**KEEP OUT OF REACH OF CHILDREN  
 PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional health and safety information.**