



# REGAL<sup>®</sup> SELECT

PREMIUM INTERIOR PAINT & PRIMER  
SEMI-GLOSS F551

## Features

- Excellent hide
- Excellent durability
- Self-priming on most substrates
- Premium flow and leveling
- Provides a mildew resistant coating
- Spatter resistant
- Easy application

## Recommended For

Ideal for interior trim, doors, cabinets, walls, and new or coated acoustic ceilings. For new or previously painted wallboard, plaster, masonry, and primed or previously painted wood and metal.

## General Description

A premium quality, easy to use, durable, washable, and scrubable finish. Beautiful finish for trim and accents. Ideal for surfaces subject to abuse and soil such as corridors, stairwells, cafeterias, locker rooms, laboratories, etc. Easy to apply by brush, roller, or spray gun. Excellent hiding and leveling properties. Self-priming on most substrates

## Limitations

- Do not apply when air and surface temperatures are below 10 °C (50 °F).

## Product Information

### Colours — Standard:

White (01)

### — Tint Bases:

Benjamin Moore<sup>®</sup> Gennex<sup>®</sup> Bases 1X, 2X, 3X, & 4X

### — Special Colours:

Contact your Benjamin Moore representative.

### Certifications & Qualifications:

#### VOC compliant in all regulated areas

Eligible for LEED<sup>®</sup> v4 Credit

Qualifies for CHPS low emitting credit  
(Collaborative for High Performance Schools)

CDPH v1 Emission Certified

Class A (0-25) over non-combustible surfaces when tested in accordance with ASTM E-84

Anti-microbial – This product contains antimicrobial additives that inhibit the growth of mould and mildew on the surface of the paint film.

Master Painters Institute MPI # 54, 141, 147

This Benjamin Moore product has been tested by independent third parties and meets or exceeds the published chemical restriction and performance criteria of the Green Seal<sup>™</sup> GS-11 2015 standard



Benjamin Moore's Green Promise<sup>®</sup> designation is our company's assurance that this product meets – and often exceeds – rigorous environmental and performance criteria regarding VOCs, emissions, application, washability, scrubability and packaging, while also delivering the premium levels of performance you expect from Benjamin Moore.

### Customer Information Centre:

1-800-361-5898, info@benjaminmoore.ca, [www.benjaminmoore.ca](http://www.benjaminmoore.ca)

### Technical Data<sup>◇</sup>

### Base 1

Vehicle Type	Proprietary 100 % Acrylic Latex	
Pigment Type	Titanium Dioxide	
Volume Solids	36.1 ± 2%	
Theoretical Coverage at	37.2 – 41.8 sq. m.	
Recommended Film Thickness	(400 – 450 sq. ft)	
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.		
Recommended Film Thickness	– Wet	3.6 – 4.1 mils
	– Dry	1.3 – 1.5 mils
Dry Time @ 25°C (77°F) @ 50% RH	– To Touch	1 Hour
	– To Recoat	3 Hours
Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.		
Dries By	Evaporation, Coalescence	
Viscosity	108 ± 2 KU	
Flash Point	None	
Gloss/Sheen	Semi-Gloss (50 – 60 @ 60°)	
Surface Temperature at application	– Min.	10 °C (50 °F)
	– Max.	32.2 °C (90 °F)
Thin With	See Chart	
Clean Up Thinner	Clean Water	
Weight Per 3.79 L	4.9 kg (10.8 lbs)	
Storage Temperature	– Min.	4.4 °C (40 °F)
	– Max.	32.2 °C (90 °F)

### Volatile Organic Compounds (VOC)

96.1 g/L

## Regal® Select Premium Interior Paint & Primer, Semi-Gloss (F551)

### Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water-soluble materials, and mildew. Remove any peeling or scaling paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles.

**Difficult Substrates:** Benjamin Moore® offers a number of specialty primers for use over difficult substrates such as bleeding woods, grease stains, crayon markings, hard glossy surfaces, galvanized metal, or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore® retailer can recommend the right problem-solving primer for your special needs.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

### Primer/Finish Systems

Regal® Select is self-priming on most surfaces. On bare substrates two coats are required; previously painted surfaces can be finished with 1 or 2 coats. While the high quality of our products sometimes makes one-coat coverage achievable, Benjamin Moore recommends two coats of this product to achieve full colour development and to maximize paint film performance. **Special Note:** Certain deep custom colours may require a Deep Base Primer tinted to a special prescription formula to achieve the desired colour. Consult your retailer.

#### Wood and Engineered Wood Products:

**Primer:** Fresh Start® Multi-Purpose Latex Primer (F023) or Fresh Start® High-Hiding All Purpose Primer (K046)

**Finish:** 1 or 2 coats Regal® Select Premium Interior Paint & Primer, Semi-Gloss (F551)

#### For bleeding woods such as cedar and redwood:

**Primer:** Fresh Start® High-Hiding All Purpose Primer (K046) or Fresh Start® Multi-Purpose Oil Based Primer (F024)

**Finish:** 1 or 2 coats Regal® Select Premium Interior Paint & Primer, Semi-Gloss (F551)

#### Drywall:

**Primer/Finish:** 1 or 2 coats Regal® Select Premium Interior Paint & Primer, Semi-Gloss (F551)

#### Plaster:

**Primer/Finish:** 1 or 2 coats Regal® Select Premium Interior Paint & Primer, Semi-Gloss (F551)

#### Rough or Pitted Masonry:

**Primer:** Ultra Spec® Masonry Interior/Exterior Hi-Build Block Filler (K571)

**Finish:** 1 or 2 coats Regal® Select Premium Interior Paint & Primer, Semi-Gloss (F551)

#### Smooth Poured or Precast Concrete

**Primer/Finish:** 1 or 2 coats Regal® Select Premium Interior Paint & Primer, Semi-Gloss (F551)

#### Ferrous Metal (Steel and Iron):

**Primer:** Ultra Spec® HP Acrylic Metal Primer (FP04) or Super Spec HP® Alkyd Metal Primer (KP06)

**Finish:** 1 or 2 coats Regal® Select Premium Interior Paint & Primer, Semi-Gloss (F551)

#### Non-Ferrous Metal (Galvanized & Aluminium)

All new metal surfaces must be thoroughly cleaned with an Oil & Grease Emulsifier Corotech® V600 to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion.

**Primer/Finish:** 1 or 2 coats Regal® Select Premium Interior Paint & Primer, Semi-Gloss (F551)

**Repaint, All Substrates:** Prime bare areas with the primer recommended for the substrate above.

### Application

**Mixing of Paint:** Stir thoroughly before and during use. Apply one or two coats. For best results, use a premium Benjamin Moore custom-blended nylon/polyester brush, premium Benjamin Moore roller, or a similar product. Apply paint generously from unpainted area into wet area. This product can also be sprayed.

### Thinning/Clean Up

Conditioning with Benjamin Moore® K518 Extender may be necessary under certain conditions to adjust open time or spray characteristics. The chart below is for general guidance		
	Mild conditions	Severe conditions
	Humid (RH> 50 %) with no direct sunlight & with little to no wind	Dry (RH<50 %), in direct sunlight, or windy conditions
<b>Brush:</b> Nylon / Polyester	No thinning necessary	Add K518 Extender or water:  Max of 236 mL (8 fl. oz.) to a 3.79 L  <b>Never add other paints or solvents.</b>
<b>Roller:</b> Premium Quality 10 mm (3/8")		
<b>Spray: Airless</b> Pressure: 1500 -2500 psi Tip: 0.011-0.015		

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents. Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

### Environmental Health & Safety Information

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional  
health and safety information.**