



# ULTRA SPEC<sup>®</sup> MASONRY INTERIOR/EXTERIOR 100% ACRYLIC SEALER 608

## Features

- Reduces the porosity of masonry surfaces.
- Provides excellent surface adhesion.
- Tintable.
- High alkali resistant – up to pH-13.

## Recommended For

- For commercial and residential applications
- For application to new or previously painted masonry and plaster surfaces including; tilt-up concrete construction, stucco surfaces and block construction.

## General Description

Ultra Spec<sup>®</sup> Masonry Interior/Exterior 100% Acrylic Sealer is designed to penetrate and seal the surface of new or previously painted masonry surfaces providing the proper foundation for subsequent finish coats. It can be applied to masonry and plaster surfaces with pH levels as high as 13.

## Limitations

- Do not apply when air and surface temperatures are below 50 °F (10 °C).

## Product Information

<p><b>Colors — Standard:</b> White (01), Clear (00)</p> <p>(White may be tinted with up to 2.0 fl. oz. of Benjamin Moore<sup>®</sup> Gennex<sup>®</sup> colorants per gallon.)</p>	<table border="1"> <thead> <tr> <th colspan="2">Technical Data<sup>◇</sup></th> <th>White</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td></td> <td>100% Acrylic Latex</td> </tr> <tr> <td>Pigment Type</td> <td></td> <td>N/A</td> </tr> <tr> <td>Volume Solids</td> <td></td> <td>17.8%</td> </tr> <tr> <td>Coverage per Gallon at Recommended Film Thickness</td> <td></td> <td>200 – 400 Sq. Ft.</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet</td> <td>5.3 mils</td> </tr> <tr> <td></td> <td>– Dry</td> <td>0.95 mils</td> </tr> <tr> <td colspan="3">Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.</td> </tr> <tr> <td>Dry Time @ 77 °F (25 °C) @ 50% RH</td> <td>– To Touch</td> <td>1 Hour</td> </tr> <tr> <td></td> <td>– To Recoat</td> <td>4 Hours</td> </tr> <tr> <td colspan="3">Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.</td> </tr> <tr> <td>Dries By</td> <td></td> <td>Evaporation, Coalescence</td> </tr> <tr> <td>Viscosity</td> <td></td> <td>94 ± 2 KU</td> </tr> <tr> <td>Flash Point</td> <td></td> <td>None</td> </tr> <tr> <td>Gloss / Sheen</td> <td></td> <td>Semi-Gloss (45 - 65 @ 60°)</td> </tr> <tr> <td colspan="3"><small>Gloss/Sheen will vary due to surface texture and porosity</small></td> </tr> <tr> <td>Surface Temperature at Application</td> <td>– Min.</td> <td>50 °F</td> </tr> <tr> <td></td> <td>– Max.</td> <td>90 °F</td> </tr> <tr> <td>Thin With</td> <td></td> <td>Clean Water</td> </tr> <tr> <td>Clean Up Thinner</td> <td></td> <td>Clean Water</td> </tr> <tr> <td>Weight Per Gallon</td> <td></td> <td>8.5 lbs</td> </tr> <tr> <td>Storage Temperature</td> <td>– Min.</td> <td>40 °F</td> </tr> <tr> <td></td> <td>– Max.</td> <td>90 °F</td> </tr> <tr> <td colspan="3" style="text-align: center;"><b>Volatile Organic Compounds (VOC)</b></td> </tr> <tr> <td colspan="2"></td> <td>46 Grams/Liter .67 Lbs./Gallon</td> </tr> </tbody> </table>	Technical Data <sup>◇</sup>		White	Vehicle Type		100% Acrylic Latex	Pigment Type		N/A	Volume Solids		17.8%	Coverage per Gallon at Recommended Film Thickness		200 – 400 Sq. Ft.	Recommended Film Thickness	– Wet	5.3 mils		– Dry	0.95 mils	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.			Dry Time @ 77 °F (25 °C) @ 50% RH	– To Touch	1 Hour		– To Recoat	4 Hours	Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.			Dries By		Evaporation, Coalescence	Viscosity		94 ± 2 KU	Flash Point		None	Gloss / Sheen		Semi-Gloss (45 - 65 @ 60°)	<small>Gloss/Sheen will vary due to surface texture and porosity</small>			Surface Temperature at Application	– Min.	50 °F		– Max.	90 °F	Thin With		Clean Water	Clean Up Thinner		Clean Water	Weight Per Gallon		8.5 lbs	Storage Temperature	– Min.	40 °F		– Max.	90 °F	<b>Volatile Organic Compounds (VOC)</b>					46 Grams/Liter .67 Lbs./Gallon
Technical Data <sup>◇</sup>		White																																																																										
Vehicle Type		100% Acrylic Latex																																																																										
Pigment Type		N/A																																																																										
Volume Solids		17.8%																																																																										
Coverage per Gallon at Recommended Film Thickness		200 – 400 Sq. Ft.																																																																										
Recommended Film Thickness	– Wet	5.3 mils																																																																										
	– Dry	0.95 mils																																																																										
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.																																																																												
Dry Time @ 77 °F (25 °C) @ 50% RH	– To Touch	1 Hour																																																																										
	– To Recoat	4 Hours																																																																										
Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.																																																																												
Dries By		Evaporation, Coalescence																																																																										
Viscosity		94 ± 2 KU																																																																										
Flash Point		None																																																																										
Gloss / Sheen		Semi-Gloss (45 - 65 @ 60°)																																																																										
<small>Gloss/Sheen will vary due to surface texture and porosity</small>																																																																												
Surface Temperature at Application	– Min.	50 °F																																																																										
	– Max.	90 °F																																																																										
Thin With		Clean Water																																																																										
Clean Up Thinner		Clean Water																																																																										
Weight Per Gallon		8.5 lbs																																																																										
Storage Temperature	– Min.	40 °F																																																																										
	– Max.	90 °F																																																																										
<b>Volatile Organic Compounds (VOC)</b>																																																																												
		46 Grams/Liter .67 Lbs./Gallon																																																																										
<p><b>— Tint Bases:</b> Not available</p>																																																																												
<p><b>— Special Colors:</b> Contact your Benjamin Moore representative</p>																																																																												
<p><b>Certifications &amp; Qualifications:</b></p> <p><b>VOC compliant in all regulated areas</b></p> <p>Qualifies for LEED<sup>®</sup> v4 Credit Qualifies for CHPS low emitting credit (Collaborative for High Performance Schools) CDPH v1 Emission Certified Master Painters Institute MPI # 3, 3 X-Green<sup>™</sup> Water vapor permeance (breathability) ASTM D1693: 46.5 Perms</p>																																																																												
<p><b>Technical Assistance</b> Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-866-708-9180 or visit <a href="http://www.benjaminmoore.com">www.benjaminmoore.com</a></p>																																																																												

<sup>◇</sup> Reported values are for White. Contact Benjamin Moore for values of other bases or colors

## Surface Preparation

Surface must be dry, clean, and sound; free of chalk, peeling paint, form oils, efflorescence, and mildew. Remove chalk, surface deposits, and loose or scaling paint by scraping, sanding, and preferably power washing.

Glossy areas should be dulled. Un-weathered areas must be power washed or scrubbed with a detergent solution and rinsed to remove surface salts that can interfere with adhesion. Loose, sandy masonry should be hosed down thoroughly to remove surface particles and allowed to dry.

For masonry that has been allowed to cure for a minimum of 7 days under normal drying conditions and has a pH of 13 or less may be sealed with Ultra Spec® Masonry Interior/Exterior 100% Acrylic Sealer (608) prior to finishing.

A common exterior paint failure on masonry construction is peeling and scaling, often caused by painting over chalk deposits. The most practical and efficient way to remove this substance is by power washing. Multiple coats of paint that are in an advanced state of deterioration or prior applications of cement based coatings must be removed to a sound substrate.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## Primer/Finish Systems

New surfaces should be fully primed, and previously painted surfaces may be primed or spot primed as necessary.

### Rough or Pitted Masonry:

**Primer:** Ultra Spec® Masonry Interior/Exterior 100% Acrylic Sealer (608)

**Finish:** Appropriate Benjamin Moore® exterior house paint, or use Ultra Spec® Masonry Elastomeric Waterproof Coating - Low Lustre (360), Flat (359)

### Smooth Poured or Precast Concrete & Fiber Cement Siding:

**Primer:** Ultra Spec® Masonry Interior/Exterior 100% Acrylic Sealer (608)

**Finish:** Appropriate Benjamin Moore® exterior house paint, or use Ultra Spec® Masonry Elastomeric Waterproof Coating — Low Lustre (0360) or Flat (0359)

### Cured Plaster:

**Primer:** Ultra Spec® Masonry Interior/Exterior 100% Acrylic Sealer (608)

**Finish:** Appropriate Benjamin Moore® finish coat

**Repaint, All Substrates:** Prime bare areas with the primer recommended for the substrate above.

## Application

Do not apply when air and surface temperatures are below 50 °F (10 °C).

**Brush:** Stir thoroughly and apply generously as received in the container with a good quality synthetic brush. Work into crevices to ensure adequate penetration and sealing.

**Roller:** Stir thoroughly and apply generously as received in the container with a good quality long-nap roller. Work into crevices to ensure adequate penetration and sealing.

**Spray, Airless:** Fluid Pressure — 1,000 to 2,000 PSI;

Tip—.013-.017 Orifice

## Thinning/Clean up

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents. Clean up with warm soapy water. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

**USE COMPLETELY OR DISPOSE OF PROPERLY.** Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for more information on disposal options.**

## Environmental, Health & Safety Information

**Use only with adequate ventilation.** Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



**WARNING** Cancer and Reproductive Harm—  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

**FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL:** — Absorb with inert material and dispose of as specified under **Thinning/Clean up**.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional  
health and safety information**