



AURA®

WATERBORNE EXTERIOR PAINT

LOW LUSTRE FINISH K634

Features

- Extreme hide - it covers dark colours and imperfections in less coats
- Low temperature application
- Superior adhesion
- Delivers a high-build paint film for excellent durability
- Colour Lock™ technology and extreme UV resistance
- Soap and water clean-up Fast dry and re-coat times
- Resistant to fading, cracking, peeling, chalking blistering, dirt pick-up
- Provides a mildew resistant film
- Self-priming in most situations
- Vapour permeable

Recommended For

Recommended for exterior use on wood, fibre cement board, hard board, vinyl and aluminium siding, shakes, unglazed brick, concrete, stucco, cinder block and primed metal.

General Description

A super premium quality, 100% acrylic exterior low lustre latex finish. This product combines the advantages of our latest resin technology and our proprietary Gennex® colorant system to provide the ultimate exterior coating. This high solids formula is suitable for a variety of exterior surfaces and can be applied as low as 4.4 °C (40 °F). Aura® Waterborne Exterior Low Lustre Finish is suitable for wind driven rain when applied according to recommendations.

Limitations

- Do not apply when air and surface temperatures are below 4.4 °C (40 °F)
- For Wind-Driven Rain over smooth, and stable masonry only (non-elastomeric use). Follow primer/finish instructions.

Product Information

Colours — Standard: White (01)

— Benjamin Moore® Gennex® Tint Bases:
Benjamin Moore® Gennex® bases 1X, 2X, 3X & 4X

— Special Colours:
Contact your Benjamin Moore® representative.

Certifications & Qualifications:

Master Painters Institute MPI # 15, 315

The following results are based on independent, third-party laboratory testing:

- Passes Wind Driven Rain Test (38.4 ml) ASTM D6904
1 coat Ultra Spec® Acrylic Masonry Sealer K608 @ 4 mils WFT
1 or 2 coats Aura® Exterior Paint Low Lustre Finish K634 each @ 2.8 mils DFT
- Passes Alkali Resistance Test (no effect) ASTM D1308
1 coat Ultra Spec® Acrylic Masonry Sealer K608 @ 4 mils WFT
1 or 2 coats Aura® Exterior Paint Low Lustre Finish K634 @ 2.8 mils DFT
- Passes Conical Mandrel Flexibility Test (no cracking) ASTM D522
1 coat Aura® Exterior Paint Low Lustre Finish K634 @ 2.8 mils DFT
- Passes Mildew, Mould Resistance Test (no growth) ASTM D3273/D3274
1 coat Aura® Exterior Paint Low Lustre Finish K634 @ 2.8 mils DFT
- ASTM D1653 – Water Vapour Transmission Properties
Topcoat 63401, one-coat at 23.2 sq. m./3.79 L (2.8-mils DFT)---25.7 perms
- ASTM D2370 Tensile Properties
Peak Tensile Strength, psi 255
Elongation at Break, percent 120

LIFETIME LIMITED WARRANTY: Benjamin Moore & Co., Limited warrants that this product, when used in accordance with the label instructions, will not: 1. blister from properly prepared and primed surfaces; 2. peel from properly prepared and primed surfaces; and 3. wear down or weather to expose the previously painted surface. This limited warranty shall be effective for so long as you reside in your home and is made to the original residential consumer paint purchaser. This limited warranty is non-transferable. If this product fails to perform as explained above when used according to label instructions within the warranty period, Benjamin Moore & Co., Limited will, upon presentation of proof of purchase (original sales receipt), provide an equivalent or comparable product at no charge. Since we have no control over surface preparation or application, this limited warranty does not include the cost of labour for application of paint. Benjamin Moore & Co., Limited shall in no event be liable for indirect, special, incidental or consequential damages, including economic loss. This limited warranty gives you specific legal rights and is applicable to products sold in Canada. You may also have other rights, which vary from province to province. **EXCEPT AS SET OUT ABOVE OR PURSUANT TO APPLICABLE LAWS, THE LIMITED WARRANTY PROVIDED ABOVE IS THE SOLE AND EXCLUSIVE WARRANTY PROVIDED BY BENJAMIN MOORE & CO., LIMITED TO YOU FOR THIS PRODUCT AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, WHETHER ARISING OUT OF OPERATION OF LAW OR OTHERWISE.**

Technical Data

Technical Data		Pastel Base
Vehicle Type		Proprietary 100% Acrylic
Pigment Type		Titanium Dioxide
Volume Solids		42.7%
Coverage per 3.79 L at		23.3 – 32.5 sq. m
Recommended Film Thickness		(250 – 350 Sq. Ft.)
Recommended Film Thickness	– Wet	4.6 – 6.4 mils
	– Dry	2.0 – 2.8 mils
High Build System Coverage: 14.9 to 24.6 sq. m. (160 – 265 sq. ft.) 6-10 mils wet film thickness.		
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.		
Dry Time @ 25 °C	– To Touch	1 Hour
(77 °F) @ 50% RH	– To Recoat	4 Hours
High humidity and cool temperatures will result in longer dry, recoat and service times		
Dries By		Evaporation, Coalescence
Viscosity		102 ± 2 KU
Flash Point		None
Gloss / Sheen		Low Lustre (9 – 14 @ 60°)
Surface Temperature at Application	– Min.	4.4 °C (40 °F)
	– Max.	37.7 °C (100 °F)
Thin With		See Chart
Clean Up Thinner		Clean Water
Weight Per 3.79 L		5.26 kg (11.6 lbs)
Storage Temperature	– Min.	4.4 °C (40 °F)
	– Max.	32.2 °C (90 °F)

Volatile Organic Compounds (VOC)

46.6 g/L

CUSTOMER SERVICE INFORMATION CENTRE

1-800-361-5898
info@benjaminmoore.ca , www.benjaminmoore.ca

◇ Reported values are for Pastel Base. Contact Benjamin Moore for values of other bases or colours.

Aura® Waterborne Exterior Paint Low Lustre Finish K634

Surface Preparation

Surfaces must be clean and free of grease, wax, and mildew. Remove any chalk and loose or scaling paint. If previously coated with cement-base waterproofing paints, clean by sandblasting. Glossy surfaces must be dulled. Un-weathered areas such as eaves, ceilings, and overhangs should be washed with a detergent solution and/or rinsed with a strong stream of water from a garden hose to remove contaminants that can interfere with proper adhesion. Stains from mildew must be removed by cleaning with Benjamin Moore® Clean (K318) prior to coating the surface. **Caution:** Refer to the (K318) Clean technical data and material safety data sheets for instructions on its proper use and handling. For metal surfaces, remove rust. Wipe down with paint thinner to remove surface oils.

Difficult Substrates: Benjamin Moore® offers a number of specialty primers for use over difficult substrates such as bleeding woods, grease stains, crayon markings, hard glossy surfaces, or other substrates where paint adhesion or stain suppression is a particular problem. Your Benjamin Moore® retailer can recommend the right problem-solving primer for your special needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Primer/Finish Systems

Aura® Waterborne Exterior Low Lustre Finish is self priming on most properly prepared substrates, including: wood, fibre cement board, hardboard, nonferrous metals and cured masonry surfaces. On bare substrates two coats are required; previously painted surfaces can be finished with 1 or 2 coats. **Special Note:** For certain deep colours, Aura® Colour Foundation must be used to achieve maximum hide and the desired topcoat colour. Consult your retailer.

Wood, (Including Shakes and Shingles)

Primer: No primer needed

Finish: 2 coats Aura® Waterborne Exterior Paint Low Lustre Finish (K634)

Bleeding Type Woods, (Redwood and Cedar)

Primer: Fresh Start® Exterior Wood Primer (K094), Fresh Start® Multi-Purpose Oil Primer (F024) or 1-2 coats of Fresh Start® High-Hiding All Purpose Primer (K046) may be used.

Finish: 1 or 2 coats Aura® Waterborne Exterior Low Lustre Finish (K634)

Hardboard Siding, Bare or Factory Primed

Primer: No primer needed

Finish: 1 or 2 coats Aura® Waterborne Exterior Low Lustre Finish (K634)

Vinyl Siding & Vinyl Composite

In most cases, a primer is not necessary. Only areas of pitted and porous vinyl siding must be primed. In these cases, we recommend Fresh Start® High-Hiding All Purpose Primer (K046), or Fresh Start® Multi-Purpose Latex Primer (F023). **Colours that are safe for use on vinyl siding** – Do not paint vinyl with any colour darker than the original colour or having a Light Reflective Value (LRV) of less than 55 unless it is in the Benjamin Moore approved Colours for Vinyl palette and complies with the specific vinyl manufacturer guidelines when making the colour selection and painting. Otherwise, the colour will absorb more heat, possibly causing the siding to warp, resulting in additional repairs and expenses.

Rough or Pitted Masonry Poured and precast concrete and block construction should be allowed to cure for at least 30 days. All surfaces must be thoroughly brushed with stiff fibre bristles to remove loose particles

Primer: Ultra Spec® Masonry Interior/Exterior Hi-Build Block Filler (K571)

Finish: 1 or 2 coats Aura® Waterborne Exterior Low Lustre Finish (K634)

Poured or Pre-cast Concrete and Fibre Cement Siding

Primer: No primer needed

Finish: 1 or 2 coats Aura® Waterborne Exterior Low Lustre Finish (K634)

Masonry, Weathered and Unpainted, Soft with Age (Including Unglazed Brick): Remove any loose, sandy masonry by dry brushing.

Primer: Ultra Spec® Masonry Interior / Exterior 100% Acrylic Masonry Sealer (K608)

Finish: 1 or 2 coats Aura® Waterborne Exterior Low Lustre Finish (K634)

Ferrous Metal (Steel and Iron)

Primer: Ultra Spec® HP Acrylic Metal Primer (FP04) or Super Spec HP® Alkyd Metal Primer (KP06)

Finish: 1 or 2 coats Aura® Waterborne Exterior Low Lustre Finish (K634)

Non-Ferrous Metal (Galvanized & Aluminium) All new metal surfaces must be thoroughly cleaned with Corotech® Oil & Grease Emulsifier (V600) to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion

Primer: Not required on properly prepared surfaces

Finish: 1 or 2 coats Aura® Waterborne Exterior Low Lustre Finish (K634)

Repaint, All Substrates: Prime bare areas with the primer recommended for the substrate above.

Application

Use the same application techniques as you would for any low-VOC compliant coating. Use a Benjamin Moore® Premium roller or Premium extra firm nylon polyester brush for best results. Aura® paint features excellent flow and levelling; it's not necessary to over brush to smooth out brush marks. Aura® dries faster than other acrylic paints; avoid lap marks by not painting in direct sunlight and by coating sections of the surface either down or across the structure to natural breaks, maintaining a wet edge. If your edge begins to dry or you see that you missed a spot and the paint is already setting up, allow it to dry completely before touching up that area.

This product can also be sprayed; refer to the chart below.

Thinning/Clean up

Conditioning with Benjamin Moore® K518 Extender may be necessary under certain conditions to adjust open time or spray characteristics. The chart below is for general guidance		
	Mild conditions	Severe conditions
	Humid (RH> 50%) with no direct sunlight & with little to no wind	Dry (RH<50%), in direct sunlight, or windy conditions
Brush: Nylon / Polyester	No thinning necessary	Add K518 Extender or water:
Roller: Aura® Roller Cover		Max of 236 ml to a can of 3.79 L
Spray: Airless Pressure: 2,000 -3,000 psi Tip: 0.015-0.017		Never add other paints or solvents.
* Under normal application conditions Aura® may be sprayed to achieve a high build one coat system over properly prepared substrates that are in good condition. Refer to Surface Preparation / Priming Sections for appropriate priming and preparation information. High Build System Coverage: 14.9 to 24.6 sq. m. (160 – 265 sq. ft.) 6-10 mils wet film thickness.		

Clean up: Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or provincial environmental agency on disposal options.**

Environmental Health & Safety Information

May cause allergic skin reaction.

Do not get on skin or clothing.

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

WARNING: This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

Refer to Safety Data Sheet for additional health and safety information.