



# SUPER KOTE 5000

## ACRYLIC LATEX ENAMEL

### LOW-SHEEN EGGSHELL 1130

#### Features

- Premium commercial acrylic latex designed for the professional painter
- No spatter and fast-dry formula provide fast production
- Professional finish withstands washing
- Soap and water clean up
- Low VOC

#### General Description

Super Kote 5000 Latex Low-Sheen Eggshell Enamel is designed for commercial projects—when getting the job done quickly is a priority. It applies easily without spattering, covers most surfaces in one coat and may be washed repeatedly without film damage. Perfect for bedrooms, hallways or wherever a low-sheen eggshell finish is desirable.

#### Recommended For

Interior drywall, plaster, wood, metal, masonry and stucco in commercial, institutional and residential applications. It may be washed repeatedly without film damage. Perfect for bedrooms, hallways or wherever a low-sheen eggshell enamel is desired.

#### Limitations

- May be applied when surface and air temperatures are between 10 °C and 32.2 °C (50 °F and 90 °F).

#### Product Information

Colours — Standard:	Technical Data◇	White
White (1)	Vehicle Type	Vinyl Acrylic
	Pigment Type	Titanium Dioxide
	Volume Solids	31.9 ± 1.0%
	Coverage per 3.79 L at	27.9 – 37.2 sq. m.
	Recommended Film Thickness	(300 – 400 sq. ft.)
	Recommended Film Thickness	– Wet 4.0 – 5.3 mils
		– Dry 1.3 – 1.7 mils
	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.	
	Dry Time @ 25 °C (77 °F) @ 50% RH	– Tack Free 30 Minutes – To Recoat 4 Hours
	High humidity and cool temperatures will result in longer dry, recoat and service times.	
	Dries By	Coalescence
	Viscosity	95 – 100 KU
	Flash Point	N/A
	Gloss / Sheen	Eggshell (10 – 15 @ 85°)
	Surface Temperature at Application	– Min. 10 °C (50 °F) – Max. 32.2 °C (90 °F)
	Thin With	Clean Water
	Clean Up Thinner	Warm, Soapy Water
	Weight Per 3.79 L	5 kg (11.0 lbs)
	Storage Temperature	– Min. 7.2 °C (45 °F) – Max. 32.2 °C (90 °F)
	<b>Volatile Organic Compounds (VOC)</b>	
	95.8 Grams/Litre	
<b>Colours — Standard:</b> White (1)		
<b>— Tint Bases:</b> Pastel Base (32) Tint with Universal colorants only		
<b>— Special Colours:</b> Contact your retailer		
<b>Certifications &amp; Qualifications:</b>  This product meets the qualifications for LEED (Leadership in Energy and Environmental Design) projects as a non-flat coating.  Master Painters Institute MPI # 44  This product has been approved by CFIA (Canadian Food Inspection Agency) for use in Food Processing Facilities.		
<b>Technical Assistance:</b> Available through your local authorized independent retailer. For the location of the retailer nearest you, call 1-800-361-5898 or visit <a href="http://www.coronadopaint.ca">www.coronadopaint.ca</a>		

◇ Reported values are for White.

## Super Kote 5000 Acrylic Latex Enamel Low-Sheen Eggshell 1130

### Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Knife off any protrusions and prime plaster before and after applying patching compound. Remove any powder or loose particles.

**Primers:** New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>.

### Application

Stir thoroughly. Apply by brush (synthetic filament), roller or spray. Length of roller nap depends upon the texture of the surface. Thinning is not usually required for brush or roller application. Apply a full, even coat. Do not apply directly over chalky surfaces or bleeding stains. Apply only when surface and air temperatures are above 10 °C (50 °F).

#### Spray, Airless:

Fluid Pressure—1,500 to 2,000 PSI;

Tip—.017 - .019 Orifice

### Clean Up

Clean up with warm, soapy water followed by a clean water rinse.

### Environmental Health & Safety Information

**WARNING:** This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for  
additional health and safety information.**