



QUICKSTAIN BREAKAWAY GLAZE BASE 1GZ.1200

Features

- Ready To Use Formulation
- Removes Easily With Scotch-Brite™ Pads
- Tints with Industrial Colorants
- 10 Minutes To Recoat

Recommended For

FOR SHOP APPLICATION ONLY: Simulated grain/brush marks, highlights and accents, antiquing furniture and cabinetry, crackle finishes

General Description

Lenmar® QuickStain Breakaway Glaze base has been uniquely designed for the professional woodworker in the Furniture & Cabinet Industry and is formulated strictly for use in shop applications only. The major benefits of this glaze base include: the ability to tint with industrial pigments and quick dry times (in most cases, ready to topcoat in 10-15 minutes). This glaze system may be applied over pigmented systems or over transparent/translucent systems, by spray only. Many times, each application of a glaze is a unique use of the product, so test each finish for colour and adhesion on test samples before beginning any production.

Limitations

- Moisture content of wood should be no higher than 9%.
- Not for use on floors.

Product Information

Colours — Standard:	Technical Data◇	Clear Base
N/A	Vehicle Type	Alkyd/Oil
	Weight Solids	20.67% ± 1.0%
	Volume Solids	9.11%
— Tint Bases:	Coverage per 3.79 L at Recommended Film Thickness	N/A
1GZ.1200, Clear Base	Recommended Film Thickness	N/A
	— Wet	N/A
	— Dry	N/A
— Special Colours:	Dry Time @ 23.8 °C (75 °F) @ 50% RH	— Tack Free 5 - 10 Minutes — To Remove 5 - 10 Minutes — To Recoat 10 - 15 Minutes
Contact your Dealer/Distributor.	High humidity and cool temperatures will result in longer dry and recoat times.	
Certification:	Dries By	Evaporation
The products supported by this data sheet contain a maximum of 680 grams per litre VOC /VOS excluding water and exempt solvents.	Viscosity	N/A
	Flash Point	-2.8 °C (27 °F)
	Gloss / Sheen	N/A
	Surface Temperature at Application	— Min. 20 °C (68 °F) — Max. 32 °C (90 °F)
	Thin With	Do Not Thin
	Clean Up Thinner	VM&P Naphtha
	Weight Per 3.79 L	3.1 kg (6.80 – 6.90 lbs.)
	Storage Temperature	— Min. 10 °C (50 °F) — Max. 32 °C (90 °F)
Technical Assistance:	Volatle Organic Compounds (VOC)	
For Technical Assistance please contact your authorized Lenmar® Dealer/Distributor, your Lenmar® sales representative, Technical Service at 1-800-225-5554, or visit www.lenmar-coatings.ca	675 Grams/Litre	

◇ Reported values are for Clear Base. Contact dealer/distributor for values of other bases or colours.

QuickStain Breakaway Glaze Base 1GZ.1200

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php.

Application

For stained system, seal and sand surface. For pigmented system, apply undercoater and sand. Best if used over precatalyzed or conversion systems, but will work with any Lenmar® clear product. Allow all systems to dry/cure fully before proceeding. Apply one coat of QuickStain Breakaway Glaze by spray only, in accordance with label directions. Allow to dry 5 - 10 minutes, then remove the excess with a grey Scotch-Brite™ pad or extra-fine sanding sponge, to achieve the desired result. For best results, glaze should be removed within one hour of application. Topcoat when desired look has been achieved. Always check adhesion, colour, and finish clarity before proceeding with this type of application. See characteristics for other information

Specifications

Moisture content of wood should be no higher than 9%. Wood must be free of all surface contaminants. Using 120-grit sandpaper, sand with the grain and remove all dust. Finish as above. Thoroughly mix glaze. Test colour before proceeding. Colour intensity may vary due to wood species, surface preparation, and method of application. Read label and SDS for additional information and warnings.

Clean up

Clean up with VM&P Naphtha.

Environmental Health & Safety Information

DANGER!

Toxic if inhaled

Causes skin irritation

Causes serious eye irritation

May cause genetic defects

May cause cancer

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Highly flammable liquid and vapour

Risk of spontaneous combustion

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Wear eye/face protection. Do not breathe dust/fume/mist/vapours/spray. Keep away from heat/sparks/open flames/hot surfaces, no smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep cool. Immediately after use, place rags, steel wool or waste used with this product in a sealed water-filled metal container or lay flat to dry.

Response: If exposed or concerned get medical attention. If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical attention. If skin irritation occurs get medical attention. If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. If inhaled remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician. If swallowed immediately call a POISON CENTER or physician. Do NOT induce vomiting. In case of fire use CO₂, dry chemical, or foam for extinction.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents/container to an approved waste disposal plant. Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

This document represents hazards of the product referenced above. Refer to the individual Safety Data Sheet for hazards of the specific product you will be using.

KEEP OUT OF REACH OF CHILDREN

THIS PRODUCT IS INTENDED FOR SHOP OR OEM APPLICATION ONLY.

READ ALL DIRECTIONS BEFORE USE.
UNDERSTAND **ALL** DANGERS WITH THIS PRODUCT PRIOR TO USE.

Refer to Safety Data Sheet for additional health and safety information.