



# QUICKSTAIN®

## WATERBORNE WIPING STAIN

### 1WB.1100

#### Features

- Tint Base For Custom Colors
- Ready To Use Formulation
- Uniform Penetration
- Helps Against Blotching
- Superior Grain Definition
- Resists Fading and Bleeding
- Fast Drying
- Minimal Grain Raising

#### Recommended For

Kitchen Cabinets, Furniture, Window & Door Trim, Baseboards & Moldings, Interior Doors & Hand Rails.

#### General Description

Lenmar® QuickStain® Waterborne Wiping Stains have been uniquely designed for the professional woodworker in the Furniture & Cabinet Industry and are formulated to be quick drying and with consistent color. The major benefits of this stain include: a natural / clear tint base for custom tinting with universal colorants (or another approved system), ease of application for uniform penetration, superior grain definition, and resistance to bleeding and fading.

#### Limitations

- Entire system should not exceed 5 mils dry.

#### Product Information

Colors — Standard:	Technical Data◇	Natural/Clear Base
N/A	Vehicle Type	Proprietary
	Pigment Type	N/A
<b>— Tint Bases:</b>	Weight Solids	13% ± 1.0%
1WB.1100, Natural/Clear Tint Base	Coverage per Gallon at 1 mil DFT	N/A
Tint with Universal colorants.	Recommended Film Thickness	– Wet: N/A – Dry: N/A
<b>— Special Colors:</b>	Dry Time @ 75 °F (23.8 °C) @ 50% RH	– Spray and Wipe: 15 – 30 Minutes
Contact your Dealer/Distributor.	High humidity and cool temperatures will result in longer dry and recoat times.	
<b>Certifications &amp; Qualifications:</b>	Dries By	Evaporation
<b>VOC compliant in all regulated areas</b>	Viscosity	13 – 17 Seconds (#3 Zahn)
The products supported by this data sheet contain a maximum of 250 grams per liter VOC /VOS (2.09 lbs. /gal.) excluding water & exempt solvents.	Flash Point	>200°F
	Gloss / Sheen	N/A
	Surface Temperature at Application	– Min.: 68 °F – Max.: 90 °F
	Thin With	Not Recommended
	Clean Up Thinner	Water
	Weight Per Gallon	8.55 – 8.75 lbs
<b>Technical Assistance:</b>	Storage Temperature	– Min.: 50 °F – Max.: 90 °F
Available through your local authorized independent Lenmar dealer. For the location of the dealer nearest you, call 1-866-708-9180 or visit <a href="http://www.lenmar-coatings.com">www.lenmar-coatings.com</a>	<b>Volatile Organic Compounds (VOC)</b>	
	235 Grams/Liter	1.96 Lbs./Gallon

◇ Reported values are for Clear Base. Contact dealer/distributor for values of other bases or colors.

## QuickStain® Waterborne Wiping Stain 1WB.1100

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### Application

**ENTIRE SYSTEM SHOULD NOT EXCEED MORE THAN 5 MILS DRY. LENMAR PRODUCTS ARE DESIGNED FOR INTERIOR USE, BY SPRAY APPLICATION ONLY.**

Over properly prepared interior wood surfaces, apply only one full coat of QuickStain® Waterborne Wiping Stain by spray, natural bristle brush or with a clean lint-free cloth. Remove all excess stain within 5 minutes after application. When dry (usually 15-30 minutes), continue with sealer and topcoat system in accordance with their Product Data Sheets. Check adhesion before proceeding with this application.

**ENTIRE SYSTEM SHOULD NOT EXCEED MORE THAN 5 MILS DRY.**

### Specifications

Moisture content of wood should be no higher than 9%. Wood must be free of all surface contaminants. Using 150-grit sandpaper, sand with the grain and remove all dust. Thoroughly mix stain (**do not shake**) before use. Test color before proceeding. Color intensity may vary due to wood species, surface preparation, and method of application. Read label and SDS for additional information and warnings.

### Clean Up

Clean up with water.

## Environmental Health & Safety Information

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS)

Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling. Refer to Safety Data Sheet for additional health and safety information.



**WARNING** Cancer and Reproductive Harm—  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

**KEEP OUT OF REACH OF CHILDREN  
KEEP FROM FREEZING**

**Refer to Safety Data Sheet for  
additional health and safety information.**