



SUPER KOTE 3000

ACRYLIC LATEX EGGSHELL

302 LINE

Features

- Acrylic Latex Eggshell Paint
- Washable
- Low Sheen
- Fast Drying

General Description

Super Kote 3000 Acrylic Latex Eggshell is designed particularly for the professional contractor. The formulation provides that necessary balance between performance and value. Super Kote 3000 Acrylic Latex Eggshell demonstrates good hide and will withstand repeated washing without damaging the film. May be used for new work or re-do, commercial or residential interior applications.

Recommended For

Professional grade paint for commercial and residential use on drywall, plaster, wood, metal and masonry. Provides excellent touch up and hides imperfections in new construction and repaint work.

Limitations

- Apply only when surface and air temperatures are above 10 °C (50 °F).

Product Information

Colours — Standard:	Technical Data [◇]	White
White (1)	Vehicle Type	Acrylic
— Tint Bases:	Pigment Type	Titanium Dioxide
Pastel Base (32), Tint Base (33)	Volume Solids	30.2 ± 1.0%
Tint with Universal colorants only	Coverage per 3.79 L at	(27.9-37.2 m ²)
— Special Colours:	Recommended Film Thickness	300 – 400 Sq. Ft.
Contact your dealer.	Recommended Film Thickness	– Wet 4.0 to 5.3 mils
Certifications & Qualifications:	– Dry 1.2 to 1.6 mils	
VOC compliant in all regulated areas	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.	
The products supported by this data sheet contain a maximum of 50 grams per liter VOC/VOS (0.41 lbs/gal.) excluding water & exempt solvents.	Dry Time @ 77°F	– Tack Free 2 Hours
This product meets the qualifications for LEED (Leadership in Energy and Environmental Design) projects as a non-flat coating.	(25°C) @ 50% RH	– To Recoat 4 Hours
Technical Assistance:	High humidity and cool temperatures will result in longer dry, recoat and service times.	
Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-361-5898 or visit www.coronadopaint.ca	Dries By	Evaporation
	Viscosity	92 – 97 KU
	Flash Point	N/A
	Gloss / Sheen	Eggshell (15 - 20 @ 85°)
	Surface Temperature at Application	– Min. 10 °C (50 °F)
	– Max.	32 °C (90 °F)
	Thin With	Clean Water
	Clean Up Thinner	Warm Soapy Water
	Weight Per 3.79-L Can	4.67 kg (10.3 lbs.)
	Storage Temperature	– Min. 4.4 °C (40 °F)
	– Max.	35 °C (95 °F)
	Volatile Organic Compounds (VOC)	
	43.3 Grams/Litre	

[◇] Reported values are for White, Contact dealer for values of other bases or colours.

Super Kote 3000 Acrylic Latex Eggshell 302 Line

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Remove any powder or loose particles.

Primers: New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Application

Stir product with a circular, lifting motion before you begin to paint. Product may be applied by brush, roller, pad or spray techniques, at a rate of application not to exceed 37.2 m²/3.79 L (400 square feet per gallon). Surface texture and porosity will affect actual yield. For best brush application results, use a quality synthetic filament brush. For roller application use a 6.4 mm or 9.5 mm (¼" or 3/8") nap cover for smooth surfaces, a 12.7 mm (½") nap cover for semi-rough surfaces, and a 19.1 mm (¾") nap cover for rough surfaces. May be reduced with clean water up to 15% for spray application.

Spray, Airless - Fluid Pressure—1,500 to 2,000 PSI; Tip—0.43-0.53 mm (.017 - .019") Orifice

Clean-Up

Clean up with warm, soapy water.

Environmental Health & Safety Information

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**