



SUPER KOTE[®] 3000

ACRYLIC LATEX SEMI-GLOSS

304 LINE

Features

- Acrylic Latex Semi-Gloss Paint
- Washable
- Semi-Gloss Sheen
- Fast Drying
- Water Clean Up

Recommended For

Professional grade paint for commercial and residential use on drywall, plaster, wood, metal and masonry. Provides excellent touch up and hides imperfections in new construction and repaint work.

General Description

A professional grade Acrylic Latex Semi-Gloss that exhibits good washing characteristics. May be applied on interior walls and trim in kitchens, hallways, bathrooms, or other areas where routine maintenance is required. This product dries quickly and resists spattering.

Limitations

- Apply only when surface and air temperatures are above 50 °F (10 °C).

Product Information

Colors — Standard:

White (1)

— Tint Bases:

Pastel Base (32), Tint Base (33)

Tint with Universal colorants only

— Special Colors:

Contact your dealer.

Certification & Qualifications :

The products supported by this data sheet contain a maximum of 100 grams per liter VOC/VOS (0.83 lbs. /gal.) excluding water & exempt solvents.

This product meets the qualifications for LEED (Leadership in Energy and Environmental Design) projects as a non-flat coating.

VOC REGION	COMPLIANT
FEDERAL	YES
OTC	YES
OTCII	YES
CARB	YES
CARB07	YES
UTAH	YES
AZMC	YES
SCAQMD	NO

Technical Assistance:

Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-866-708-9180, or visit www.coronadopaint.com

Technical Data[◇]

White

Vehicle Type	Acrylic
Pigment Type	Titanium Dioxide
Volume Solids	28.9 ± 1.0%
Coverage per Gallon at Recommended Film Thickness	300 – 400 Sq. Ft.
Recommended Film Thickness	– Wet 4.0 to 5.3 mils – Dry 1.2 to 1.5 mils

Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.

Dry Time @ 77 °F (25 °C) @ 50% RH	– Tack Free	2 Hours
	– To Recoat	4 Hours

High humidity and cool temperatures will result in longer dry, recoat and service times.

Dries By Coalescence

Viscosity 90 – 95 KU

Flash Point N/A

Gloss / Sheen Semi-Gloss (45 - 55 @ 60°)

Surface Temperature at Application	– Min.	50 °F
	– Max.	90 °F

Thin With Clean Water

Clean Up Thinner Warm Soapy Water

Weight Per Gallon 10.0 lbs.

Storage Temperature	– Min.	40 °F
	– Max.	95 °F

Volatile Organic Compounds (VOC)

94 Grams/Liter 0.78 Lbs./Gallon

[◇] Reported values are for White. Contact dealer for values of other bases or colors.

Super Kote® 3000 Acrylic Latex Semi-Gloss 304 Line

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, peeling or flaking paint, water soluble materials and mildew. Remove any peeling or flaking paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure.

Primers: New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Stir product thoroughly with a circular, lifting motion ensuring even mixing throughout.

Roller – 3/8" to 1 ¼ " nap, depending on surface texture

Brush – Nylon or polyester filament

Spray, Airless – Fluid Pressure—1,500 to 2,000 PSI; Tip—.015 - .019 Orifice

Clean Up

Clean up with warm, soapy water.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Clean Up".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**