



SUPER KOTE 3000

ACRYLIC LATEX SEMI-GLOSS

304 LINE

Features

- Acrylic Latex Semi-Gloss Paint
- Washable
- Semi-Gloss Sheen
- Fast Drying
- Water Clean-Up

General Description

A professional grade Acrylic Latex Semi-Gloss that exhibits good washing characteristics. May be applied on interior walls and trim in kitchens, hallways, bathrooms, or other areas where routine maintenance is required. This product dries quickly, and resists spattering during application.

Recommended For

Professional grade paint for commercial and residential use on drywall, plaster, wood, metal and masonry. Provides excellent touch-up and hides imperfections in new construction and repaint work.

Limitations

- Apply only when surface and air temperatures are above 10°C (50°F).

Product Information

Product Information		White	
Colours — Standard: White	Technical Data	Acrylic	
	Pigment Type	Titanium Dioxide	
— Tint Bases: 304-32, Pastel Base 304-33, Tint Base	Volume Solids	28.9 ± 1.0%	
	Coverage per 3.79 L at Recommended Film Thickness	27.9-37.2 m ² (300 – 400 Sq. Ft.)	
— Special Colours: Contact your dealer.	Recommended Film Thickness	4.0 to 5.3 mils	
	Thickness	1.2 to 1.5 mils	
Certifications & Qualifications : The products supported by this data sheet contain a maximum of 100 grams per liter VOC/VOS (0.83 lbs. /gal.) excluding water & exempt solvents. This product is compliant under the Ozone Transport Commission regulations as a Non-Flat Coating. This product meets the qualifications for LEED (Leadership in Energy and Environmental Design) projects as a non-flat coating.	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.		
	Dry Time @ 77°F (25°C) @ 50% RH	– Tack Free – To Recoat	2 Hours 4 Hours
Technical Assistance: Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-361-5898 or visit www.coronadopaint.ca	High humidity and cool temperatures will result in longer dry, recoat and service times.		
	Dries By	Coalescence	
	Viscosity	90 – 95 KU	
	Flash Point	N/A	
	Gloss / Sheen	Semi-Gloss 45 - 55 units @16°C (60°F)	
	Surface Temperature at Application	– Min. – Max.	10°C (50°F) 32°C (90°F)
	Thin With	Clean Water	
	Clean Up Thinner	Warm Soapy Water	
	Weight Per Gallon	4.54 kg (10.0 lbs.)	
	Storage Temperature	– Min. – Max.	4.4°C (40°F) 35°C (95°F)
	Volatile Organic Compounds (VOC)		
	94 Grams/Litre	0.35 kg/3.79 L (0.78 Lbs./Gallon)	

◇ Reported values are for White. Contact dealer for values of other bases or colours.

Super Kote 3000 Acrylic Latex Semi-Gloss 304 Line

Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, peeling or flaking paint, water soluble materials and mildew. Remove any peeling or flaking paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure.

Primers: New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right primer solving primer necessary to meet your needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Application

Stir product thoroughly with a circular, lifting motion ensuring even mixing throughout.

Roller – 9.5-31.8 mm (3/8"-1¼") nap, depending on surface texture

Brush – Nylon or polyester filament

Spray, Airless – Fluid Pressure—1,500 to 2,000 PSI; Tip—0.38-0.48 mm (.015 - .019") Orifice

Clean-Up

Clean up with warm, soapy water.

Environmental Health & Safety Information

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**