



SUPREME

HOUSE PAINT EXTERIOR ACRYLIC

SATIN 408 LINE

Features

- Fast Dry
- Blister Resistant
- Suitable for use in USDA inspected facilities
- Excellent Color Retention
- Durable
- Low Odor
- Low VOC

General Description

An Acrylic Latex Satin House Paint which provides lasting service over new or previously painted surfaces in good condition. Acrylic Latex House Paint will provide a durable and protective finish on any properly prepared and primed exterior surface.

Recommended For

For exterior wood, hardboard, masonry and properly prepared metal surfaces in commercial, institutional and residential applications. It is self-priming on non-bleeding woods, masonry and clean, rust free galvanized surfaces. Also apply over primed ferrous metal and aluminum. Contains an agent which inhibits growth of mildew on the surface of the paint film.

Limitations

- Apply only when surface and air temperatures are above 50°F (10 °C).

Product Information

Colors — Standard: White	Technical Data \diamond White Vehicle Type Acrylic Pigment Type Titanium Dioxide Volume Solids 32.5 \pm 1.0%
— Tint Bases: 408-33, Tint Base 408-34, Deep Base 408-36, Accent Base	Coverage per Gallon at Recommended Film Thickness 350 - 450 Sq. Ft. Recommended Film Thickness — Wet 3.6 to 4.6 mils — Dry 1.2 to 1.5 mils
— Special Colors: Contact your dealer.	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.
Certification: The products supported by this data sheet contain a maximum of 100 grams per liter VOC/VOS (0.83 lbs./gal.) excluding water & exempt solvents. This product is compliant under the Ozone Transport Commission regulations as a Non-Flat Coating.	Dry Time @ 77°F (25°C) @ 50% RH — Tack Free 30 Minutes — To Recoat 4 Hours High humidity and cool temperatures will result in longer dry, recoat and service times. Dries By Evaporation Viscosity 92 – 97 KU Flash Point 200°F or greater (TT-P-141, Method 4293) Gloss / Sheen Satin 30 -35 units @85°
Technical Assistance: Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-225-5554 or visit www.coronadopaint.com .	Surface Temperature — Min. 50°F at Application — Max. 90°F Thin With Clean Water Clean Up Thinner Warm Soapy Water Weight Per Gallon 10.6 lbs. Storage Temperature — Min. 40°F — Max. 95°F Volatile Organic Compounds (VOC) 95 Grams/Liter 0.79 Lbs./Gallon

\diamond Reported values are for White. Contact your dealer for values of other bases or colors.

Supreme House Paint Exterior Acrylic Satin 408 Line

Surface Preparation

Surfaces must be clean and free of grease, wax, and mildew. Remove any chalk and loose or scaling paint. If previously coated with cement-base waterproofing paints, clean by sandblasting. Glossy surfaces must be dulled. Un-weathered areas such as eaves, ceilings, and overhangs should be washed with a detergent solution and/or rinsed with a strong stream of water from a garden hose to remove contaminants that can interfere with proper adhesion. Stains from mildew must be removed by cleaning with an anti-mildew wash prior to coating the surface. **Caution:** Refer to the anti-mildew wash technical data and material safety data sheet for instructions on its proper use and handling. For metal surfaces, remove rust. Wipe down with paint thinner to remove surface oils.

All new masonry surfaces must be power washed or brushed thoroughly with stiff fiber bristles to remove loose particles. New masonry substrates must be allowed to cure for 30 days before priming or painting.

Primers: New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Stir thoroughly. Apply by brush (synthetic filament), roller or spray. Length of roller nap depends upon the texture of the surface. Thinning is not usually required for brush or roller application. Apply a full, even coat. Do not apply directly over chalky surfaces or bleeding stains. Apply only when surface and air temperatures are above 50 °F (10 °C).

Clean Up

Clean up with warm, soapy water.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only with adequate ventilation. Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under "Clean Up".

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**