



FINALTOUCH™

FLAT WALL & CEILING PAINT

62 LINE

Features

- Fast Drying
- Water Clean-Up
- Excellent Touch-Up
- Resists Spattering

General Description

FinalTouch™ is formulated to provide perfect touch-up and final finishing for all interior new construction wall surfaces. After spray and back-roll of your final finish coat, FinalTouch™ is designed to feather smoothly with a fine nap roller to provide invisible touch-ups.

Recommended For

Interior – Drywall, Plaster, Wood, Metal, Masonry, Cement, Block, Stucco. An ideal flat coating to be used for new construction as well as general maintenance, apartments and the budget minded consumers.

Limitations

- Do not apply directly over chalky surfaces or bleeding stains.
- Apply when temperature is above 10 °C (50 °F) and in humidity less than 85%.
- Not for use in high abuse areas.

Product Information

Colors — Standard: White (1)	Technical Data◇		White
— Tint Bases: Pastel Base (32) Tint with Universal colorants only	Vehicle Type		Vinyl Acrylic
— Special Colors: Contact your dealer.	Pigment Type		Titanium Dioxide
Certifications & Qualifications: VOC compliant in Canada The products supported by this data sheet contain a maximum of 50 grams per litre VOC/VOS (0.42 lbs/gal.) excluding water & exempt solvents. This product meets the qualifications for LEED (Leadership in Energy and Environmental Design) projects as a flat coating.	Volume Solids		33 ± 1.0%
	Coverage per Gallon at Recommended Film Thickness		27.8 – 37.1 sq. m. (300 – 400 sq. ft.)
Technical Assistance: Available through your local authorized independent dealer. For the location of the retailer nearest you, call 1-877-711-6830 or visit www.coronadopaint.ca	Recommended Film Thickness		– Wet 4.0 – 5.4 mils – Dry 1.3 – 1.8 mils
	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.		
	Dry Time @ 77 °F (25 °C) @ 50% RH		– Tack Free 30 Minutes – To Recoat 4 Hours
	High humidity and cool temperatures will result in longer dry, recoat and service times.		
	Dries By		Coalescence
	Viscosity		108 – 113 KU
	Flash Point		93.2 °C (200 °F) or greater (TT-P-141, Method 4293)
	Gloss / Sheen		Flat (0 – 2 @ 85°)
	Surface Temperature at Application		– Min. 10 °C (50 °F) – Max. 32.2 °C (90 °F)
	Thin With		Clean Water
Clean Up Thinner		Warm Soapy Water	
Weight Per Gallon		10.9 lbs.	
Storage Temperature		– Min. 7.2 °C (45 °F) – Max. 35 °C (95 °F)	
Volatile Organic Compounds (VOC)			
46 Grams/Litre		0.17 kg/3.79 L	

◇ Reported values are for White. Contact dealer for values of other bases or colors.

Surface Preparation

Surface to be painted must be clean and free of dirt, chalk, mildew, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by scrubbing with warm soapy water and thoroughly rinsed with clean water. Mildew must be removed by scrubbing with a solution of one part household bleach* and three parts water. Rinse well with clean water and allow it to dry thoroughly before painting. Wax should be removed with a commercial wax stripper or by solvent cleaning. Grease should be cleaned by using an Oil & Grease Emulsifier. Rust must be removed by hand sanding or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Glossy surfaces must be dulled by lightly sanding. Remove sanding dust before paint application. Any exposed substrate should be spot primed with the appropriate primer.

*Follow bleach manufacturer's instructions for safe handling and use of bleach solution.

Primers: New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

Application

Stir product thoroughly with a circular, lifting motion ensuring even mixing throughout.

Roller – 3/8" nap, depending on surface texture

Brush – Nylon or polyester filament

Airless Spray – Tip size and atomization pressure will vary with type of equipment, viscosity and temperature. Normally a tip size of .017 @ 2000-2500 psi will provide the most satisfactory spray pattern. If necessary product may be thinned up to 10% with clean water for spray application.

Best results are more likely obtained by using quality application tools. Do not apply directly over chalky surfaces or bleeding stains. Apply when temperature is above 10 °C (50 °F) and in humidity less than 85%.

Clean Up

Clean up with warm, soapy water followed by a clean water rinse.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

Use only in a well ventilated area. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

WARNING: This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**