



# CORONADO GRAND<sup>®</sup>

## ACRYLIC LATEX PAINT & PRIMER

### MATTE FINISH 701

#### Features

- Dries to a smooth finish
- Exceptional durability
- Washable
- Under 50 g/L VOC
- Paint and Primer Together
- Easy application
- Excellent Coverage

#### Recommended For

Ideal for walls, ceilings and wood trim throughout residential or commercial structures. For drywall, plaster, wood, previously painted metal and masonry. Its durability lends itself to use in kitchens, laundries, family rooms, bedrooms, common areas, etc.

#### General Description

Coronado Grand<sup>®</sup> Interior Acrylic Latex Paint & Primer is a quality, low VOC acrylic paint engineered to provide excellent color retention and washability. It is easy to apply, dries to a smooth professional finish and offers quality performance and exceptional value.

#### Limitations

- Apply only when surface temperature is above 50 °F (10 °C)

#### Product Information

| Colors — Standard:   | Technical Data <sup>◇</sup>  | White  |
|--|--|--|
| White  | Vehicle Type   | Acrylic  |
|  | Pigment Type   | Titanium Dioxide   |
| <b>— Tint Bases:</b>   | Volume Solids  | 38.6 %   |
| Pastel Base (32), Tint Base (33), Deep Base (34), Accent Base (36)   | Coverage per Gallon at Recommended Film Thickness  | 400 - 450 Sq. Ft.  |
| Tint with Universal colorants only   | Recommended Film Thickness   | – Wet 3.8 mils<br>– Dry 1.5 mils                                   |
| <b>— Special Colors:</b>   | Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint. |  |
| Contact your dealer  | Dry Time @ 77 °F (25 °C) @ 50% RH  | – Tack Free 1 Hour<br>– To Recoat 1-2 Hours<br>– Full Cure 14 Days |
| <b>Certifications &amp; Qualifications:</b>  | Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times.   |  |
| <b>VOC compliant in all regulated areas</b>  | Dries By   | Evaporation, Coalescence   |
| This product meets the qualifications for LEED (Leadership in Energy and Environmental Design) projects as a non-flat coating  | Viscosity  | 98 – 102 KU  |
| <b>Technical Assistance:</b>   | Flash Point  | 200°F or greater (TT-P-141, Method 4293)                           |
| Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-866-708-9180, or visit <a href="http://www.coronadopaint.com">www.coronadopaint.com</a> | Gloss / Sheen  | Matte (6 - 10 @ 85°)   |
|  | Surface Temperature at Application   | – Min. 50 °F<br>– Max. 90 °F                                       |
|  | Thin With  | Clean Water  |
|  | Clean Up Thinner   | Warm Soapy Water   |
|  | Weight Per Gallon  | 11.0 lbs   |
|  | Storage Temperature  | – Min. 45 °F<br>– Max. 95 °F                                       |
|  | <b>Volatile Organic Compounds (VOC)</b>  |  |
|  | 50 Grams/Liter   | 0.42 Lbs./Gallon   |

<sup>◇</sup> Reported values are for White, Contact dealer for values of other bases or colors.

## Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials and mildew. Remove any peeling or scaling paint, and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust. Spot prime before and after filling nail holes, cracks, and other surface imperfections.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure.

**Primers:** New surfaces should be primed where indicated. Previously painted surfaces should be spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## Primer/Finish Systems

Coronado Grand® Interior Acrylic Paint Matte Finish will act as its own primer on specific substrates as well as on previously painted surfaces, providing the optimal foundation for the subsequent finish coat.

**Special Note:** Certain colors require a primer tinted to a special prescription formula to achieve the desired color. Consult your retailer.

**Wood (non-bleeding), and engineered wood products:**

**Primer/Finish:** 1 or 2 coats of Coronado Grand® Matte Finish (701)

**Bleeding Type Woods (Redwood and Cedar):**

**Primer:** Oil-based, tannin and stain blocking primer such as INSL-X® Prime Lock™ Plus or equivalent

**Finish:** 1 or 2 coats of Coronado Grand® Matte Finish (701)

**Drywall:**

**Primer/Finish:** 1 or 2 coats of Coronado Grand® Matte Finish (701)

**Plaster:**

**Primer:** Super Kote 5000® Interior Acrylic Latex Primer Sealer (40-11)

**Finish:** 1 or 2 coats of Coronado Grand® Matte Finish (701)

**Masonry; Rough or Pitted:**

**Primer:** Super Kote 5000® Production Block Filler (958)

**Finish:** 1 or 2 coats of Coronado Grand® Matte Finish (701)

**Masonry (Cured); Smooth Poured or Precast Concrete:**

**Primer/Finish:** 1 or 2 coats of Coronado Grand® Matte Finish (701)

**Hard glossy alkyd surfaces:** Abrasion by sanding for optimum adhesion prior to priming with Coronado® Grip & Seal Latex Stain Blocker (116)

**Ferrous Metal (Steel & Iron):**

**Primer:** Rust Scat® Acrylic Metal Primer (36) or Rust Scat® Alkyd Metal Primer (35)

**Finish:** 1 or 2 coats of Coronado Grand® Matte Finish (701)

**Non-Ferrous Metal (Galvanized & Aluminum):** All new metal surfaces must be thoroughly cleaned with an Oil & Grease Emulsifier to remove contaminants. New shiny non-ferrous metal surfaces that will be subject to abrasion should be dulled with very fine sandpaper or a synthetic steel wool pad to promote adhesion.

**Primer:** Rust Scat® Acrylic Metal Primer (36)

**Finish:** 1 or 2 coats of Coronado Grand® Matte Finish (701)

## Application

Stir thoroughly before use. Apply one or two coats. For best results, use a Professional custom-blended nylon/polyester brush, Professional roller, or a similar product. This product can also be sprayed. Two coats provide maximum hiding and film durability.

**For best brush application** results, use a quality polyester or nylon filament brush. **For roller application**, use a 3/8" to 1" nap cover depending on surface texture. Do not jeopardize the success of your painting project by using poor quality applicator tools.

**Spray, Airless:**

Fluid Pressure —1,500 to 2,500 PSI;

Tip — .013 - .017 Orifice.

Apply only when surface and air temperatures are between 50° and 90° F.

## Clean Up

Clean up with warm, soapy water followed by a clean water rinse.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

## Environmental Health & Safety Information

**Use only with adequate ventilation.** Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



**WARNING** Cancer and Reproductive Harm—  
[www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

**FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL** – Absorb with inert material and dispose of as specified under “Clean up”.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for  
additional health and safety information.**