



SUPER KOTE 5000[®]

EXTERIOR ACRYLIC SATIN

803 LINE

Features

- Fast Dry
- Blister Resistant
- Excellent Color Retention
- Durable
- Low VOC

Recommended For

For exterior wood, hardboard, masonry and properly prepared metal surfaces in commercial, institutional and residential applications. It is self-priming on non-bleeding woods, masonry and clean, rust free galvanized surfaces. Also apply over primed ferrous metal and aluminum. Contains an agent which inhibits growth of mildew on the surface of the paint film.

General Description

An Acrylic Satin Exterior Paint which provides lasting service over new or previously painted surfaces in good condition. Acrylic Exterior Paint will provide a durable and protective finish on any properly prepared and primed exterior surface.

Limitations

- Apply only when surface and air temperatures are above 50 ° (10°C)

Product Information

Colors — Standard:

White (01)

— Tint Bases:

Tint Base (33), Deep Base (34), Accent Base (36)

Tint only with Universal Colorants

— Special Colors:

Contact your dealer.

Certification & Qualifications:

The products supported by this data sheet contain a maximum of 100 grams per liter VOC/VOS (0.83 lbs/gal.) excluding water & exempt solvents.

Master Painters Institute MPI # 214

VOC REGION	COMPLIANT
FEDERAL	YES
OTC	YES
LADCO	YES
OTCII	YES
OTCII RI	YES
CARB	YES
CARB07	YES
UTAH	YES
AZMC	YES
SCAQMD	NO

Technical Assistance:

Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-866-708-9180, or visit www.coronadopaint.com

Technical Data[◇]

White

Vehicle Type	Acrylic				
Pigment Type	Titanium Dioxide				
Volume Solids	32.5 ± 1.0%				
Coverage per Gallon at Recommended Film Thickness	350 - 450 Sq. Ft.				
Recommended Film Thickness	<table border="0"> <tr> <td>– Wet</td> <td>3.6 to 4.6 mils</td> </tr> <tr> <td>– Dry</td> <td>1.2 to 1.5 mils</td> </tr> </table>	– Wet	3.6 to 4.6 mils	– Dry	1.2 to 1.5 mils
– Wet	3.6 to 4.6 mils				
– Dry	1.2 to 1.5 mils				
Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.					
Dry Time @ 77 °F (25 °C) @ 50% RH	<table border="0"> <tr> <td>– Tack Free</td> <td>30 Minutes</td> </tr> <tr> <td>– To Recoat</td> <td>4 Hours</td> </tr> </table>	– Tack Free	30 Minutes	– To Recoat	4 Hours
– Tack Free	30 Minutes				
– To Recoat	4 Hours				
High humidity and cool temperatures will result in longer dry, recoat and service times.					
Dries By	Evaporation				
Viscosity	92 – 97 KU				
Flash Point	200 °F or greater (TT-P-141, Method 4293)				
Gloss / Sheen	Satin (30 - 35 @ 85°)				
Surface Temperature at Application	<table border="0"> <tr> <td>– Min.</td> <td>50 °F</td> </tr> <tr> <td>– Max.</td> <td>100 °F</td> </tr> </table>	– Min.	50 °F	– Max.	100 °F
– Min.	50 °F				
– Max.	100 °F				
Thin With	Clean Water				
Clean Up Thinner	Warm Soapy Water				
Weight Per Gallon	10.6 lbs.				
Storage Temperature	<table border="0"> <tr> <td>– Min.</td> <td>40 °F</td> </tr> <tr> <td>– Max.</td> <td>95 °F</td> </tr> </table>	– Min.	40 °F	– Max.	95 °F
– Min.	40 °F				
– Max.	95 °F				

Volatile Organic Compounds (VOC)

95 Grams/Liter 0.79 Lbs./Gallon

[◇] Reported values are for White. Contact your dealer for values of other bases or colors.

Super Kote 5000® Exterior Acrylic Satin 803 Line

Surface Preparation

Surfaces must be clean and free of grease, wax, and mildew. Remove any chalk and loose or scaling paint. If previously coated with cement-base waterproofing paints, clean by sandblasting. Glossy surfaces must be dulled. Un-weathered areas such as eaves, ceilings, and overhangs should be washed with a detergent solution and/or rinsed with a strong stream of water from a garden hose to remove contaminants that can interfere with proper adhesion. Stains from mildew must be removed by cleaning with an anti-mildew wash prior to coating the surface. **Caution:** Refer to the anti-mildew wash technical data and material safety data sheet for instructions on its proper use and handling. For metal surfaces, remove rust. Wipe down with paint thinner to remove surface oils.

All new masonry surfaces must be power washed or brushed thoroughly with stiff fiber bristles to remove loose particles. New masonry substrates must be allowed to cure for 30 days before priming or painting.

Primers: New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARRANTY: Manufacturer warrants that this product when used in accordance with the label instructions will not: 1. blister from properly prepared and primed surfaces, 2. peel from properly prepared and primed surfaces, and 3. wear down or weather to expose the previously painted surface. This warranty shall be effective for 15 years and is made to the original residential consumer paint purchaser. This warranty is non-transferable. If this product fails to perform as explained above when used according to label instructions within the warranty period, Manufacturer will, upon presentation of proof of purchase (original sales receipt), provide an equivalent or comparable product at no charge. Since we have no control over surface preparation or application, THIS LIMITED WARRANTY DOES NOT INCLUDE THE COST OF LABOR FOR APPLICATION OF PAINT. MANUFACTURER SHALL IN NO EVENT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. SOME STATES DO NOT ALLOW THE EXCLUSION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE LIMITATIONS OR EXCLUSIONS CONTAINED IN THE ABOVE WARRANTY MAY NOT APPLY TO YOU. This warranty gives you specific legal rights; you may also have other rights which vary state to state.

Application

Stir thoroughly. Apply by brush (synthetic filament), roller or spray. Length of roller nap depends upon the texture of the surface. Thinning is not usually required for brush or roller application. Apply a full, even coat. Do not apply directly over chalky surfaces or bleeding stains. Apply only when surface and air temperatures are above 50°F (10°C).

Spray, Airless: Fluid Pressure—1,500 to 2,000 PSI;
Tip—.015 - .019 Orifice

Clean Up

Clean up with warm, soapy water.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

Environmental Health & Safety Information

WARNING!

Possible birth defect hazard. Contains, **Carbamic acid, 1H-benzimidazol-2-yl-, methyl ester**, which may cause birth defects based on animal data.

Use only with adequate ventilation. Do not breathe vapors, spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.



WARNING: Cancer and Reproductive Harm—
www.P65warnings.ca.gov

WARNING: This product contains isothiazolinone compounds at levels of <0.1%. These substances are biocides commonly found in most paints and a variety of personal care products as a preservative. Certain individuals may be sensitive or allergic to these substances, even at low levels.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under “Clean Up”.

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**