



# CORONADO GOLD®

## INTERIOR ACRYLIC PAINT & PRIMER

### SEMI-GLOSS 822

#### Features

- Easy application
- Paint and primer together\*
- Low odor
- Vinyl acrylic formula
- Under 50 g/l VOC
- Available in thousands of colors
- Suitable for use in USDA inspected facilities

\* self-priming on previously painted substrates in good condition.

#### Recommended For

Ideal for wood trim, cabinets, doors and walls throughout residential or commercial structures. Its durability lends itself to use in kitchens, bathrooms, laundries, family rooms, bedrooms, common areas, etc.

#### General Description

Coronado Gold® Interior Acrylic Paint & Primer is a quality, low VOC acrylic paint engineered to provide excellent color retention and washability. It is easy to apply, dries to a smooth professional finish and offers quality performance and exceptional value.

#### Limitations

- Do not paint when temperature of air and surface is below 50°F (10°C).

#### Product Information

Colors — Standard:	Technical Data◇	Base 1				
White (01)	Vehicle Type	Proprietary Acrylic Latex				
	Pigment Type	Titanium Dioxide				
	Volume Solids	36%				
<b>— Tint Bases:</b>	Coverage per Gallon at Recommended Film Thickness	400 – 450 Sq. Ft.				
Base 1X. Tint Bases <b>only</b> with Gennex® Waterborne Colorant.	Recommended Film Thickness	<table border="0"> <tr> <td>– Wet</td> <td>3.6 - 4.0 mils</td> </tr> <tr> <td>– Dry</td> <td>1.3 - 1.4 mils</td> </tr> </table>	– Wet	3.6 - 4.0 mils	– Dry	1.3 - 1.4 mils
– Wet	3.6 - 4.0 mils					
– Dry	1.3 - 1.4 mils					
<b>— Special Colors:</b>	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint					
Contact your dealer.	Dry Time @ 77°F (25°C) @ 50% RH	<table border="0"> <tr> <td>– To Touch</td> <td>1 Hour</td> </tr> <tr> <td>– To Recoat</td> <td>2 Hours</td> </tr> </table>	– To Touch	1 Hour	– To Recoat	2 Hours
– To Touch	1 Hour					
– To Recoat	2 Hours					
<b>Certification:</b>	Painted surfaces can be washed after two weeks. High humidity and cool temperatures will result in longer dry, recoat and service times					
<b>VOC compliant in all regulated areas.</b>	Dries By	Evaporation, Coalescence				
This product meets the qualifications for LEED [Leadership in Energy and Environmental Design] projects as a non-flat coating	Viscosity	92 ± 3 KU				
	Flash Point	None				
	Gloss / Sheen	Semi-Gloss (35-55 @ 60°)				
	Surface Temperature at Application	<table border="0"> <tr> <td>– Min.</td> <td>50°F</td> </tr> <tr> <td>– Max.</td> <td>90°F</td> </tr> </table>	– Min.	50°F	– Max.	90°F
– Min.	50°F					
– Max.	90°F					
	Thin With	Clean Water				
	Clean Up Thinner	Clean Water				
	Weight Per Gallon	10.6 lbs				
<b>Technical Assistance:</b>	Storage Temperature	<table border="0"> <tr> <td>– Min.</td> <td>40°F</td> </tr> <tr> <td>– Max.</td> <td>90°F</td> </tr> </table>	– Min.	40°F	– Max.	90°F
– Min.	40°F					
– Max.	90°F					
Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-225-5554 or visit <a href="http://www.coronadopaint.com">www.coronadopaint.com</a> .	<b>Volatile Organic Compounds (VOC)</b>					
	50 Grams / Liter	0.42 Lbs. / Gallon				

◇ Reported values are for Base 1. Contact dealer for values of other bases or colors.

## Coronado Gold® Interior Acrylic Paint & Primer Semi-Gloss Finish 822

### Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure (30 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure.

**Primers:** New surfaces should be fully primed. Previously painted surfaces should be primed or spot primed as necessary. There are a number of specialty primers available in our family of brands that can be used on difficult substrates such as bleeding woods, hard glossy surfaces, or other substrates where paint adhesion or stain blocking is a problem. Your dealer can recommend the right problem solving primer necessary to meet your needs.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### Application

Stir thoroughly before use. Apply one or two coats. For best results, use a Professional custom-blended nylon/polyester brush, Professional roller, or a similar product. This product can also be sprayed. Two coats provide maximum hiding and film durability.

**Spray, Airless:** Fluid Pressure —1,500 to 3,000 PSI;  
Tip — .011 – .015 Orifice.

### Thinning/Clean up

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents.

**Clean up:** Wash brushes, rollers, and other painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency on disposal options.**

### Environmental Health & Safety Information

**Use only with adequate ventilation.** Do not breathe spray mist or sanding dust. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to dust and spray mist by wearing a NIOSH approved respirator during application, sanding and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

**WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

**FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**IN CASE OF SPILL** – Absorb with inert material and dispose of as specified under "Clean Up".

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for additional  
health and safety information.**