



# RUST PREVENTATIVE ALKYD AEROSOL FLAT AC13

## Features

- Superior rust protection
- Durable, Long Lasting
- Resistant to Wear, Weathering & Fading

## General Description

Superior interior/exterior rust preventative satin enamel paint and primer in one. Direct to metal, spray at any angle, comfort spray tip.

## Recommended For

Interior and exterior metal surfaces. Also for wood, and handcrafts.

## Limitations

- Do not use on Styrofoam , ceramic tiles or marble

## Product Information

<b>Colors — Standard:</b> White and Black	<b>Technical Data</b> <span style="float: right;"><b>Black</b></span>																										
<b>— Tint Bases:</b> N/A	<table border="1"> <tr> <td>Vehicle Type</td> <td>Medium Oil Alkyd</td> </tr> <tr> <td>Pigment Type</td> <td>Black</td> </tr> <tr> <td>Weight Solids</td> <td>16.777 ± 1.0%</td> </tr> <tr> <td>Coverage in can</td> <td>Approx. 7 - 9 sq. ft.</td> </tr> <tr> <td>Recommended Film Thickness</td> <td> <table border="1"> <tr> <td>– Wet</td> <td>2.5 to 4.0 mils</td> </tr> <tr> <td>– Dry</td> <td>1.5 to 2.5 mils</td> </tr> </table> </td> </tr> </table>	Vehicle Type	Medium Oil Alkyd	Pigment Type	Black	Weight Solids	16.777 ± 1.0%	Coverage in can	Approx. 7 - 9 sq. ft.	Recommended Film Thickness	<table border="1"> <tr> <td>– Wet</td> <td>2.5 to 4.0 mils</td> </tr> <tr> <td>– Dry</td> <td>1.5 to 2.5 mils</td> </tr> </table>	– Wet	2.5 to 4.0 mils	– Dry	1.5 to 2.5 mils												
Vehicle Type	Medium Oil Alkyd																										
Pigment Type	Black																										
Weight Solids	16.777 ± 1.0%																										
Coverage in can	Approx. 7 - 9 sq. ft.																										
Recommended Film Thickness	<table border="1"> <tr> <td>– Wet</td> <td>2.5 to 4.0 mils</td> </tr> <tr> <td>– Dry</td> <td>1.5 to 2.5 mils</td> </tr> </table>	– Wet	2.5 to 4.0 mils	– Dry	1.5 to 2.5 mils																						
– Wet	2.5 to 4.0 mils																										
– Dry	1.5 to 2.5 mils																										
<b>— Special Colors:</b> Contact your dealer.	<p>Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure color uniformity and minimize the disposal of excess paint.</p> <table border="1"> <tr> <td>Dry Time @ 77°F (25°C) @ 50% RH</td> <td> <table border="1"> <tr> <td>– Tack Free</td> <td>1 – 2 Hours</td> </tr> <tr> <td>– To Recoat</td> <td>within 1 Hour</td> </tr> <tr> <td>– To Cure</td> <td>3 -5 Day</td> </tr> </table> </td> </tr> </table>	Dry Time @ 77°F (25°C) @ 50% RH	<table border="1"> <tr> <td>– Tack Free</td> <td>1 – 2 Hours</td> </tr> <tr> <td>– To Recoat</td> <td>within 1 Hour</td> </tr> <tr> <td>– To Cure</td> <td>3 -5 Day</td> </tr> </table>	– Tack Free	1 – 2 Hours	– To Recoat	within 1 Hour	– To Cure	3 -5 Day																		
Dry Time @ 77°F (25°C) @ 50% RH	<table border="1"> <tr> <td>– Tack Free</td> <td>1 – 2 Hours</td> </tr> <tr> <td>– To Recoat</td> <td>within 1 Hour</td> </tr> <tr> <td>– To Cure</td> <td>3 -5 Day</td> </tr> </table>	– Tack Free	1 – 2 Hours	– To Recoat	within 1 Hour	– To Cure	3 -5 Day																				
– Tack Free	1 – 2 Hours																										
– To Recoat	within 1 Hour																										
– To Cure	3 -5 Day																										
<b>Certification:</b>  Aerosol Coating Category: Flat Coating Max VOC 60% Max EPA PWR 1.20 Max CA PWMIR 0.80	<p>High humidity and cool temperatures will result in longer dry, recoat and service times.</p> <table border="1"> <tr> <td>Dries By</td> <td>Evaporation &amp; Oxidation</td> </tr> <tr> <td>Spray Rate</td> <td>1.5 grams to 3.0 grams / second</td> </tr> <tr> <td>Flash Point</td> <td>-139° F (-95° C)</td> </tr> <tr> <td>Gloss / Sheen</td> <td>Flat</td> </tr> <tr> <td>Surface Temperature at Application</td> <td> <table border="1"> <tr> <td>– Min.</td> <td>50°F</td> </tr> <tr> <td>– Max.</td> <td>90°F</td> </tr> </table> </td> </tr> <tr> <td>Thin With</td> <td>N/A</td> </tr> <tr> <td>Clean Spray Tip with</td> <td>Mineral Spirit, Toluol</td> </tr> <tr> <td>Fill ounces</td> <td>12 oz.</td> </tr> <tr> <td>Storage Temperature</td> <td> <table border="1"> <tr> <td>– Min.</td> <td>0°F</td> </tr> <tr> <td>– Max.</td> <td>120°F</td> </tr> </table> </td> </tr> </table>	Dries By	Evaporation & Oxidation	Spray Rate	1.5 grams to 3.0 grams / second	Flash Point	-139° F (-95° C)	Gloss / Sheen	Flat	Surface Temperature at Application	<table border="1"> <tr> <td>– Min.</td> <td>50°F</td> </tr> <tr> <td>– Max.</td> <td>90°F</td> </tr> </table>	– Min.	50°F	– Max.	90°F	Thin With	N/A	Clean Spray Tip with	Mineral Spirit, Toluol	Fill ounces	12 oz.	Storage Temperature	<table border="1"> <tr> <td>– Min.</td> <td>0°F</td> </tr> <tr> <td>– Max.</td> <td>120°F</td> </tr> </table>	– Min.	0°F	– Max.	120°F
Dries By	Evaporation & Oxidation																										
Spray Rate	1.5 grams to 3.0 grams / second																										
Flash Point	-139° F (-95° C)																										
Gloss / Sheen	Flat																										
Surface Temperature at Application	<table border="1"> <tr> <td>– Min.</td> <td>50°F</td> </tr> <tr> <td>– Max.</td> <td>90°F</td> </tr> </table>	– Min.	50°F	– Max.	90°F																						
– Min.	50°F																										
– Max.	90°F																										
Thin With	N/A																										
Clean Spray Tip with	Mineral Spirit, Toluol																										
Fill ounces	12 oz.																										
Storage Temperature	<table border="1"> <tr> <td>– Min.</td> <td>0°F</td> </tr> <tr> <td>– Max.</td> <td>120°F</td> </tr> </table>	– Min.	0°F	– Max.	120°F																						
– Min.	0°F																										
– Max.	120°F																										
<b>Technical Assistance:</b>  Available through your local authorized independent Insl-x dealer. For the location of the dealer nearest you, call 1-800-225-5554 or visit <a href="http://www.insl-x.com">www.insl-x.com</a> .	<p style="text-align: center;"><b>Volatile Organic Compounds (VOC)</b></p> <p style="text-align: center;">MAX 60%</p>																										

◇ Reported values are for Black. Contact dealer for values of other colors.

## Rust Preventative Alkyd Aerosol Flat AC13

### Surface Preparation

Surface to be painted must be clean and free of dirt, chalk, wax, grease, rust or loose, flaking paint. Dirt and chalk should be removed by scrubbing with warm soapy water and thoroughly rinsed with clean water. Wax should be removed with a commercial wax stripper or by solvent cleaning. Grease should be cleaned by using an oil and grease emulsifier or other surface prep degreaser. Rust must be removed by hand sanding vigorously or by conscientious power tool cleaning. Remove loose paint by scraping. Feather sand rough edges to insure a smooth finish coat. Remove sanding dust before paint application.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### Application

Before spraying, shake can for 2 minutes after ball within begins to rattle and occasionally during use. Hold can 10" to 16" away from the surface and apply several thin coats a few minutes apart rather than one heavy coat, slightly overlapping each stroke. Keep can in motion while spraying Recoat within one hour.

### Clean Up

USE COMPLETELY OR DISPOSE OF PROPERLY. This product contains organic solvents which may cause adverse effects to the environment if handled improperly. Emptied containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition. Disposal of wastes containing either organic solvents or free-liquids in landfills is prohibited. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for local disposal options.**

### Environmental Health & Safety Information

#### DANGER!

**EXTREMELY FLAMMABLE LIQUID AND VAPOR.**

**VAPORS MAY CAUSE FLASH FIRE.**

**CONTENTS UNDER PRESSURE.**

#### Contains: acetone, propane, butane, petroleum distillates

Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes irritation to eyes, skin and respiratory tract. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120 °F.

**NOTICE:** Repeated or prolonged exposure to organic solvents may lead to permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Vapors may ignite explosively. Keep away from heat, sparks and flame. Turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

**Use only with adequate ventilation.** Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. To avoid breathing vapors or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor levels are above the applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

**WARNING:** This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

**FIRST AID:** If affected by inhalation of vapors or spray mist, remove to fresh air. In case of eye contact, immediately flush with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If swallowed, do not induce vomiting. Get medical attention immediately.

**IN CASE OF FIRE** – Use foam, CO<sub>2</sub>, dry chemical or water fog.

**IN CASE OF SPILL** – Absorb with inert material and dispose of as specified under "Clean Up".

### KEEP OUT OF REACH OF CHILDREN

**Refer to Safety Data Sheet for additional health and safety information.**