



# COLOUR-CHANGING CEILING PAINT

## PC-1200

### Features

- Spatter resistant
- Self-Priming
- Disappearing pink colour-change technology
- For smooth or textured ceilings
- Easy clean-up

### General Description

Colour-Changing Ceiling Paint is applied as a light pink colour to indicate painted areas for preventing missed spots. It dries to a uniform, white finish in a flat sheen that helps minimize the appearance of surface imperfections.

### Recommended For

For new or previously painted wallboard, acoustical ceiling tile cured masonry, plaster, and other ceiling substrates.

### Limitations

- Apply when surface and ambient temperature is above 10 °C (50 °F) and below 32 °C (90 °F).
- Not for high traffic areas or surfaces that require frequent cleaning

### Product Information

Colours — Standard:	Technical Data◇	White
White	Vehicle Type	Acrylic
	Pigment Type	Titanium Dioxide
	Volume Solids	28 ± 1.0%
	Coverage per Gallon at	27.8 – 37.1 sq. m.
	Recommended Film Thickness	(300 – 400 sq. ft.)
	Recommended Film Thickness	– Wet 3.9 – 4.6 mils
		– Dry 1.1 – 1.3 mils
	Depending on surface texture and porosity. Be sure to estimate the right amount of paint for the job. This will ensure colour uniformity and minimize the disposal of excess paint.	
	Dry Time @ 25 °C (77 °F) @ 50% RH	– Tack Free 1 Hour – To Recoat 2 Hours
	High humidity and cool temperatures will result in longer dry, recoat and service times.	
	Dries By	Coalescence
	Viscosity	99 – 103 KU
	Flash Point	None
	Gloss / Sheen	Flat (2 – 5 @ 85°)
	Surface Temperature at Application	– Min. 10 °C (50 °F) – Max. 32.2 °C (90 °F)
	Thin With	Do not Thin
	Clean Up Thinner	Warm Soapy Water
	Weight Per Gallon	5.1 kg (11.2 lbs.)
	Storage Temperature	– Min. 4.4 °C (40 °F) – Max. 32.2 °C (90 °F)
	<b>Volatile Organic Compounds (VOC)</b>	
	47.8 Grams/Liter	
<b>Colours — Standard:</b> White		
<b>— Tint Bases:</b> N/A		
<b>— Special Colours:</b> Contact your retailer		
<b>Certifications &amp; Qualifications:</b> VOC compliant in all regulated areas		
<b>Technical Assistance:</b> Available through your local authorized independent dealer. For the location of the dealer nearest you, call 1-800-361-5898 or visit <a href="http://www.insl-x.ca">www.insl-x.ca</a>		

◇ Reported values are for White.

## Colour-Changing Ceiling Paint PC-1200

### Surface Preparation

Surfaces to be painted must be clean, dry, and free of dirt, dust, grease, oil, soap, wax, scaling paint, water soluble materials, and mildew. Remove any peeling or scaling paint and sand these areas to feather edges smooth with adjacent surfaces. Glossy areas should be dulled. Drywall surfaces must be free of sanding dust.

New plaster or masonry surfaces must be allowed to cure before applying base coat. Cured plaster should be hard, have a slight sheen and maximum PH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles before priming. Wood substrates must be thoroughly dry. Caution: Smooth planed clapboards or siding must be sanded thoroughly to break the "mill glaze" allowing proper penetration and adhesion.

**Difficult Substrates:** Insl-x offers a number of specialty primers for use over difficult substrates such as stains, grease, crayon markings, hard glossy surfaces, galvanized metal, or other substrates where paint adhesion or stain suppression is a particular problem.

### Application

Colour-Changing Ceiling Paint applies easily with a quality brush, roller, airless, HVLP or conventional spray methods. Apply paint generously from unpainted area into wet area. Stir product thoroughly before using. When applying by brush, apply a smooth and generous coat application in an "M" or criss-cross motion avoiding any excessive re-spreading or reworking. If applying by airless sprayer, it is recommended to use a unit with a minimum of 1500 PSI of pressure with a 0.013 – 0.017 fluid spray tip. It is important to maintain a wet edge during all methods of paint application by brushing or rolling into previously applied coating area. Apply when surface and ambient temperature are above 10 °C (50 °F) and below 32.2 °C (90 °F).

### Clean Up

Remove all spatters immediately with soap and water. Wash all equipment with soap and water immediately after use.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ <https://www.canada.ca/en/health-canada/services/environmental-workplace-health/environmental-contaminants/lead/lead-information-package-some-commonly-asked-questions-about-lead-human-health.html>

### Environmental Health & Safety Information

May cause allergic skin reaction.

Do not get on skin or clothing.

**Use only in a well ventilated area.** Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with local regulations. Wash thoroughly after handling.

**KEEP OUT OF REACH OF CHILDREN  
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for  
additional health and safety information.**