



URETHANE REDUCER V700

Features

- For use with all two-part solvent-based urethane coatings
- Effectively cleans tools and equipment
- May be used to reduce and thin coatings up to the legal limits allowed by district

General Description

Urethane Reducer is 100% butyl acetate for use in thinning catalyzed acrylic urethanes. Effective for cleaning equipment immediately after use as well. Do not use this product for cleaning synthetic brushes or rollers, as it will dissolve them.

Recommended For

Corotech® Urethane Reducer is 100% butyl acetate for use in thinning catalyzed acrylic urethanes. Use for clean-up of equipment immediately after use.

Limitations

- Do not use this product for cleaning synthetic brushes or rollers as it will dissolve them.

Product Information

Colors — Standard:

N/A

— Tint Bases:

N/A

— Special Colors:

N/A

Certification & Qualifications:

The product supported by this data sheet is regulated by consumer product VOC rules, in some areas, as a paint thinner, multi-purpose solvent.

It also does not apply to LEED (Leadership in Energy and Environmental Design) standards.

VOC REGION	COMPLIANT
FEDERAL	YES
OTC	NO
OTCII	NO
CARB	NO
CARB07	NO
UTAH	NO
AZMC	NO
SCAQMD	NO

Technical Assistance:

Available through your local authorized independent Benjamin Moore retailer. For the location of the retailer nearest you, call 1-866-708-9180 or visit www.benjaminmoore.com

Technical Data

Urethane Reducer

Vehicle Type	100% Butyl Acetate	
Pigment Type	N/A	
Volume Solids	N/A	
Coverage per Gallon at Recommended Film Thickness	N/A	
Recommended Film Thickness	– Wet	N/A
	– Dry	N/A
Dry Time @ 77°F (25°C) @ 50% RH	– Tack Free	N/A
	– To Recoat	N/A
Dries By	N/A	
Dry Heat Resistance	N/A	
Viscosity	N/A	
Flash Point	81 °F (TT-P-141, Method 4293)	
Gloss / Sheen	N/A	
Surface Temperature at Application	– Min.	N/A
	– Max	N/A
Thin With	N/A	
Clean Up Thinner	N/A	
Weight Per Gallon		
Storage Temperature	– Min.	40 °F (4.4 °C)
	– Max	95 °F (35 °C)

Volatile Organic Compounds (VOC)

880 g/L 7.35 Lbs./Gallon

Urethane Reducer V700

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Informational Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Application

Corotech® Urethane Reducer is 100% Butyl Acetate for use in thinning catalyzed acrylic urethanes. Use for clean-up of equipment immediately after use. Do not use this product for cleaning synthetic brushes or rollers as it will dissolve them.

Environmental Health & Safety Information

WARNING!

May cause drowsiness or dizziness

Flammable liquid and vapor

Prevention: Avoid breathing dust /fume /mist /vapors /spray. Use only outdoors or in a well-ventilated area. Keep away from heat /sparks /open flames /hot surfaces, No smoking. Keep container tightly closed. Ground /bond container and receiving equipment. Use explosion-proof electrical /ventilating /lighting /equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves /protective clothing /eye protection /face protection. Keep cool.

Response: If on skin (or hair), take off immediately all contaminated clothing. Rinse skin with water. If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. In case of fire, use CO2, dry chemical, or foam for extinction.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents /container to an approved waste disposal plant.



WARNING Cancer and Reproductive Harm—
www.P65warnings.ca.gov

**KEEP OUT OF REACH OF CHILDREN
PROTECT FROM FREEZING**

**Refer to Safety Data Sheet for
additional health and safety information.**