



# BRUSHING REDUCER V701

## Features

- For use with all alkyd and oil-modified polyurethane coatings
- Effectively cleans tools and equipment
- May be used to reduce and thin coatings up to the legal limits allowed by district

## General Description

Brushing Reducer is a blend of High Flash Naphtha and Mineral Spirits. Use this solvent to improve the brushing characteristics of single-component, solvent-based coatings.

## Recommended For

For use with all alkyd and oil modified polyurethane coatings. For effective cleaning of tools and equipment. May be used to reduce and thin coatings up to the legal limits allowed by district

## Limitations

- Do not use for thinning 2-component urethanes.
- For Industrial Use Only

## Product Information

Product Information																																																					
<b>Colours — Standard:</b> N/A	<table border="1"> <thead> <tr> <th>Technical Data</th> <th>Brushing Reducer</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td>N/A</td> </tr> <tr> <td>Pigment Type</td> <td>N/A</td> </tr> <tr> <td>Volume Solids</td> <td>N/A</td> </tr> <tr> <td>Coverage per 3.79 L at Recommended Film Thickness</td> <td>N/A</td> </tr> <tr> <td>Recommended Film Thickness</td> <td> <table border="1"> <tr> <td>– Wet</td> <td>N/A</td> </tr> <tr> <td>– Dry</td> <td>N/A</td> </tr> </table> </td> </tr> <tr> <td>Dry Time @ 25 °C (77 °F) @ 50% RH</td> <td> <table border="1"> <tr> <td>– Tack Free</td> <td>N/A</td> </tr> <tr> <td>– To Recoat</td> <td>N/A</td> </tr> </table> </td> </tr> <tr> <td>Dries By</td> <td>N/A</td> </tr> <tr> <td>Viscosity</td> <td>N/A</td> </tr> <tr> <td>Flash Point</td> <td>40 °C (104 °F) (TT-P-141, Method 4293)</td> </tr> <tr> <td>Gloss / Sheen</td> <td>N/A</td> </tr> <tr> <td>Surface Temperature at Application</td> <td> <table border="1"> <tr> <td>– Min.</td> <td>N/A</td> </tr> <tr> <td>– Max.</td> <td>N/A</td> </tr> </table> </td> </tr> <tr> <td>Thin With</td> <td>N/A</td> </tr> <tr> <td>Clean Up Thinner</td> <td>N/A</td> </tr> <tr> <td>Weight Per 3.79 L</td> <td>3 kg (6.6 lbs)</td> </tr> <tr> <td>Storage Temperature</td> <td> <table border="1"> <tr> <td>– Min.</td> <td>4.4 °C (40 °F)</td> </tr> <tr> <td>– Max.</td> <td>35 °C (95 °F)</td> </tr> </table> </td> </tr> <tr> <td colspan="2" style="text-align: center;"><b>Volatile Organic Compounds (VOC)</b></td> </tr> <tr> <td colspan="2" style="text-align: center;">787 Grams/Litre</td> </tr> </tbody> </table>	Technical Data	Brushing Reducer	Vehicle Type	N/A	Pigment Type	N/A	Volume Solids	N/A	Coverage per 3.79 L at Recommended Film Thickness	N/A	Recommended Film Thickness	<table border="1"> <tr> <td>– Wet</td> <td>N/A</td> </tr> <tr> <td>– Dry</td> <td>N/A</td> </tr> </table>	– Wet	N/A	– Dry	N/A	Dry Time @ 25 °C (77 °F) @ 50% RH	<table border="1"> <tr> <td>– Tack Free</td> <td>N/A</td> </tr> <tr> <td>– To Recoat</td> <td>N/A</td> </tr> </table>	– Tack Free	N/A	– To Recoat	N/A	Dries By	N/A	Viscosity	N/A	Flash Point	40 °C (104 °F) (TT-P-141, Method 4293)	Gloss / Sheen	N/A	Surface Temperature at Application	<table border="1"> <tr> <td>– Min.</td> <td>N/A</td> </tr> <tr> <td>– Max.</td> <td>N/A</td> </tr> </table>	– Min.	N/A	– Max.	N/A	Thin With	N/A	Clean Up Thinner	N/A	Weight Per 3.79 L	3 kg (6.6 lbs)	Storage Temperature	<table border="1"> <tr> <td>– Min.</td> <td>4.4 °C (40 °F)</td> </tr> <tr> <td>– Max.</td> <td>35 °C (95 °F)</td> </tr> </table>	– Min.	4.4 °C (40 °F)	– Max.	35 °C (95 °F)	<b>Volatile Organic Compounds (VOC)</b>		787 Grams/Litre	
Technical Data	Brushing Reducer																																																				
Vehicle Type	N/A																																																				
Pigment Type	N/A																																																				
Volume Solids	N/A																																																				
Coverage per 3.79 L at Recommended Film Thickness	N/A																																																				
Recommended Film Thickness	<table border="1"> <tr> <td>– Wet</td> <td>N/A</td> </tr> <tr> <td>– Dry</td> <td>N/A</td> </tr> </table>	– Wet	N/A	– Dry	N/A																																																
– Wet	N/A																																																				
– Dry	N/A																																																				
Dry Time @ 25 °C (77 °F) @ 50% RH	<table border="1"> <tr> <td>– Tack Free</td> <td>N/A</td> </tr> <tr> <td>– To Recoat</td> <td>N/A</td> </tr> </table>	– Tack Free	N/A	– To Recoat	N/A																																																
– Tack Free	N/A																																																				
– To Recoat	N/A																																																				
Dries By	N/A																																																				
Viscosity	N/A																																																				
Flash Point	40 °C (104 °F) (TT-P-141, Method 4293)																																																				
Gloss / Sheen	N/A																																																				
Surface Temperature at Application	<table border="1"> <tr> <td>– Min.</td> <td>N/A</td> </tr> <tr> <td>– Max.</td> <td>N/A</td> </tr> </table>	– Min.	N/A	– Max.	N/A																																																
– Min.	N/A																																																				
– Max.	N/A																																																				
Thin With	N/A																																																				
Clean Up Thinner	N/A																																																				
Weight Per 3.79 L	3 kg (6.6 lbs)																																																				
Storage Temperature	<table border="1"> <tr> <td>– Min.</td> <td>4.4 °C (40 °F)</td> </tr> <tr> <td>– Max.</td> <td>35 °C (95 °F)</td> </tr> </table>	– Min.	4.4 °C (40 °F)	– Max.	35 °C (95 °F)																																																
– Min.	4.4 °C (40 °F)																																																				
– Max.	35 °C (95 °F)																																																				
<b>Volatile Organic Compounds (VOC)</b>																																																					
787 Grams/Litre																																																					
<b>— Tint Bases:</b> N/A																																																					
<b>— Special Colours:</b> N/A																																																					
<b>Certification:</b>  The product supported by this data sheet is regulated by consumer product VOC rules, in some areas, as a paint thinner, multi-purpose solvent.  This product is exempt under the Ozone Transport Commission regulations.  It also does not apply to LEED (Leadership in Energy and Environmental Design) standards.																																																					
<b>Technical Assistance:</b> Available through your local authorized independent Benjamin Moore® retailer. For the location of the retailer nearest you, call 1-877-711-6830, or visit <a href="http://www.benjaminmoore.ca">www.benjaminmoore.ca</a>																																																					

## Brushing Reducer V701

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ [http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked\\_questions\\_questions\\_posees-eng.php](http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions_questions_posees-eng.php)

### Application

Corotech® Brushing Reducer is a blend of Mineral Spirits and High Flash Naphtha. Use this solvent to improve the brushing characteristics of solvent-based coatings.

## Environmental Health & Safety Information

### Danger

**Causes skin irritation**

**Causes serious eye irritation**

**May cause damage to organs**

**Causes damage to organs through prolonged or repeated exposure**

**May be fatal if swallowed and enters airways**

**Flammable liquid and vapour**

**Prevention:** Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/mist/vapours/spray. Do not eat, drink or smoke when using this product. Keep away from heat/sparks/open flames/hot surfaces, no smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical /ventilating /lighting /equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

**Response:** If exposed or if you feel unwell call a POISON CENTER or physician.

If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical attention. If skin irritation occurs get medical attention. If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. If swallowed immediately call a POISON CENTER or physician. Do NOT induce vomiting. In case of fire use CO<sub>2</sub>, dry chemical, or foam for extinction.

**Storage:** Store locked up. Store in a well-ventilated place. Keep cool.

**Disposal:** Dispose of contents/container to an approved waste disposal plant.

**KEEP OUT OF REACH OF CHILDREN  
FOR INDUSTRIAL USE ONLY**

**Refer to Safety Data Sheet for  
additional health and safety information.**