



XYLENE V703

Features

- Xylene

General Description

Xylene is an aromatic solvent that can be used in numerous industrial coatings systems as a general thinner and clean-up solvent. Use to modify evaporation rates and improve dry. For effective cleaning of tools and equipment.

Recommended For

Use to modify evaporation rates and modify dry. For effective cleaning of tools and equipment. May be used to reduce and thin coatings up to the legal limits allowed by local regulations.

Limitations

Product Information																																																																		
<p>Colours — Standard: N/A</p>	<table border="1"> <thead> <tr> <th colspan="2">Technical Data</th> <th>Xylene</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td></td> <td>Xylene</td> </tr> <tr> <td>Pigment Type</td> <td></td> <td>N/A</td> </tr> <tr> <td>Volume Solids</td> <td></td> <td>N/A</td> </tr> <tr> <td>Coverage per 3.79 L at Recommended Film Thickness</td> <td></td> <td>N/A</td> </tr> <tr> <td rowspan="2">Recommended Film Thickness</td> <td>– Wet</td> <td>N/A</td> </tr> <tr> <td>– Dry</td> <td>N/A</td> </tr> <tr> <td></td> <td></td> <td>N/A</td> </tr> <tr> <td rowspan="2">Dry Time @ 25 °C (77 °F) @ 50% RH</td> <td>– Tack Free</td> <td>N/A</td> </tr> <tr> <td>– To Recoat</td> <td>N/A</td> </tr> <tr> <td>Dries By</td> <td></td> <td>N/A</td> </tr> <tr> <td>Viscosity</td> <td></td> <td>N/A</td> </tr> <tr> <td>Flash Point</td> <td></td> <td>26.7 °C (80 °F) (TT-P-141, Method 4293)</td> </tr> <tr> <td>Gloss / Sheen</td> <td></td> <td>N/A</td> </tr> <tr> <td rowspan="2">Surface Temperature at Application</td> <td>– Min.</td> <td>N/A</td> </tr> <tr> <td>– Max.</td> <td>N/A</td> </tr> <tr> <td>Thin With</td> <td></td> <td>N/A</td> </tr> <tr> <td>Clean Up Thinner</td> <td></td> <td>N/A</td> </tr> <tr> <td>Weight Per 3.79 L</td> <td></td> <td>3.3 kg (7.3 lbs)</td> </tr> <tr> <td rowspan="2">Storage Temperature</td> <td>– Min.</td> <td>7.2 °C (45 °F)</td> </tr> <tr> <td>– Max.</td> <td>35 °C (95 °F)</td> </tr> <tr> <td colspan="3" style="text-align: center;">Volatile Organic Compounds (VOC)</td> </tr> <tr> <td colspan="3" style="text-align: center;">868 Grams/Litre</td> </tr> </tbody> </table>	Technical Data		Xylene	Vehicle Type		Xylene	Pigment Type		N/A	Volume Solids		N/A	Coverage per 3.79 L at Recommended Film Thickness		N/A	Recommended Film Thickness	– Wet	N/A	– Dry	N/A			N/A	Dry Time @ 25 °C (77 °F) @ 50% RH	– Tack Free	N/A	– To Recoat	N/A	Dries By		N/A	Viscosity		N/A	Flash Point		26.7 °C (80 °F) (TT-P-141, Method 4293)	Gloss / Sheen		N/A	Surface Temperature at Application	– Min.	N/A	– Max.	N/A	Thin With		N/A	Clean Up Thinner		N/A	Weight Per 3.79 L		3.3 kg (7.3 lbs)	Storage Temperature	– Min.	7.2 °C (45 °F)	– Max.	35 °C (95 °F)	Volatile Organic Compounds (VOC)			868 Grams/Litre		
Technical Data		Xylene																																																																
Vehicle Type		Xylene																																																																
Pigment Type		N/A																																																																
Volume Solids		N/A																																																																
Coverage per 3.79 L at Recommended Film Thickness		N/A																																																																
Recommended Film Thickness	– Wet	N/A																																																																
	– Dry	N/A																																																																
		N/A																																																																
Dry Time @ 25 °C (77 °F) @ 50% RH	– Tack Free	N/A																																																																
	– To Recoat	N/A																																																																
Dries By		N/A																																																																
Viscosity		N/A																																																																
Flash Point		26.7 °C (80 °F) (TT-P-141, Method 4293)																																																																
Gloss / Sheen		N/A																																																																
Surface Temperature at Application	– Min.	N/A																																																																
	– Max.	N/A																																																																
Thin With		N/A																																																																
Clean Up Thinner		N/A																																																																
Weight Per 3.79 L		3.3 kg (7.3 lbs)																																																																
Storage Temperature	– Min.	7.2 °C (45 °F)																																																																
	– Max.	35 °C (95 °F)																																																																
Volatile Organic Compounds (VOC)																																																																		
868 Grams/Litre																																																																		
<p>— Tint Bases: N/A</p>																																																																		
<p>— Special Colours: N/A</p>																																																																		
<p>Certification:</p> <p>The product supported by this data sheet is regulated by consumer product VOC rules, in some areas, as a paint thinner, multi-purpose solvent. This product is exempt under the Ozone Transport Commission regulations. It also does not apply to LEED (Leadership in Energy and Environmental Design) standards.</p>																																																																		
<p>Technical Assistance: Available through your local authorized independent Benjamin Moore® retailer. For the location of the retailer nearest you, call 1-877-711-6830, or visit www.benjaminmoore.ca</p>																																																																		

Xylene V703

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions_questions_posees-eng.php

Application

Corotech® Xylene is for use with all 2-part solvent-based epoxy and other high-performance coatings. Use to modify evaporation rates and modify dry. For effective cleaning of tools and equipment. May be used to reduce and thin coatings up to the legal limits allowed by local regulations.

Environmental, Health & Safety Information

Warning

Harmful in contact with skin

Harmful if inhaled

Causes skin irritation

Causes eye irritation

Suspected of causing cancer

May cause damage to organs

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable liquid and vapour

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. Do not breathe dust /fume /mist /vapours /spray. Do not eat, drink or smoke when using this product. Keep away from heat /sparks /open flames /hot surfaces, no smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Response: If exposed or concerned get medical attention.

If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical attention. Call a POISON CENTER or physician if you feel unwell. If skin irritation occurs get medical attention. If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. If inhaled remove victim to fresh air and keep at rest in a position comfortable for breathing. If swallowed immediately call a POISON CENTER or physician. Do NOT induce vomiting. In case of fire use CO₂, dry chemical, or foam for extinction.

Storage: Store locked up. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container to an approved waste disposal plant.

KEEP OUT OF REACH OF CHILDREN

Refer to Safety Data Sheet for additional health and safety information.