



EPOXY THINNER V704

Features

- For use with all 2-part solvent-based epoxy coatings
- For effective cleaning of tools and equipment
- May be used to reduce and thin coatings up to the legal limits allowed by district

Recommended For

For use with all 2-part solvent-based epoxy coatings. For effective cleaning of tools and equipment. May be used to reduce and thin coatings up to the legal limits allowed by district

General Description

Epoxy Thinner is a carefully balanced combination of the proper solvents for reducing catalyzed epoxy primers and finish coats.

Limitations

- Do not use for cleaning synthetic brushes or rollers as it will dissolve them.

Product Information																																					
<p>Colours — Standard: N/A</p> <p>— Tint Bases: N/A</p> <p>— Special Colours: N/A</p> <p>Certification:</p> <p>The product supported by this data sheet is regulated by consumer product VOC rules, in some areas, as a paint thinner, multi-purpose solvent.</p> <p>This product is exempt under the Ozone Transport Commission regulations.</p> <p>It also does not apply to LEED (Leadership in Energy and Environmental Design) standards.</p> <p>Technical Assistance: Available through your local authorized independent Benjamin Moore® retailer. For the location of the retailer nearest you, call 1-877-711-6830, or visit www.benjaminmoore.ca</p>	<table border="1"> <thead> <tr> <th>Technical Data</th> <th>Epoxy Thinner</th> </tr> </thead> <tbody> <tr> <td>Vehicle Type</td> <td>N/A</td> </tr> <tr> <td>Pigment Type</td> <td>N/A</td> </tr> <tr> <td>Volume Solids</td> <td>N/A</td> </tr> <tr> <td>Coverage per 3.79 L at Recommended Film Thickness</td> <td>N/A</td> </tr> <tr> <td>Recommended Film Thickness</td> <td>– Wet N/A – Dry N/A</td> </tr> <tr> <td>Dry Time @ 25 °C (77 °F) @ 50% RH</td> <td>– Tack Free N/A – To Recoat N/A</td> </tr> <tr> <td>Dries By</td> <td>N/A</td> </tr> <tr> <td>Viscosity</td> <td>N/A</td> </tr> <tr> <td>Flash Point</td> <td>–5 °C (23 °F) (TT-P-141, Method 4293)</td> </tr> <tr> <td>Gloss / Sheen</td> <td>N/A</td> </tr> <tr> <td>Surface Temperature at Application</td> <td>– Min. N/A – Max. N/A</td> </tr> <tr> <td>Thin With</td> <td>N/A</td> </tr> <tr> <td>Clean Up Thinner</td> <td>N/A</td> </tr> <tr> <td>Weight Per 3.79 L</td> <td>3.2 kg (6.95 lbs)</td> </tr> <tr> <td>Storage Temperature</td> <td>– Min. 4.4 °C (40 °F) – Max. 35 °C (95 °F)</td> </tr> <tr> <td colspan="2" style="text-align: center;">Volatile Organic Compounds (VOC)</td> </tr> <tr> <td colspan="2" style="text-align: center;">832 Grams/Litre</td> </tr> </tbody> </table>	Technical Data	Epoxy Thinner	Vehicle Type	N/A	Pigment Type	N/A	Volume Solids	N/A	Coverage per 3.79 L at Recommended Film Thickness	N/A	Recommended Film Thickness	– Wet N/A – Dry N/A	Dry Time @ 25 °C (77 °F) @ 50% RH	– Tack Free N/A – To Recoat N/A	Dries By	N/A	Viscosity	N/A	Flash Point	–5 °C (23 °F) (TT-P-141, Method 4293)	Gloss / Sheen	N/A	Surface Temperature at Application	– Min. N/A – Max. N/A	Thin With	N/A	Clean Up Thinner	N/A	Weight Per 3.79 L	3.2 kg (6.95 lbs)	Storage Temperature	– Min. 4.4 °C (40 °F) – Max. 35 °C (95 °F)	Volatile Organic Compounds (VOC)		832 Grams/Litre	
Technical Data	Epoxy Thinner																																				
Vehicle Type	N/A																																				
Pigment Type	N/A																																				
Volume Solids	N/A																																				
Coverage per 3.79 L at Recommended Film Thickness	N/A																																				
Recommended Film Thickness	– Wet N/A – Dry N/A																																				
Dry Time @ 25 °C (77 °F) @ 50% RH	– Tack Free N/A – To Recoat N/A																																				
Dries By	N/A																																				
Viscosity	N/A																																				
Flash Point	–5 °C (23 °F) (TT-P-141, Method 4293)																																				
Gloss / Sheen	N/A																																				
Surface Temperature at Application	– Min. N/A – Max. N/A																																				
Thin With	N/A																																				
Clean Up Thinner	N/A																																				
Weight Per 3.79 L	3.2 kg (6.95 lbs)																																				
Storage Temperature	– Min. 4.4 °C (40 °F) – Max. 35 °C (95 °F)																																				
Volatile Organic Compounds (VOC)																																					
832 Grams/Litre																																					

Epoxy Thinner V704

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by logging onto Health Canada @ http://www.hc-sc.gc.ca/ewh-semt/contaminants/lead-plomb/asked_questions-questions_posees-eng.php

Application

Corotech® Epoxy Thinner is for use with all 2-part solvent-based epoxy coatings and for effective cleaning of tools and equipment. It may be used to reduce and thin coatings up to the legal limits allowed by district.

Environmental Health & Safety Information

DANGER!

Harmful if swallowed

Causes skin irritation

Causes serious eye damage

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Highly flammable liquid and vapour

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dust/fume/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces, no smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep cool.

Response: If exposed or concerned get medical attention.

If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician. If skin irritation occurs get medical attention. If on skin (or hair) take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. If inhaled remove victim to fresh air and keep at rest in a position comfortable for breathing. If swallowed immediately call a POISON CENTER or physician. Do NOT induce vomiting. Rinse mouth. In case of fire use CO₂, dry chemical, or foam for extinction.

Storage: Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents/container to an approved waste disposal plant.

KEEP OUT OF REACH OF CHILDREN

Refer to Safety Data Sheet for additional health and safety information.

